

Package: CRediTas (via r-universe)

August 30, 2026

Type Package
Title Generate CRediT Author Statements
Version 0.3.0.9000
Description A tiny package to generate CRediT author statements (<<https://credit.niso.org/>>). It provides three functions: create a template, read it back and generate the CRediT author statement in a text file.
License MIT + file LICENSE
Encoding UTF-8
LazyData true
URL <https://github.com/ropensci/CRediTas/>,
<https://docs.ropensci.org/CRediTas/>,
<https://github.com/ropensci/CRediTas>
BugReports <https://github.com/ropensci/CRediTas/issues>
RoxygenNote 7.2.3
Suggests knitr, rmarkdown, rvest, testthat (>= 3.0.0)
Config/testthat/edition 3
VignetteBuilder knitr
Repository <https://ropensci.r-universe.dev>
Date/Publication 2025-08-25 11:42:15 UTC
RemoteUrl <https://github.com/ropensci/CRediTas>
RemoteRef master
RemoteSha b904e1da4736873e6061e6d7e75c371f6f60a000

Contents

cras_write	2
roles_get	3
template_create	3
template_read	4

cras_write	<i>Write CRediT author statement</i>
------------	--------------------------------------

Description

The function transforms the information in the template (from `template_create`) to a raw string following the CRediT authors statement format of "author1: contributions author2: contributions ..."

Usage

```
cras_write(
  cras_table,
  file,
  drop_authors = TRUE,
  overwrite = FALSE,
  markdown = TRUE,
  quiet = FALSE
)
```

Arguments

<code>cras_table</code>	A data.frame created using <code>create_template()</code>
<code>file</code>	The text file to be created. If not provided (default), the statement is returned as a string instead of written to a file.
<code>drop_authors</code>	If TRUE (default) the authors without contributions are removed from the statement. If FALSE, they are kept without contributions assigned.
<code>overwrite</code>	If TRUE, the file is overwritten. Otherwise, a error is triggered.
<code>markdown</code>	If TRUE (default), the authors are surrounded by <code>**</code> to make them bold in mark-down.
<code>quiet</code>	If TRUE and <code>drop_authors</code> is also TRUE, authors without contributions are silently dropped out. If FALSE, a warning is triggered in case any authors is dropped out.

Value

A text file with the CRediT authors statement or, if `file` is NULL (default), a character vector of length 1 with the statement that can be used in a Rmarkdown or quarto document using inline code: ``r cras_write(cras_table, markdown = TRUE)``

Examples

```
# Generate a template and populate it (randomwly for this example)
cras_table <- template_create(authors = c("Josep Maria", "Jane Doe"))
cras_table[,2:ncol(cras_table)] <- sample(0:1, (ncol(cras_table)-1)*2,
                                           replace = TRUE)

# Create a temporary file just for this example
file <- tempfile()

# Write to the file
cras_write(cras_table, file, markdown = TRUE)

# Check the content of the file
readLines(file)
```

roles_get	<i>Get default roles for CRediT</i>
-----------	-------------------------------------

Description

Get default roles for CRediT

Usage

```
roles_get()
```

template_create	<i>Create a template to fill the CRediT author statement.</i>
-----------------	---

Description

Create a template to fill the CRediT author statement. (<https://credit.niso.org>). The template is a table where the authors are the rows and the columns are the roles.

Usage

```
template_create(authors, file, roles = roles_get())
```

Arguments

authors	A character vector with all the authors to be included in the statement.
file	If a path is provided, the template is saved as a csv for excel
roles	A character vector with the roles to be included in the statement. If NULL, it uses all the roles defined in the CRediT author statement.

Details

The dataframe can be edited in R or, if file is provided, it is exported to a csv to be edited manually in your preferred csv editor. The csv is created to be compatible with Microsoft Excel, since it is the most popular spreadsheet software among scientists. Therefore, it is separated by semicolon.

Value

A dataframe with a row for each author and a column for each role, filled with zeros.

Examples

```
template_create(authors = c("Josep Maria", "Jane Doe"))
```

template_read	<i>Read a template from a csv file</i>
---------------	--

Description

The template should be created using `create_template()`

Usage

```
template_read(file)
```

Arguments

file	A character vector with the path to the csv file
------	--

Value

a data.frame with the content of the csv file

Examples

```
# Create a temporary file for this example
file <- tempfile()

# Create a template and save it to a csv file
template_create(authors = c("Josep Maria", "Jane Doe"), file = file)

# Read the template back (in real life once it has been populated)
template_read(file)
```

Index

cras_write, [2](#)

roles_get, [3](#)

template_create, [3](#)

template_read, [4](#)