

Package: RefManageR (via r-universe)

December 19, 2024

Version 1.4.3

Title Straightforward 'BibTeX' and 'BibLaTeX' Bibliography Management

Maintainer Mathew W. McLean <mathew.w.mclean@gmail.com>

Description Provides tools for importing and working with bibliographic references. It greatly enhances the 'bibentry' class by providing a class 'BibEntry' which stores 'BibTeX' and 'BibLaTeX' references, supports 'UTF-8' encoding, and can be easily searched by any field, by date ranges, and by various formats for name lists (author by last names, translator by full names, etc.). Entries can be updated, combined, sorted, printed in a number of styles, and exported. 'BibTeX' and 'BibLaTeX' '.bib' files can be read into 'R' and converted to 'BibEntry' objects. Interfaces to 'NCBI Entrez', 'CrossRef', and 'Zotero' are provided for importing references and references can be created from locally stored 'PDF' files using 'Poppler'. Includes functions for citing and generating a bibliography with hyperlinks for documents prepared with 'RMarkdown' or 'RHTML'.

License GPL-2 | GPL-3 | BSD_3_clause + file LICENSE

Imports xml2, jsonlite, utils, plyr, tools, httr, lubridate (>= 1.5.0), stringr, stringi, R.utils, methods, bibtex (>= 0.4.1)

Suggests knitr, markdown, testthat

Encoding UTF-8

Depends R (>= 3.0)

VignetteBuilder knitr

BugReports <https://github.com/ropensci/RefManageR/issues>

URL <https://github.com/ropensci/RefManageR/>,
<https://docs.ropensci.org/RefManageR/>

RoxygenNote 7.3.2

Config/pak/sysreqs libicu-dev libxml2-dev libssl-dev

Repository <https://ropensci.r-universe.dev>

RemoteUrl <https://github.com/ropensci/RefManager>

RemoteRef master

RemoteSha d616da567dd8581adff235db3cd4ab766394736e

Contents

| | |
|----------------------------------|----|
| +BibEntry | 3 |
| as.BibEntry | 4 |
| as.data.frame.BibEntry | 6 |
| BibEntry | 7 |
| BibOptions | 10 |
| c.BibEntry | 12 |
| Cite | 13 |
| GetBibEntryWithDOI | 16 |
| GetPubMedByID | 17 |
| GetPubMedRelated | 18 |
| head.BibEntry | 19 |
| levels.BibEntry | 20 |
| LookupPubMedID | 21 |
| names<-.BibEntry | 22 |
| open.BibEntry | 23 |
| print.BibEntry | 24 |
| ReadBib | 25 |
| ReadCrossRef | 27 |
| ReadGS | 29 |
| ReadPDFs | 31 |
| ReadPubMed | 32 |
| ReadZotero | 33 |
| RelistBibEntry | 35 |
| sort.BibEntry | 36 |
| toBiblatex | 38 |
| UpdateFieldName | 40 |
| WriteBib | 41 |
| [.BibEntry | 42 |
| [<-.BibEntry | 44 |
| [.BibEntry | 46 |
| [[<-.BibEntry | 47 |
| \$.BibEntry | 48 |
| \$<-.BibEntry | 49 |

Index

50

`+.BibEntry`*Merge two BibEntry objects while discarding duplicates*

Description

Merges two BibEntry objects comparing only the specified fields to detect duplicates, thus it can be made less strict than using duplicated, unique, etc. Attributes are also merged and keys are ensured to be unique. merge and + simply provide different interfaces for merging.

Usage

```
## S3 method for class 'BibEntry'
e1 + e2

## S3 method for class 'BibEntry'
merge(
  x,
  y,
  fields.to.check = BibOptions()$merge.fields.to.check,
  ignore.case = BibOptions()$ignore.case,
  ...
)
```

Arguments

| | |
|-----------------|---|
| e1 | BibEntry object |
| e2 | BibEntry object to be merged with e1 |
| x | BibEntry object |
| y | BibEntry object |
| fields.to.check | character vector; which BibLaTeX fields should be checked to determine if an entry is a duplicate? Can include "bibtype" to check entry type and "key" to check entry keys. Specifying "all" checks all fields using duplicated . |
| ignore.case | logical; if TRUE, case is ignored when determining if fields are duplicates. |
| ... | ignored |

Value

an object of class BibEntry

Author(s)

McLean, M. W. <mathew.w.mclean@gmail.com>

See Also

[duplicated](#), [unique](#)

Other operators: [\\$.BibEntry\(\)](#), [\\$<-.BibEntry\(\)](#), [\[.BibEntry\(\)](#), [\[<-.BibEntry\(\)](#), [\[\[.BibEntry\(\)](#), [\[\[<-.BibEntry\(\)](#), [c.BibEntry\(\)](#)

Examples

```

if (requireNamespace("bibtex")) {
  file.name <- system.file("Bib", "biblatexExamples.bib", package="RefManager")
  bib <- suppressMessages(ReadBib(file.name))
  bib1 <- bib[seq_len(44)]
  bib2 <- bib[45:length(bib)]

  ## The following is FALSE because the parent entry of one entry in bib1
  ##   is in bib2, so the child entry is expanded in the BibEntry object
  ##   returned by `[` to include the fields inherited from the dropped parent
  identical(merge(bib1, bib2, 'all'), bib)
  toBiblatex(bib1[[1L]])
  toBiblatex(bib[[1L]])

  ## Alternatively, the operator `[[` for BibEntry objects does not expand
  ##   cross references
  bib1 <- bib[[seq_len(44)]]
  bib2 <- bib[[45:length(bib)]]
  identical(merge(bib1, bib2, 'all'), bib)

  ## Not strict enough
  invisible(merge(bib1, bib2, c('title', 'date')))
}

## New publications of R.J. Carroll from Google Scholar and Crossref
## Not run:
if (requireNamespace("bibtex")) {
  bib1 <- ReadGS(scholar.id = "CJOHNoQAAAAJ", limit = '10', sort.by.date = TRUE)
  bib2 <- ReadCrossRef(query = "rj carroll", limit = 10, sort = "relevance",
    min.relevance = 80)
  oldopt <- BibOptions(merge.fields.to.check = "title")
  rjc.new.pubs <- bib1 + bib2
  BibOptions(oldopt)
}

## End(Not run)

```

as.BibEntry

Coerce to a BibEntry object

Description

Functions to check if an object is a BibEntry, or coerce it if possible.

Usage

```
as.BibEntry(x)
```

```
is.BibEntry(x)
```

Arguments

x any R object.

Details

as.BibEntry is able to coerce suitably formatted character vectors, [bibentry](#) objects, lists, and data.frames to BibEntry objects. See the examples.

Value

as.BibEntry - if successful, an object of class BibEntry.

is.BibEntry - logical; TRUE if x is a BibEntry object.

Note

Each entry to be coerced should have a bibtype, key, and all required fields for the specified bibtype.

See Also

[BibEntry](#)

Examples

```
if (requireNamespace("bibtex")) {
  file.name <- system.file("Bib", "biblatexExamples.bib", package="RefManager")
  bib <- suppressMessages(ReadBib(file.name))[[20:21]]
  identical(as.BibEntry(unlist(bib)), bib) ## see also RelistBibEntry

  identical(as.BibEntry(unclass(bib)), bib)

  identical(as.BibEntry(as.data.frame(bib)), bib)
}

bib <- c(bibtype = "article", key = "mclean2014", title = "My New Article",
  author = "Mathew W. McLean", journaltitle = "The Journal", date = "2014-01")
as.BibEntry(bib)

bib <- bibentry(bibtype = "article", key = "mclean2014", title = "My New Article",
  journal = "The Journal", year = 2014, author = "Mathew W. McLean")
print(bib, .bibstyle = "JSS")
as.BibEntry(bib)

bib <- list(c(bibtype = "article", key = "mclean2014a", title = "My New Article",
  author = "Mathew W. McLean", journaltitle = "The Journal", date = "2014-01"),
  c(bibtype = "article", key = "mclean2014b", title = "Newer Article",
```

```
  author = "Mathew W. McLean", journaltitle = "The Journal", date = "2014-02"))
as.BibEntry(bib)
```

```
as.data.frame.BibEntry
```

Coerce to a Data Frame

Description

Coerces a BibEntry object to a data.frame, with each row of the data frame being a field present in at least one entry in the BibEntry object being coerced.

Usage

```
## S3 method for class 'BibEntry'
as.data.frame(x, row.names = NULL, optional = FALSE, ...)
```

Arguments

| | |
|-----------|---------------------|
| x | - a BibEntry object |
| row.names | - ignored |
| optional | - ignored |
| ... | - ignored |

Value

a data.frame object with row names giving the keys, and first column giving entry type.

See Also

[BibEntry](#), [as.BibEntry](#)

Examples

```
bib <- list(c(bibtype = "article", key = "mclean2014a", title = "My New Article",
  author = "Mathew W. McLean", journaltitle = "The Journal", date = "2014-01"),
  c(bibtype = "article", key = "mclean2014b", volume = 10, title = "My Newer Article",
  author = "Mathew W. McLean", journaltitle = "The Journal", date = "2014-02"))
bib <- as.BibEntry(bib)
as.data.frame(bib)
```

Description

Provides a new class `BibEntry` which builds on `bibentry` to provide enhanced functionality for representing, manipulating, importing, etc. bibliographic information in BibTeX or BibLaTeX style.

Usage

```
BibEntry(
    bibtype,
    textVersion = NULL,
    header = NULL,
    footer = NULL,
    key = NULL,
    ...,
    other = list(),
    mheader = NULL,
    mfooter = NULL
)
```

Arguments

| | |
|--------------------------|---|
| <code>bibtype</code> | a character string with a BibTeX entry type. See Entry Types for details. |
| <code>textVersion</code> | a character string with a text representation of the reference to optionally be employed for printing. |
| <code>header</code> | a character string with optional header text. |
| <code>footer</code> | a character string with optional footer text. |
| <code>key</code> | a character string giving the citation key for the entry. |
| <code>...</code> | arguments of the form <code>tag = value</code> giving the fields of the entry, with <code>tag</code> and <code>value</code> the name and value of the field, respectively. Arguments with empty values are dropped. See Entry Fields for details. |
| <code>other</code> | list; additional way to specify fields and their values |
| <code>mheader</code> | string; optional “outer” header text |
| <code>mfooter</code> | string; optional “outer” footer text |

Details

The `BibEntry` objects created by `BibEntry` can represent an arbitrary positive number of references, as with `bibentry`, but many additional methods are defined for building and manipulating a database of references.

Value

an object of class BibEntry

Entry Types

bibentry creates "bibentry" objects, which are modeled after BibLaTeX and BibTeX entries. The entry should be a valid BibLaTeX or BibTeX entry type. For a list of valid BibTeX entry types, see [bibentry](#). BibLaTeX supports all entry types from BibTeX for backwards compatibility. BibLaTeX defines following entry types '

- *article* - An article in a journal, magazine, newspaper, or other periodical which forms a self-contained unit with its own title. Required fields: author, title, journal/journaltitle, year/date.
- *book* - A single-volume book with one or more authors where the authors share credit for the work as a whole. Required fields: author, title, year/date. (Also covers BibTeX @inbook).
- *mvbook* - A multi-volume *book*. For backwards compatibility, multi-volume books are also supported by the entry type @book. Required fields: author, title, year/date.
- *inbook* - A part of a book which forms a self-contained unit with its own title. Note that the profile of this entry type is different from standard BibTeX. Required fields: author, title, booktitle, year/date
- *bookinbook* This type is similar to *inbook* but intended for works originally published as a stand-alone book.
- *suppbook* - Supplemental material in a *book*. This type is closely related to the *inbook* entry type.
- *booklet* - A book-like work without a formal publisher or sponsoring institution. Required fields: author/editor, title, year/date.
- *collection* - A single-volume collection with multiple, self-contained contributions by distinct authors which have their own title. Required fields: editor, title, year/date.
- *mvcollection* - A multi-volume *collection*. Also supported by *collection*. Required fields: editor, title, year/date.
- *incollection* - A contribution to a collection which forms a self-contained unit with a distinct author and title. Required fields: author, editor, title, booktitle, year/date.
- *suppcollection* - Supplemental material in a *collection*.
- *manual* - Technical or other documentation, not necessarily in printed form. Required fields: author/editor, title, year/date
- *misc* - A fallback type for entries which do not fit into any other category. Required fields: author/editor, title, year/date
- *online* - An online resource. Required fields: author, title, number, year/date.
- *patent* - A patent or patent request. Required fields: author, title, number, year/date.
- *periodical* - A complete issue of a periodical, such as a special issue of a journal. Required fields: editor, title, year/date
- *suppperiodical* - Supplemental material in a *periodical*.
- *proceedings* - A single-volume conference proceedings. Required fields: editor, title, year/date.
- *mvproceedings* - A multi-volume @proceedings entry. Required fields: editor, title, year/date.

- *inproceedings* - An article in a conference proceedings. Required fields: author, editor, title, booktitle, year/date.
- *reference* - A single-volume work of reference such as an encyclopedia or a dictionary. Alias for *collection* in standard styles.
- *mvreference* - A multi-volume *reference* entry.
- *inreference* - An article in a work of reference. Alias for *incollection* in most styles.
- *report* - A technical report, research report, or white paper published by a university or some other institution. Required fields: author, title, type, institution, year/date.
- *set* - An entry set. This entry type is special, see BibLaTeX manual.
- *thesis* - A thesis written for an educational institution to satisfy the requirements for a degree. Use the type field to specify the type of thesis. Required fields: author, title, type, institution, year/date.
- *unpublished* A work with an author and a title which has not been formally published, such as a manuscript or the script of a talk. Required fields: author, title, year/date.
- *xdata* - This entry type is special. *xdata* entries hold data which may be inherited by other entries. (Biber only.)
- *custom[a-f]* Custom types (up to five) for special bibliography styles. Not used by the standard styles.

Note

Date fields are parsed using the locale specified by `Sys.getlocale("LC_TIME")` (relevant when specifying a character 'month' field, instead of the recommended integer format)

Name list fields (author, editor, etc.) should be specified as they would be for BibTeX/BibLaTeX; e.g. `author = "Doe, Jane and Smith, Bob A."`.

Author(s)

McLean, M. W. <mathew.w.mclean@gmail.com>

References

BibLaTeX manual <http://mirrors.ibiblio.org/CTAN/macros/latex/contrib/biblatex/doc/biblatex.pdf>

See Also

[bibentry](#)

Examples

```
BibEntry(bibtype = "Article", key = "mclean2014", title = "An Article Title",
  author = "McLean, Mathew W. and Wand, Matt P.", journaltitle = "The Journal Title",
  date = "2014-02-06", pubstate = "forthcoming")
bib <- BibEntry(bibtype = "XData", key = "arxiv_data", eprinttype = "arxiv",
  eprintclass = "stat.ME", year = 2013, urldate = "2014-02-01", pubstate = "submitted")
bib <- c(bib, BibEntry(bibtype = "Misc", key = "mclean2014b",
```

```

title = "Something On the {arXiv}", author = "Mathew W. McLean", eprint = "1312.9999",
xdata = "arxiv_data", url = "https://arxiv.org/abs/1310.5811")
bib
toBiblatex(bib)

```

BibOptions

Set options/hooks for RefManageR

Description

This function is used to access and set package options for RefManageR, similar to `options`. The options are listed in the details

Usage

```
BibOptions(..., restore.defaults = FALSE)
```

Arguments

`...` a character vector or strings specifying option names to access; or to set options values, a named list or vector of option values or options specified in name=value pairs.

`restore.defaults` logical; if TRUE, `...`'s are ignored and all package options are restored to their defaults.

Details

The following are valid package options.

Options for searching/indexing a BibEntry object. See [\[.BibEntry](#) and [\[<-.BibEntry](#)

1. `match.author` - string; controls how name list fields (author, editor, translator, etc.) are matched when searching for names. "family.with.initials" require family names and given name initials to match, "exact" requires names to match exactly, and any other value results in only family names being compared (the default).
2. `match.date` - string; controls how date fields are matched when searching. If "year.only" (the default), only years are checked for equality when comparing dates, otherwise months and days will also be compared, if they are available.
3. `use.regex` - logical; if TRUE, regular expressions are used when searching non-date fields; otherwise, exact matching is used.
4. `ignore.case` - logical; if TRUE, case is ignored when searching.
5. `return.ind` - logical; if TRUE the return value of `SearchBib` and the operators [\[.BibEntry](#), will be the indices of any matches; otherwise, a BibEntry object is returned.

Options for Printing with [print.BibEntry](#) and [PrintBibliography](#)

1. `bib.style` - string; Biblatex bibliography style to use when printing and formatting a `BibEntry` object. Possible values are “numeric” (default), “authoryear”, “authortitle”, “alphabetic”, “draft”.
2. `first.inits` - logical; if TRUE, only given name initials are displayed when printing; otherwise, full names are used.
3. `dashed` - logical; if TRUE and `bib.style = "authoryear"` or `bib.style = "authortitle"`, recurring author and editor names are replaced with “—” when printing.
4. `sorting` - string; controls how `BibEntry` objects are sorted. Possible values are “nty”, “nyt”, “nyvt”, “anyt”, “anyvt”, “ynt”, “ydnf”, “none”, “debug”; see [sort.BibEntry](#)
5. `max.names` - numeric; maximum number of names to display before using “et al.” when formatting and printing name list fields. This is also the minimum number of names that will be displayed if “et al.” is used (corresponding to the ‘minnames’ package option in Biblatex). See below and option `longnamesfirst` when using this argument with the citation functions ([Citet](#), etc.).
6. `no.print.fields` character vector; fields that should not be printed, e.g., doi, url, isbn, etc.
7. `style` - character string naming the printing style. Possible values are plain text (style “text”), BibTeX (“Bibtex”), BibLaTeX (“Biblatex”), a mixture of plain text and BibTeX as traditionally used for citations (“citation”), HTML (“html”), LaTeX (“latex”), “markdown”, “yaml”, R code (“R”), and a simple copy of the `textVersion` elements (style “textVersion”, see [BibEntry](#))

Options for the [Cite](#) functions

1. `cite.style` - character string; bibliography style to use to generate citations.
2. `style` - as above, but used to format the citations.
3. `hyperlink` - character string or logical; for use with `style = "markdown"` and `style = "html"` (ignored otherwise). If FALSE, no hyperlink will be generated for the citation or in the bibliography when printing. If set equal to “to.bib”, then hyperlinks will be generated linking the citation and bibliography. The default value, “to.doc”, will try to create the hyperlink using the `url`, `doi`, or `eprint` fields of entry. If these fields are not available, the hyperlink will point to the bibliography. See also [open.BibEntry](#).
4. `super` - logical; should superscripts be used for numeric citations? Ignored if `cite.style != "numeric"`.
5. `max.names` - numeric; same as above, except for citations. Note, that the first time a reference is cited, this option will be ignored if `longfirstnames` is TRUE.
6. `longnamesfirst` logical; should the first time a citation appears in the text not be truncated at `max.names`?
7. `bibpunct` - character vector; punctuation to use in a citation. The entries in `bibpunct` are as follows
 - (a) The left delimiter for non-alphabetic and non-numeric citation styles
 - (b) The right delimiter for non-alphabetic and non-numeric citation styles
 - (c) The left delimiter for alphabetic and numeric citation styles
 - (d) The right delimiter for alphabetic and numeric citation styles
 - (e) The separator between references in a citation.
 - (f) Punctuation to go between the author and year.

Other

1. `check.entries` - string or FALSE; if FALSE entries are not checked to ensure that they have all the required fields for the type of entry; if “warn” then entries are checked, but only a warning is issued and the entry is processed anyway; otherwise an error is produced if an entry does not have the required fields (default). Note that the majority of fields listed as required for a particular entry type in the Biblatex manual are not actually required for Biblatex to produce an entry.
2. `merge.fields.to.check` - character vector; for `merge.BibEntry` and the operator `+.BibEntry`, the fields that should be checked when comparing entries for equality when merging BibEntry objects. Specifying “all” results in all fields be checked with `duplicated`. The default is “key” to only check for duplicated keys.

Value

if a vector of option names is supplied, the current value of the requested options, or if ... is missing, all current option values; otherwise, when setting options the old values of the changed options are (invisibly) returned as a list.

Note

If ... is missing and `restore.defaults = FALSE`, all options and their current values will be returned as a list.

See Also

`print.BibEntry`, `BibEntry`, `options`

Examples

```
BibOptions()
BibOptions("first.inits", "bib.style")

oldopts <- BibOptions(first.inits = FALSE, bib.style = "authoryear")
oldopts
BibOptions(oldopts)

BibOptions(restore.defaults = TRUE)
```

c.BibEntry

Combine BibEntry objects.

Description

Combines multiple BibEntry objects into a single one.

Usage

```
## S3 method for class 'BibEntry'
c(..., recursive = FALSE)
```

Arguments

... - BibEntry objects to be concatenated.
 recursive - logical; ignored.

Value

a single BibEntry object.

Note

c will remove all attributes besides class.

No checking for duplicate entries is performed though keys will be made unique.

See Also

Other operators: `$.BibEntry()`, `$<- .BibEntry()`, `+ .BibEntry()`, `[.BibEntry()`, `[<- .BibEntry()`, `[[.BibEntry()`, `[[<- .BibEntry()`

Examples

```
bib <- c(BibEntry(bibtype = "article", key = "mclean2014a", title = "My New Article",
  author = "Mathew W. McLean", journaltitle = "The Journal", date = "2014-01"),
  BibEntry(bibtype = "article", key = "mclean2014b",
  title = "My Newer Article", author = "Mathew W. McLean", journaltitle = "The Journal",
  date = "2014-02"))
```

 Cite

Cite a BibEntry object in text and print all citations

Description

The Cite functions allow for citing a BibEntry object in text. The PrintBibliography function allows for printing the bibliography of all the cited entries. The NoCite function adds references to the bibliography without including a citation. These functions are most useful when used in, e.g., a RMarkdown or RHTML document.

Usage

```
Cite(bib, ..., textual = FALSE, before = NULL, after = NULL, .opts = list())
```

```
PrintBibliography(bib, .opts = list(), start = 1, end = length(bib))
```

```
Citep(bib, ..., before = NULL, after = NULL, .opts = list())
```

```
AutoCite(bib, ..., before = NULL, after = NULL, .opts = list())
```

```
Citet(bib, ..., before = NULL, after = NULL, .opts = list())
```

```
TextCite(bib, ..., before = NULL, after = NULL, .opts = list())
```

```
NoCite(bib, ..., .opts = list())
```

Arguments

| | |
|----------------------|---|
| <code>bib</code> | a <code>BibEntry</code> or <code>bibentry</code> object |
| <code>...</code> | passed to <code>SearchBib</code> for indexing into <code>bib</code> . A character vector of keys, for example. |
| <code>textual</code> | logical; if <code>TRUE</code> , a “textual” citation is produced, i.e. what is produced by <code>\citet</code> in <code>natbib</code> and <code>\textcite</code> in <code>BibLaTeX</code> ; otherwise, a parenthetical citation as <code>\citep</code> and <code>\autocite</code> . |
| <code>before</code> | string; optional text to display before the citation. |
| <code>after</code> | string; optional text to display after the citation. |
| <code>.opts</code> | list; See the relevant section in <code>BibOptions</code> for a description of all valid options for these functions. |
| <code>start</code> | Integer; specifying the index of the first citation to print. Useful for printing long bibliographies on multiple pages/slides. |
| <code>end</code> | Integer; specifying the index of the last citation to print. Useful for printing long bibliographies on multiple pages/slides. |

Details

See the package vignettes and execute the examples below.

If `bib.style = "alphabetic"` or `bib.style = "numeric"`, then sorting needs to be done at the start of the document prior to using a cite function as sorting is not done by the `PrintBibliography` function for those styles (specifying `sorting` in `.opts` is ignored in this case). If no sorting is done, the references are listed in the order they were cited in for those two styles.

If the `...` argument to `NoCite` is identical to `"*"`, then all references in `bib` are added to the bibliography without citations.

Value

For the cite functions: a character string containing the citation

`PrintBibliography`: The formatted list of references.

`NoCite`: no return value; invoked for its side-effect.

See Also

[print.BibEntry](#), [BibOptions](#), [citeNatbib](#), the package vignettes `bib <-`

Examples

```

if (requireNamespace("bibtex")) {
  file <- system.file("Bib", "biblatexExamples.bib", package = "RefManager")
  BibOptions(check.entries = FALSE)
  bib <- ReadBib(file)
  Citet(bib, 12)
  NoCite(bib, title = "Alkanethiolate")
  PrintBibliography(bib, .opts = list(style = "latex",
                                     bib.style = "authoryear"))
}
## Not run:
if (requireNamespace("bibtex")){
  Citep(bib, c("loh", "geer"), .opts = list(cite.style = "numeric",
                                           before = "see e.g., "))
  Citet(bib, "loh", .opts = list(cite.style = "numeric", super = TRUE))
  AutoCite(bib, eprinttype = "arxiv", .opts = list(cite.style = "authoryear"))
  AutoCite(bib, eprinttype = "arxiv", .opts = list(cite.style = "pandoc"))
  Citep(bib, author = "kant")
  ## shorthand field in both entries gets used for numeric and alphabetic labels
  TextCite(bib, author = "kant", .opts = list(cite.style = "alphabetic"))
  TextCite(bib, author = "kant", .opts = list(cite.style = "numeric"))
  TextCite(bib, author = "kant", .opts = list(cite.style = "alphabetic",
                                             style = "html"))
  punct <- unlist(BibOptions("bibpunct"))
  punct[3:4] <- c("(", ")")
  TextCite(bib, 33, .opts = list(bibpunct = punct, cite.style = "alphabetic"))

  BibOptions(restore.defaults = TRUE)
}

## End(Not run)
## Not run:
library(knitr)
## See also TestNumeric.Rmd and TestAlphabetic.Rmd for more examples
old.dir <- setwd(tdir <- tempdir())
doc <- system.file("Rmd", "TestRmd.Rmd", package = "RefManager")
file.show(doc)
tmpfile <- tempfile(fileext = ".html", tmpdir = tdir)
knit2html(doc, tmpfile)
browseURL(tmpfile)

doc <- system.file("Rhtml", "TestAuthorYear.Rhtml", package = "RefManager")
file.show(doc)
tmpfile <- tempfile(fileext = ".html", tmpdir = tdir)
knit2html(doc, tmpfile)
browseURL(tmpfile)
setwd(old.dir)
unlink(tdir)

## End(Not run)

```

GetBibEntryWithDOI *Lookup a Bibtex entry using a Digital Object Identifier*

Description

Uses the DOI System API to look up bibliography information given a set of DOIs.

Usage

```
GetBibEntryWithDOI(  
  doi,  
  temp.file = tempfile(fileext = ".bib"),  
  delete.file = TRUE  
)
```

Arguments

| | |
|-------------|--|
| doi | character vector; DOIs to use to retrieve bibliographic information. |
| temp.file | string; a file to write the Bibtex data returned by the DOI System to. |
| delete.file | logical; should temp.file be deleted when the function exits? |

Details

The bibliographic information returned by the search of the <https://www.doi.org/> API is temporarily written to a file and then read back into R and return as a BibEntry object.

Value

an object of class BibEntry.

References

<https://www.doi.org/tools.html>

See Also

[ReadCrossRef](#), [BibEntry](#)

Examples

```
if (interactive() && !httr::http_error("https://www.doi.org/"))  
  GetBibEntryWithDOI(c("10.1016/j.iheduc.2003.11.004", "10.3998/3336451.0004.203"))
```

| | |
|---------------|---|
| GetPubMedByID | <i>Retrieve citation information from NCBI's Entrez for a set of PubMed IDs</i> |
|---------------|---|

Description

Uses NCBI's E-Utilities to retrieve bibliographic information given a vector of PubMed ID's and returns the results as a BibEntry object.

Usage

```
GetPubMedByID(id, db = "pubmed", ...)
```

Arguments

| | |
|-----|---|
| id | character vector; PubMed ID's for searching NCBI's Entrez. |
| db | string; Entrez database to search. |
| ... | additional parameters to use for the search. See the Entrez documentation listed in the <i>References</i> . |

Value

a BibEntry object.

Note

Returned entries will have bibtype "Article" or "Book", unless a collection title is present – in which case the bibtype will be "InBook" – or there is no journal information returned for an article – in which case the bibtype will be "Misc".

References

<https://www.ncbi.nlm.nih.gov/books/NBK25500/>

See Also

Other pubmed: [GetPubMedRelated\(\)](#), [LookupPubMedID\(\)](#), [ReadCrossRef\(\)](#), [ReadPubMed\(\)](#)

Examples

```
if (interactive() && !httr::http_error("https://eutils.ncbi.nlm.nih.gov/"))
  GetPubMedByID(c("11209037", "21245076"))
```

GetPubMedRelated *Retrieve related articles from PubMed using PubMed ID's*

Description

Searches PubMed for articles related to a set of PubMed ID's using NCBI's E-Utilities.

Usage

```
GetPubMedRelated(
  id,
  database = "pubmed",
  batch.mode = TRUE,
  max.results = 10,
  return.sim.scores = FALSE,
  return.related.ids = FALSE
)
```

Arguments

| | |
|---------------------------------|---|
| <code>id</code> | either a character vector of PubMed ID's or a BibEntry object, which is expected to have at least some entries with <code>eprinttype = "pubmed"</code> and <code>eprint</code> field specifying a PubMed ID. |
| <code>database</code> | string; the Entrez database to search |
| <code>batch.mode</code> | logical; if TRUE, the PubMed IDs in <code>id</code> are combined by Entrez when searching for linked IDs so that only one set of linked IDs is returned. If FALSE, a set of linked IDs is obtained for each ID in <code>id</code> . will be returned |
| <code>max.results</code> | numeric vector; the maximum number of results to return if <code>batch.mode</code> TRUE; or if <code>batch.mode</code> is FALSE, this should have the same length as <code>id</code> with each element giving the maximum number of results to return for the corresponding ID. |
| <code>return.sim.scores</code> | logical; Entrez returns a similarity score with each returned citation giving a measure of how similar the returned entry is to the ones specified by the query. If TRUE these scores are added to the returned BibEntry object in a field called 'score'. |
| <code>return.related.ids</code> | logical; should the original PubMed ID(s) that a returned entry is related to be stored in a field called 'PMIDrelated'. |

Value

an object of class BibEntry.

References

<https://www.ncbi.nlm.nih.gov/books/NBK25500/>

See Also

Other pubmed: [GetPubMedByID\(\)](#), [LookupPubMedID\(\)](#), [ReadCrossRef\(\)](#), [ReadPubMed\(\)](#)

Examples

```
if (interactive() && !http::http_error("https://eutils.ncbi.nlm.nih.gov/")){
  file.name <- system.file("Bib", "RJC.bib", package="RefManager")
  bib <- ReadBib(file.name)
  bib <- LookupPubMedID(bib[[101:102]])
  toBiblatex(GetPubMedRelated(bib, batch.mode = TRUE, max.results = 2,
  return.sim.scores = TRUE, return.related.ids = TRUE))
  GetPubMedRelated(bib, batch.mode = FALSE, max.results = c(2, 2))
}
```

| | |
|---------------|---|
| head.BibEntry | <i>Return the first or last part of a BibEntry object</i> |
|---------------|---|

Description

Prints the first or last entries of a BibEntry object (via [message](#)) and returns them *invisibly* (via [invisible](#)).

Usage

```
## S3 method for class 'BibEntry'
head(x, n = 6L, suppress.messages = TRUE, ...)

## S3 method for class 'BibEntry'
tail(x, n = 6L, suppress.messages = TRUE, ...)
```

Arguments

| | |
|-------------------|--|
| x | an object of class <code>BibEntry</code> . |
| n | a single integer. If positive, size for the resulting object: number of elements for a vector (including lists), rows for a matrix or data frame or lines for a function. If negative, all but the n last/first number of elements of x. |
| suppress.messages | boolean; should the head/tail entries be printed via message ? |
| ... | arguments to be passed to or from other methods. |

Details

If `suppress.messages` is `FALSE`, the head/tail entries are output to the console along with some additional formatting for the ‘bibtype’ and ‘key’, in addition to invisibly returning the entries.

Value

an object of class `BibEntry`.

Examples

```
if (requireNamespace("bibtex")) {  
  file <- system.file("Bib", "biblatexExamples.bib", package = "RefManager")  
  BibOptions(check.entries = FALSE)  
  bib <- ReadBib(file)  
  tail(bib, 2, suppress.messages = FALSE)  
  bib <- head(bib, 1, suppress.messages = TRUE)  
}
```

| | |
|-----------------|--|
| levels.BibEntry | <i>Extract all fields present in a BibEntry object</i> |
|-----------------|--|

Description

These functions return a list of all fields present in a BibEntry object.

Usage

```
## S3 method for class 'BibEntry'  
levels(x)  
  
fields(x)
```

Arguments

x a BibEntry object.

Value

a list with the same length as x of character vectors giving the fields present in each entry of a BibEntry object.

Note

The only difference between fields and levels is that levels returns a list with element names corresponding to entry keys.

Examples

```
bib <- as.BibEntry(list(c(bibtype = "Article", key = "mclean2014a", title = "My New Article",  
  author = "Mathew W. McLean",  
  journaltitle = "The Journal", date = "2014-01"), c(bibtype = "Book", key = "mclean2014b",  
  title = "My New Book", editor = "Mathew W. McLean", ISBN = "247123837", date = "2014-02")))  
fields(bib)  
levels(bib)
```

| | |
|----------------|---|
| LookupPubMedID | <i>Retrieve PubMed ID's for a BibEntry object</i> |
|----------------|---|

Description

Uses the NCBI E-utilities to search for PubMed ID's for citations stored in a BibEntry object.

Usage

```
LookupPubMedID(bib, index)
```

Arguments

| | |
|-------|---|
| bib | a bibentry object |
| index | indices specifying which entries of bib will be searched for. If missing, all entries are searched for. |

Details

For each entry a citation string is created using the fields journaltitle/journal, date/year, volume, pages, and author; and these strings are then used to search the NCBI database for PubMed ID's.

If an ID is found for an entry, the entry is updated so that the eprinttype field is assigned the value "pubmed" and the eprint field is assigned the ID.

Value

a BibEntry object - bib with additional eprinttype and eprint fields when the search is successful for an entry.

See Also

Other pubmed: [GetPubMedByID\(\)](#), [GetPubMedRelated\(\)](#), [ReadCrossRef\(\)](#), [ReadPubMed\(\)](#)

Examples

```
if (interactive() && !httr::http_error("https://eutils.ncbi.nlm.nih.gov/")){
  file.name <- system.file("Bib", "RJC.bib", package = "RefManageR")
  bib <- ReadBib(file.name)
  LookupPubMedID(bib[[101:102]])
}
```

| | |
|------------------|--|
| names<-.BibEntry | <i>Names (keys) of a BibEntry object</i> |
|------------------|--|

Description

Functions to get and set the keys of an object of class BibEntry

Usage

```
## S3 replacement method for class 'BibEntry'  
names(x) <- value  
  
## S3 method for class 'BibEntry'  
names(x)
```

Arguments

| | |
|-------|--|
| x | an object of class BibEntry |
| value | character vector of new key values to replace into x |

Value

names<- the updated BibEntry object.
names - character vector of the keys of the BibEntry object.

Author(s)

McLean, M. W. <mathew.w.mclean@gmail.com>

Examples

```
if (requireNamespace("bibtex")) {  
  bib <- ReadBib(system.file("Bib", "test.bib", package = "RefManager"))  
  names(bib)  
  names(bib)[1] <- 'newkey'  
}
```

| | |
|---------------|--|
| open.BibEntry | <i>Open BibEntry in PDF viewer or web browser.</i> |
|---------------|--|

Description

Attempts to open a connection to an entry in a BibEntry object using fields such as 'file', 'DOI', 'eprint' + 'eprinttype', and 'URL'.

Usage

```
## S3 method for class 'BibEntry'
open(
  con,
  entry = 1L,
  open.field = c("file", "url", "eprint", "doi"),
  viewer,
  ...
)
```

Arguments

| | |
|------------|--|
| con | BibEntry object to extract connections from. |
| entry | numeric index or character key of entry in bib to open. |
| open.field | character vector of fields to use in bib to open the BibEntry. Possible fields are any combination of "file", "url", "eprint", or "doi". "eprint" is implemented for eprinttype= "JSTOR", "PubMed", or "arXiv". When multiple fields are specified, they are tried in the order they appear in the vector. |
| viewer | character string giving the name of the program to be used as hypertext browser. It should be in the PATH, or a full path specified. Alternatively, an R function to be called to invoke the browser. Defaults to getOptions("pdfviewer") if open.field = "file" and getOptions("browser"), otherwise. |
| ... | not used. |

Author(s)

McLean, M. W. <mathew.w.mclean@gmail.com>

See Also

[browseURL](#)

Examples

```
## Not run:
if (requireNamespace("bibtex")) {
  testbib <- ReadBib(system.file("REFERENCES.bib", package="bibtex"))
  open(testbib)
```

```

    testbib$file <- file.path(R.home("doc/manual"), "R-intro.pdf")
    open(testbib)
}

## End(Not run)

```

`print.BibEntry` *Print BibLaTeX bibliography Entries*

Description

Prints bibliographic information stored in `BibEntry` objects in BibLaTeX style

Usage

```

## S3 method for class 'BibEntry'
print(x, .opts = list(), ...)

```

Arguments

| | |
|--------------------|--|
| <code>x</code> | a <code>BibEntry</code> object |
| <code>.opts</code> | a list of formatting options from BibOptions . Possible options are <ul style="list-style-type: none"> <code>style</code> - character string naming the printing style. Possible values are plain text (style "text"), BibTeX ("Bibtex"), BibLaTeX ("Biblatex"), a mixture of plain text and BibTeX as traditionally used for citations ("citation"), HTML ("html"), LaTeX ("latex"), "markdown", "yaml", R code ("R"), and a simple copy of the textVersion elements (style "textVersion", see BibEntry) <code>bib.style</code> - character string specifying BibLaTeX style to use for formatting references. Possible values are "numeric" (default), "authoryear", "authortitle", "alphabetic", "draft". See section 3.3.2 of the BibLaTeX manual. <code>sorting</code> - how should the entries in <code>x</code> be sorted? See sort.BibEntry. <code>max.names</code> - maximum number of names to display for name list fields before truncation with "et al." <code>first.inits</code> - logical; if true only initials of given names are printed, otherwise full names are used. <code>dashed</code> - logical; for <code>.bibstyle = "authoryear"</code> or <code>.bibstyle = "authoryear"</code> only, if TRUE duplicate author and editor lists are replaced with "—" when printed. <code>no.print.fields</code> character vector; fields that should not be printed, e.g., doi, url, isbn, etc. |
| <code>...</code> | extra parameters to pass to the renderer. |

Note

setting `max.names` to value is equivalent to setting `maxnames=value` and `minnames=value` in BibLaTeX.

Custom BibLaTeX styles may be defined using the function `bibstyle`. To fully support BibLaTeX, the created environment must have functions for formatting each of the entry types described in `BibEntry`.

References

Lehman, Philipp and Kime, Philip and Boruvka, Audrey and Wright, J. (2013). The biblatex Package. <http://mirrors.ibiblio.org/CTAN/macros/latex/contrib/biblatex/doc/biblatex.pdf>.

See Also

`BibEntry`, `ReadBib`, `sort.BibEntry`

Examples

```
if (requireNamespace("bibtex")) {
  file.name <- system.file("Bib", "biblatexExamples.bib", package="RefManager")
  bib <- suppressMessages(ReadBib(file.name))
  print(bib[author="aristotle"], .opts = list(bib.style = "numeric"))
  print(bib[55:57], .opts = list(bib.style = "authortitle", first.inits = FALSE))
  print(bib[80:88], .opts = list(bib.style = "alphabetic", max.names = 1,
    no.print.fields = "issn"))
  print(bib[32:36], .opts = list(bib.style = "draft"))
  oldopts <- BibOptions(bib.style = "authoryear", dashed = TRUE, sorting = "ydnt")
  bib[editor = "westfahl"]
  BibOptions(oldopts)
}
```

ReadBib

BibLaTeX/BibTeX .bib file parser

Description

Parser for bibliography databases in the bib format containing either BibLaTeX or BibTeX entries.

Usage

```
ReadBib(
  file,
  .Encoding = "UTF-8",
  header = if (length(preamble)) paste(preamble, sep = "\n") else "",
  footer = "",
  check = BibOptions()$check.entries
)
```

Arguments

| | |
|-----------|--|
| file | string; bib file to parse. |
| .Encoding | encoding |
| header | header of the citation list. By default this is made from the Preamble entries found in the bib file. |
| footer | footer of the citation list. |
| check | “error”, “warn”, or logical FALSE. What action should be taken if an entry is missing required fields? FALSE means no checking is done, “warn” means entry is added with an error. “error” means the entry will not be added. See BibOptions . |

Note

Date fields are parsed using the locale specified by `Sys.getlocale("LC_TIME")`. To read a bib file with character ‘month’ fields in a language other than the current locale, `Sys.setlocale` should be used to change ‘LC_TIME’ to match the bib file before calling `ReadBib`.

Keys will be made unique by calling `make.unique` with `sep = ":"`.

Author(s)

McLean, M. W., based on code in bibtex package by Francois, R.

See Also

[read.bib](#) in package bibtex

Examples

```

bib.text <- "@Manual{mclean2014,
  author = {Mathew William McLean},
  title = {Straightforward Bibliography Management in R Using the RefManager Package},
  note = {arXiv: 1403.2036 [cs.DL]},
  year = {2014},
  url = {https://arxiv.org/abs/1403.2036},
}"
tfile <- tempfile(fileext = ".bib")
writeLines(bib.text, tfile)
ReadBib(tfile)
unlink(tfile)
## Not run:
  file.name <- system.file("Bib", "RJC.bib", package="RefManagerR")
  bib <- ReadBib(file.name)

## End(Not run)

```

ReadCrossRef *Search CrossRef for citations.*

Description

Provides an interface to the CrossRef API, searching for citations given a string query. Results are written to a bib file, read back into R using [WriteBib](#), and returned as a `BibEntry` object.

Usage

```
ReadCrossRef(
  query = "",
  filter = list(),
  limit = 5,
  offset = 0,
  sort = "relevance",
  year = NULL,
  min.relevance = 2,
  temp.file = tempfile(fileext = ".bib"),
  delete.file = TRUE,
  verbose = FALSE,
  use.old.api = FALSE
)
```

Arguments

| | |
|----------------------------|--|
| <code>query</code> | string; search term |
| <code>filter</code> | named list of possible filters; see Details and References ; ignored if <code>use.old.api = TRUE</code> |
| <code>limit</code> | numeric; maximum number of entries to return |
| <code>offset</code> | numeric; CrossRef will not return the first <code>offset</code> results (default 0); ignored if <code>use.old.api = TRUE</code> |
| <code>sort</code> | string; how specifying how the results from CrossRef should be sorted. Possible values when <code>use.old.api = FALSE</code> are "score" (default; same as "relevance"), "updated", "deposited", "indexed", or "published"; see the references |
| <code>year</code> | numeric; if specified, only results from this year will be returned. |
| <code>min.relevance</code> | numeric; only results with a CrossRef-assigned relevance score at least this high will be returned. |
| <code>temp.file</code> | string; file name to use for storing Bibtex information returned by CrossRef. |
| <code>delete.file</code> | boolean; should the bib file be deleted on exit? |
| <code>verbose</code> | boolean; if TRUE, additional messages are output regarding the results of the query. |
| <code>use.old.api</code> | boolean; should the older CrossRef API be used for the search? NO LONGER SUPPORTED , all queries need to use the new API. |

Details

When `use.old.api = TRUE`, the query HTTP request only returns DOIs, which are then used to make HTTP requests for the corresponding BibTeX entries from CrossRef; when `use.old.api = FALSE`, the query HTTP request is parsed to create the BibEntry object (i.e. there are less HTTP requests when using the new API).

CrossRef assigns a score between 0 and 100 based on how relevant a reference seems to be to your query. The *old* API documentation warns that while false negatives are unlikely, the search can be prone to false positives. Hence, setting `min.relevance` to a high value may be necessary if `use.old.api = TRUE`. In some instances with the old API, no score is returned, if this happens, the entries are added with a message indicating that no score was available.

Possible values for the *names* in `filter` are "has-funder", "funder", "prefix", "member", "from-index-date", "until-index-date", "from-deposit-date", "until-deposit-date", "from-update-date", "until-update-date", "from-created-date", "until-created-date", "from-pub-date", "until-pub-date", "has-license", "license.url", "license.version", "license.delay", "has-full-text", "full-text.version", "full-text.type", "public-references", "has-references", "has-archive", "archive", "has-orcid", "orcid", "issn", "type", "directory", "doi", "updates", "is-update", "has-update-policy", "container-title", "publisher-name", "category-name", "type-name", "award.number", "award.funder", "assertion-group", "assertion", "affiliation", "has-affiliation", "alternative-id", and "article-number". See the first reference for a description of their meanings.

Value

An object of class `BibEntry`.

Note

The entries returned by CrossRef are frequently missing fields required by BibTeX, if you want the entries to be returned anyway, set `BibOptions()$check.entries` to `FALSE` or "warn"

Fields "score" (the relevancy score) and "license" will be returned when `use.old.api = FALSE`.

References

Newer API: https://github.com/CrossRef/rest-api-doc/blob/master/rest_api.md, Older API: <https://search.crossref.org/help/api>

See Also

[ReadZotero](#), [BibEntry](#), package `rcrossref` for larger queries and deep paging

Other pubmed: [GetPubMedByID\(\)](#), [GetPubMedRelated\(\)](#), [LookupPubMedID\(\)](#), [ReadPubMed\(\)](#)

Examples

```
if (interactive() && !httr::http_error("https://search.crossref.org/")){
  BibOptions(check.entries = FALSE)
  ## 3 results from the American Statistical Association involving "regression"
  ReadCrossRef("regression", filter = list(prefix="10.1198"), limit = 3)
```

```

## Some JRSS-B papers published in 2010 or later, note the quotes for filter
## names with hypens
ReadCrossRef(filter = list(issn = "1467-9868", "from-pub-date" = 2010),
              limit = 2, min.relevance = 0)

## Articles published by Institute of Mathematical Statistics
ReadCrossRef(filter = list(prefix = "10.1214"), limit = 5, min.relevance = 0)

## old API
ReadCrossRef(query = 'rj carroll measurement error', limit = 2, sort = "relevance",
              min.relevance = 80, use.old.api = TRUE)

ReadCrossRef(query = 'carroll journal of the american statistical association',
              year = 2012, limit = 2, use.old.api = TRUE)
}

```

| | |
|--------|---|
| ReadGS | <i>Import book and article references from a public Google Scholar profile by ID.</i> |
|--------|---|

Description

This function will create a BibEntry object for up to 100 references from a provided Google Scholar ID, if the profile is public. The number of citations for each entry will also be imported.

Usage

```

ReadGS(
  scholar.id,
  start = 0,
  limit = 100,
  sort.by.date = FALSE,
  .Encoding = "UTF-8",
  check.entries = BibOptions()$check.entries
)

```

Arguments

| | |
|--------------|--|
| scholar.id | character; the Google Scholar ID from which citations will be imported. The ID can be found by visiting an author's Google Scholar profile and noting the value in the uri for the "user" parameter. |
| start | numeric; index of first citation to include. |
| limit | numeric; maximum number of results to return. Cannot exceed 100. |
| sort.by.date | boolean; if true, newest citations are imported first; otherwise, most cited works are imported first. |
| .Encoding | character; text encoding to use for importing the results and creating the bib entries. |

`check.entries` What should be done with incomplete entries (those containing “...” due to long fields)? Either FALSE to add them anyway, “warn” to add with a warning, or any other value to drop the entry with a message and continue processing the remaining entries.

Details

This function creates BibTeX entries from an author’s Google Scholar page. If the function finds numbers corresponding to volume/number/pages of a journal article, an ‘Article’ entry is created. If an arXiv identifier is found, a ‘Misc’ entry is created with `eprint`, `eprinttype`, and `url` fields. Otherwise, a ‘TechReport’ entry is created; unless the entry has more than ten citations, in which case a ‘Book’ entry is created.

Long author lists, long titles, and long journal/publisher names can all lead to these fields being incomplete for a particular entry. When this occurs, these entries are either dropped or added with a warning depending on the value of the `check.entries` argument.

Value

An object of class `BibEntry`. If the entry has any citations, the number of citations is stored in a field ‘`cites`’.

Note

Read Google’s Terms of Service before using.

It is not possible to automatically import BibTeX entries directly from Google Scholar as no API is available and this violates their Terms of Service.

See Also

[BibEntry](#)

Examples

```
if (interactive() && !httr::http_error("https://scholar.google.com")){
  ## R. J. Carroll's ten newest publications
  ReadGS(scholar.id = "CJOHNoQAAAAJ", limit = 10, sort.by.date = TRUE)

  ## Matthias Katzfu\ss
  BibOptions(check.entries = "warn")
  kat.bib <- ReadGS(scholar.id = "vqW0UqUAAAAJ")

  ## retrieve GS citation counts stored in field 'cites'
  kat.bib$cites
}
```

Description

This function creates bibliographic information by reading the Metadata and text of PDFs stored in a user specified directory using Poppler (<https://poppler.freedesktop.org/>). IF requested, the function first searches for DOIs and downloads BibTeX entries from [ReadCrossRef](#) if DOIs are found. If this is not requested or a DOI is not found for an entry, an attempt is made to build a BibTeX entry from the metadata and text.

Usage

```
ReadPDFs(
  path,
  .enc = "UTF-8",
  recursive = TRUE,
  use.crossref = TRUE,
  use.metadata = TRUE,
  progress = FALSE
)
```

Arguments

| | |
|---------------------------|---|
| <code>path</code> | character; path to directory containing pdfs or filename of one pdf. <code>normalizePath</code> is used on the specified path |
| <code>.enc</code> | character; text encoding to use for reading pdf and creating <code>BibEntry</code> object. Available encodings for Poppler can be found using <code>system("pdftools -listenc")</code> . The encoding must also be listed in <code>iconvlist()</code> . |
| <code>recursive</code> | logical; same as <code>list.files</code> . Should pdfs in subdirectories of path be used? |
| <code>use.crossref</code> | logical; should an attempt be made to download bibliographic information from CrossRef if any Document Object Identifiers (DOIs) are found? This is only supported if the Suggestet package <code>bibtex</code> is found. |
| <code>use.metadata</code> | logical; should the PDF metadata also be used to help create entries? |
| <code>progress</code> | logical; should progress bar be generated when fetching from CrossRef? |

Details

This function requires that the `pdftools` utility from Poppler PDF <https://poppler.freedesktop.org/> be installed.

This function will create only `Article` or `Misc` BibTeX entries.

The absolute path to each file will be stored in the bib entry in a field called 'file', which is recognized by BibLaTeX (though not printed by any standard style) and can be used by the `open.BibEntry` function to open the PDF in the default viewer.

If the keywords metadata field is available, it will be added to the bib entry in a field 'keywords', which is recognized by BibLaTeX.

Value

An object of class `BibEntry`.

References

<https://poppler.freedesktop.org/>

See Also

[ReadCrossRef](#), [BibEntry](#), [open.BibEntry](#)

Examples

```
## Not run:  
path <- system.file("doc", package = "RefManager")  
ReadPDFs(path)  
  
## End(Not run)
```

ReadPubMed

Search NCBI's E-Utilities for citation information

Description

This function takes a query and searches an Entrez database for references using NCBI's E-Utilities, returning the results in a `BibEntry` object.

Usage

```
ReadPubMed(query, database = "PubMed", ...)
```

Arguments

| | |
|-----------------------|---|
| <code>query</code> | string; search term. |
| <code>database</code> | string; the Entrez database to search. |
| <code>...</code> | additional parameters to use for the search. See the <i>Details</i> . |

Details

Optional additional parameters to pass to the server include

- `restart` - index of the first retrieved ID that should be included in the results.
- `retmax` - maximum number of IDs the server will return (default 20).
- `field` - limits the query to search only the specified field (e.g. "title").
- `datatype` - type of date to use when limiting search by dates. E.g. "mdat" for modification date or "pdat" for publication date.

- reldate - integer; only items that have (datatype) date values within reldate *days* of the current date will be returned.
- mindate, maxdate - date ranges to restrict search results. Possible formats are “YYYY”, “YYYY/MM”, and “YYYY/MM/DD”.

Value

an object of class BibEntry.

Note

The returned entries will have type either ‘Article’ or ‘Misc’ depending on whether journal information was retrieved. See the Entrez documentation listed in the *References*.

The language of the entry will be returned in the field “language” and the abstract will be returned in the field “abstract”, if they are available.

References

<https://www.ncbi.nlm.nih.gov/books/NBK25499/#chapter4.ESearch>

See Also

Other pubmed: [GetPubMedByID\(\)](#), [GetPubMedRelated\(\)](#), [LookupPubMedID\(\)](#), [ReadCrossRef\(\)](#)

Examples

```
if (interactive() && !httr::http_error("https://eutils.ncbi.nlm.nih.gov/"))
  ReadPubMed(query = "raymond carroll measurement error", retmax = 5, mindate = 1990)
```

ReadZotero

Get Bibliography Information From a Zotero Library.

Description

Get Bibliography Information From a Zotero Library.

Usage

```
ReadZotero(
  user,
  group,
  .params,
  temp.file = tempfile(fileext = ".bib"),
  delete.file = TRUE
)
```

Arguments

| | |
|-------------|---|
| user | Zotero userID for use in calls to the Zotero API. This is not the same as your Zotero username. The userID for accessing user-owned libraries can be found at https://www.zotero.org/settings/keys after logging in. |
| group | Zotero groupID for use in calls to the Zotero API. Only one of user and group should be specified; group will be ignored if both are specified. |
| .params | A <i>named</i> list of parameters to use in requests to the Zotero API with possible values <ul style="list-style-type: none"> • q - Search string to use to search the library • qmode - Search mode. Default is "titleCreatorYear". Use "everything" to include full-text content in search. • key - API key. This must be specified to access non-public libraries. • collection - name of a specific collection within the library to search • itemType - type of entry to search for; e.g., "book" or "journalArticle" • tag - name of tag to search for in library • limit - maximum number of entries to return • start - index of first entry to return |
| temp.file | character; file name where the BibTeX data returned by Zotero will be temporarily written. |
| delete.file | boolean; should temp.file be removed on exit? |

Value

An object of class BibEntry

References

https://www.zotero.org/support/dev/server_api/v2/read_requests

See Also

[BibEntry](#)

Examples

```
## Not run:
## first two entries in library with bayesian in title
ReadZotero(user = "1648676", .params = list(q = "bayesian",
  key = "7lhgvcwVq60CDi7E68FyE3br", limit=2))

## Search specific collection
## collection key can be found by reading uri when collection is selected in Zotero
ReadZotero(user = "1648676", .params=list(q = "yu", key = "7lhgvcwVq60CDi7E68FyE3br",
  collection = "3STEQRNU"))

## Search by tag
## Notice the issue with how Zotero uses a TechReport entry for arXiv manuscripts
## This is one instance where the added fields of BibLaTeX are useful
```

```

ReadZotero(user = "1648676", .params=list(key = "7lhgvcwVq60CDi7E68FyE3br",
  tag = "Statistics - Machine Learning"))

## To read these in you must set check.entries to FALSE or "warn"
old.opts <- BibOptions(check.entries = FALSE)
length(ReadZotero(user = "1648676", .params = list(key = "7lhgvcwVq60CDi7E68FyE3br",
  tag = "Statistics - Machine Learning")))

## Example using groups
ReadZotero(group = "13495", .params = list(q = "Schmidhuber",
  collection = "QU23T27Q"))
BibOptions(old.opts)

## End(Not run)

```

RelistBibEntry

Flatten and unflatten BibEntry objects

Description

RelistBibEntry unflattens a BibEntry object that has been flattened with unlist.

unlist flattens a BibEntry object to a single list where every field (including bibtype and key) of every entry is a separate element in the list.

Usage

```
RelistBibEntry(flesh, skeleton = NULL)
```

```
## S3 method for class 'BibEntry'
unlist(x, recursive = FALSE, use.names = TRUE)
```

Arguments

| | |
|-----------|-----------------------------------|
| flesh | list; an unlisted BibEntry object |
| skeleton | currently ignored |
| x | a BibEntry object to flatten |
| recursive | ignored. |
| use.names | ignored. |

Details

RelistBibEntry is only intended for use with unlisted BibEntry objects.

Value

RelistBibEntry - an object of class BibEntry

For unlist, a list with bib entries collapsed into a single list.

Note

The names of the list elements from an unlisted BibEntry object will not be unique. To do this see [make.unique](#).

See Also

[as.BibEntry](#)

Examples

```
bib <- list(c(bibtype = "article", key = "mclean2014a", title = "My New Article",
  author = "Mathew W. McLean", journaltitle = "The Journal", date = "2014-01"),
  c(bibtype = "article", key = "mclean2014b", title = "My Newer Article",
  author = "Mathew W. McLean", journaltitle = "The Journal", date = "2014-02"))
bib <- as.BibEntry(bib)
unlist(bib)
RelistBibEntry(unlist(bib))
```

sort.BibEntry

Sort a BibEntry Object

Description

Sorts a BibEntry object by specified fields. The possible fields used for sorting and the order they are used in correspond with the options available in BibLaTeX.

Usage

```
## S3 method for class 'BibEntry'
sort(
  x,
  decreasing = FALSE,
  sorting = BibOptions()$sorting,
  .bibstyle = BibOptions()$bib.style,
  ...
)
```

Arguments

| | |
|------------|--|
| x | an object of class <code>BibEntry</code> |
| decreasing | logical; should the sort be increasing or decreasing? |
| sorting | sort method to use, see Details . |
| .bibstyle | bibliography style; used when sort is called by print.BibEntry |
| ... | internal use only |

Details

The possible values for argument `sort` are

- `nty` - sort by name, then by title, then by year
- `nyt` - sort by name, then by year, then title
- `nyvt` - sort by name, year, volume, title
- `anyt` - sort by alphabetic label, name, year, title
- `anyvt` - sort by alphabetic label, name, year, volume, title
- `ynt` - sort by year, name, title
- `ydnt` - sort by year (descending), name, title
- `debug` - sort by keys
- `none` - no sorting is performed

All sorting methods first consider the field `presort`, if available. Entries with no `presort` field are assigned `presort` value “mm”. Next the `sortkey` field is used.

When sorting by name, the `sortname` field is used first. If it is not present, the `author` field is used, if that is not present `editor` is used, and if that is not present `translator` is used. All of these fields are affected by the value of `max.names` in `.BibOptions()``$max.names`.

When sorting by title, first the field `sorttitle` is considered. Similarly, when sorting by year, the field `sortyear` is first considered.

When sorting by volume, if the field is present it is padded to four digits with leading zeros; otherwise, the string “0000” is used.

When sorting by alphabetic label, the labels that would be generating with the “alphabetic” `bibstyle` are used. First the shorthand field is considered, then `label`, then `shortauthor`, `shorteditor`, `author`, `editor`, and `translator`. Refer to the BibLaTeX manual Sections 3.1.2.1 and 3.5 and Appendix C.2 for more information.

Value

the sorted `BibEntry` object

References

Lehman, Philipp and Kime, Philip and Boruvka, Audrey and Wright, J. (2013). The `biblatex` Package. <http://mirrors.ibiblio.org/CTAN/macros/latex/contrib/biblatex/doc/biblatex.pdf>.

See Also

[BibEntry](#), [print.BibEntry](#), [order](#)

Examples

```

if (requireNamespace("bibtex")) {
  file.name <- system.file("Bib", "biblatexExamples.bib", package="RefManager")
  bib <- suppressMessages(ReadBib(file.name)[[70:73]])
  BibOptions(sorting = "none")
  bib
  sort(bib, sorting = "nyt")
  sort(bib, sorting = "ynt")
  BibOptions(restore.defaults = TRUE)
}

```

toBiblatex

Convert BibEntry objects to BibTeX or BibLaTeX

Description

toBiblatex converts a BibEntry object to character vectors with BibLaTeX markup. toBibtex will convert a BibEntry object to character vectors with BibTeX markup, converting some BibLaTeX fields and all entry types that are not supported by BibTeX to ones that are supported.

Usage

```
toBiblatex(object, encoded.names.to.latex = TRUE, ...)
```

```

## S3 method for class 'BibEntry'
toBibtex(
  object,
  note.replace.field = c("urldate", "pubstate", "addendum"),
  extra.fields = NULL,
  encoded.names.to.latex = TRUE,
  ...
)

```

Arguments

| | |
|------------------------|---|
| object | an object of class BibEntry to be converted |
| encoded.names.to.latex | if TRUE (the default) then name list fields such as ‘author’ and ‘editor’ will have non-ASCII characters translated to LaTeX escape sequences. |
| ... | ignored |
| note.replace.field | a character vector of BibLaTeX fields. When converting an entry to BibTeX, the first field in the entry that matches one specified in this vector will be added to the note field, <i>if</i> the note field is not already present |
| extra.fields | character vector; fields that are not supported in standard BibTeX styles are by default dropped in the result return by the toBibtex function. Any fields specified in extra.fields will <i>not</i> be dropped if present in an entry. |

Details

toBiblatex converts the BibEntry object to a vector containing the corresponding BibLaTeX file, it ensures the name list fields (e.g. author and editor) are formatted properly to be read by bibtex and biber and otherwise prints all fields as is, thus it is similar to [toBibtex](#).

toBibtex will attempt to convert BibLaTeX entries to a format that can be read by bibtex. Any fields not supported by bibtex are dropped unless they are specified in `extra.fields`. The fields below, if they are present, are converted as described and added to a bibtex supported field, unless that field is already present.

- `date` - The date field, if present will be truncated to a year and added to the `year` field, if it is not already present. If a month is specified with the date, it will be added to the `month` field.
- `journaltitle` - Will be changed to `journal`, if it is not already present
- `location` - Will be changed to `address`
- `institution` - Converted to `school` for thesis entries
- `sortkey` - Converted to `key`
- `maintitle` - Converted to `series`
- `issuetitle` - Converted to `booktitle`
- `eventtitle` - Converted to `booktitle`
- `eprinttype` - Converted to `archiveprefix` (for arXiv references)
- `eprintclass` - Converted to `primaryclass` (for arXiv references)

If no `note` field is present, the `note.replace.field` can be used to specified BibLaTeX fields that can be looked for and added to the `note` field if they are present.

BibLaTeX entry types that are not supported by bibtex are converted by toBibtex as follows "mv-book" = "Book", "bookinbook" = "InBook", "suppbook" = "InBook",

- `MvBook,Collection,MvCollection,Reference,MvReference,Proceedings,MvProceedings,Periodical` - to `Book`
- `BookInBook,SuppBook,InReference,SuppPeriodical` - to `InBook`
- `report,patent` - to `TechReport`
- `SuppCollection` - to `InCollection`
- `thesis` - to `MastersThesis` if `type = mathesis`, else to `PhdThesis`
- `rest` - to `Misc`

Value

an object of class "Bibtex" - character vectors where each element holds one line of a BibTeX or BibLaTeX file

Author(s)

McLean, M. W. <mathew.w.mclean@gmail.com>, Andy Bunn for code for translating non-ASCII characters to LaTeX.

See Also

[toBibtex](#), [BibEntry](#), [print.BibEntry](#)

Examples

```
if (requireNamespace("bibtex")) {  
  file.name <- system.file("Bib", "biblatexExamples.bib", package="RefManager")  
  bib <- suppressMessages(ReadBib(file.name))  
  toBiblatex(bib[70:72])  
  toBibtex(bib[70:72])  
}
```

| | |
|-----------------|---|
| UpdateFieldName | <i>Rename a field in a BibEntry object.</i> |
|-----------------|---|

Description

This function will rename a field, in every entry where it is present, in a BibEntry object.

Usage

```
UpdateFieldName(x, old.field, new.field)
```

Arguments

| | |
|-----------|---|
| x | - a BibEntry object |
| old.field | - string; the current name of the field to be renamed |
| new.field | - string; the new name to replace old.field |

Value

x, with the renamed field.

Examples

```
bib <- as.BibEntry(list(c(bibtype = "article", key = "mclean2014a", title = "My New Article",  
  author = "Mathew W. McLean", journal = "The Journal", date = "2014-01"),  
  c(bibtype = "article", key = "mclean2014b", title = "My Newer Article",  
    author = "Mathew W. McLean", journal = "The Journal", date = "2014-02")))  
bib <- UpdateFieldName(bib, "journal", "journaltitle")  
toBiblatex(bib)
```

| | |
|----------|---|
| WriteBib | <i>Create a BibTeX File from a BibEntry Object e Creates a Bibtex File from a BibEntry object for use with either BibTeX or BibLaTeX.</i> |
|----------|---|

Description

Create a BibTeX File from a BibEntry Object e Creates a Bibtex File from a BibEntry object for use with either BibTeX or BibLaTeX.

Usage

```
WriteBib(
  bib,
  file = "references.bib",
  biblatex = TRUE,
  append = FALSE,
  verbose = TRUE,
  ...
)
```

Arguments

| | |
|----------|---|
| bib | a BibEntry object to be written to file |
| file | character string naming a file, should; end in “.bib”. Can be NULL, in which case the BibEntry object will be written to stdout . |
| biblatex | boolean; if TRUE, toBiblatex is used and no conversions of the BibEntry object are done; if FALSE entries will be converted as described in toBibtex.BibEntry . |
| append | as in <code>write.bib</code> in package <code>bibtex</code> |
| verbose | as in <code>write.bib</code> in package <code>bibtex</code> |
| ... | additional arguments passed to writeLines |

Value

bib - invisibly

Note

To write the contents of bib “as is”, the argument `biblatex` should be TRUE, otherwise conversion is done as in [toBibtex.BibEntry](#).

Author(s)

McLean, M. W. based on `write.bib` by Gaujoux, R. in package `bibtex`.

See Also

`write.bib` in package `bibtex`, [ReadBib](#), [toBibtex.BibEntry](#), [toBiblatex](#), [BibEntry](#)

Examples

```

if (requireNamespace("bibtex")){
  bib <- BibEntry("Article", key = "Carroll_2012",
                 doi = "10.1080/01621459.2012.699793",
                 year = "2012", month = "sep",
                 volume = 107, number = 499,
                 pages = {1166--1177},
                 author = "R. Carroll and A. Delaigle and P. Hall",
                 title = "Deconvolution When Classifying Noisy Data ...",
                 journal = "Journal of the American Statistical Association")

  ## Write bib if no server error and bibtex available
  if (length(bib)){
    tfile <- tempfile(fileext = ".bib")
    WriteBib(bib, tfile, biblatex = TRUE)
    identical(ReadBib(tfile), bib)
    unlink(tfile)
  }
}

```

[.BibEntry

Search BibEntry objects by field

Description

Allows for searching and indexing a `BibEntry` object by fields, including names and dates. The extraction operator and the `SearchBib` function simply provide different interfaces to the same search functionality.

Usage

```

## S3 method for class 'BibEntry'
x[i, j, ..., drop = FALSE]

SearchBib(x, .opts = list(), ...)

```

Arguments

| | |
|------------------|--|
| <code>x</code> | an object of class <code>BibEntry</code> |
| <code>i</code> | A named list or character vector of search terms with names corresponding to the field to search for the search term. Alternatively, a vector of entry key values or numeric or logical indices specifying which entries to extract. |
| <code>j</code> | A named list or character vector, as <code>i</code> . Entries matching the search specified by <code>i</code> <i>OR</i> matching the query specified by <code>j</code> will be return |
| <code>...</code> | arguments in the form <code>bib.field = search.term</code> , or as <code>j</code> lists or character vectors for additional searches. For <code>SearchBib</code> , can alternatively have same form as <code>i</code> . |

| | |
|-------|--|
| drop | logical, should attributes besides class be dropped from result? |
| .opts | list of search options with name = value entries. Any option described in BibOptions is valid, with the following being the most relevant ones <ul style="list-style-type: none"> • use.regex - logical; are the search terms regular expressions or should exact matching be used? • ignore.case - logical; should case be ignored when comparing strings? • match.date - how should the date fields date, urldate, eventdate, and origdate. Default is “year.only”, so that months and days in dates are ignored when comparing. Currently, specifying any other value results the full date being used. See the Note section. • match.author - character string; how should name fields be searched? If “family.only”, only family names are compared; if “family.with.initials”, family name and given name initials are used; if “exact”, full names are used. • return.ind - logical; if TRUE the returned object is numeric indices of match locations; otherwise, a BibEntry object is returned |

Value

an object of class `BibEntry` (the results of the search/indexing), *or* if `BibOptions()$return.ind=TRUE`, the indices in `x` that match the search terms.

Note

The arguments to the `SearchBib` function that control certain search features can also be changed for the extraction operator by changing the corresponding option in the `.BibOptions` object; see [BibOptions](#).

See Also

Other operators: `$.BibEntry()`, `$<- .BibEntry()`, `+.BibEntry()`, `[<- .BibEntry()`, `[.BibEntry()`, `[[<- .BibEntry()`, `c.BibEntry()`

Examples

```
file.name <- system.file("Bib", "biblatexExamples.bib", package="RefManagerR")
bib <- suppressMessages(ReadBib(file.name))

## author search, default is to use family names only for matching
bib[author = "aristotle"]

## Aristotle references before 1925
bib[author="aristotle", date = "/1925"]

## Aristotle references before 1925 *OR* references with editor Westfahl
bib[list(author="aristotle", date = "/1925"),list(editor = "westfahl")]

## Change some searching and printing options and search for author
old.opts <- BibOptions(bib.style = "authoryear", match.author = "exact",
```

```

        max.names = 99, first.inits = FALSE)
bib[author="Mart\u00ednez, Jacinto and S\u00e1nchez, Alberto"]
BibOptions(old.opts) ## reset options

## Not run:
## Some works of Raymond J. Carroll's
file.name <- system.file("Bib", "RJC.bib", package="RefManager")
bib <- ReadBib(file.name)
length(bib)

## index by key
bib[c("chen2013using", "carroll1978distributions")]

## Papers with someone with family name Wang
length(SearchBib(bib, author='Wang', .opts = list(match.author = "family")))

## Papers with Wang, N.
length(SearchBib(bib, author='Wang, N.', .opts = list(match.author = "family.with.initials")))

## tech reports with Ruppert
length(bib[author='ruppert',bibtype="report"])

##Carroll and Ruppert tech reports at UNC
length(bib[author='ruppert',bibtype="report",institution="north carolina"])

## Carroll and Ruppert papers since leaving UNC
length(SearchBib(bib, author='ruppert', date="1987-07/",
                .opts = list(match.date = "exact")))

## Carroll and Ruppert papers NOT in the 1990's
length(SearchBib(bib, author='ruppert', date = "!1990/1999"))
identical(SearchBib(bib, author='ruppert', date = "!1990/1999"),
          SearchBib(bib, author='ruppert', year = "!1990/1999"))
table(unlist(SearchBib(bib, author='ruppert', date="!1990/1999")$year))

## Carroll + Ruppert + Simpson
length(bib[author="Carroll, R. J. and Simpson, D. G. and Ruppert, D."])

## Carroll + Ruppert OR Carroll + Simpson
length(bib[author=c("Carroll, R. J. and Ruppert, D.", "Carroll, R. J. and Simpson, D. G.")])

## Carroll + Ruppert tech reports at UNC "OR" Carroll and Ruppert JASA papers
length(bib[list(author='ruppert',bibtype="report",institution="north carolina"),
            list(author="ruppert",journal="journal of the american statistical association")])

## End(Not run)

```

Description

Assign new values for specified fields in a BibEntry object using a named character vector or list of named character vectors.

Usage

```
## S3 replacement method for class 'BibEntry'
x[i, j, ...] <- value
```

Arguments

| | |
|-------|--|
| x | - a BibEntry object. |
| i | - see [.BibEntry |
| j | - see [.BibEntry |
| ... | - see [.BibEntry |
| value | - values to be assigned to x. To update one entry only, should be a named character vector with names corresponding to fields. To update multiple entries, should be a list of named character vectors. Can also be an object of class BibEntry. |

Details

Date and name list fields should be in the format expected by Biblatex (see [BibEntry](#)).

To clear a field 'field_name' from an entry use field_name = "".

Value

an object of class BibEntry.

See Also

Other operators: [\\$.BibEntry\(\)](#), [\\$<-.BibEntry\(\)](#), [+.BibEntry\(\)](#), [\[.BibEntry\(\)](#), [\[\[.BibEntry\(\)](#), [\[\[<-.BibEntry\(\)](#), [c.BibEntry\(\)](#)

Examples

```
bib.text <- "@Manual{mclean2014,
  author = {Mathew William McLean},
  title = {Straightforward Bibliography Management in R Using the RefManager Package},
  note = {arXiv: 1403.2036 [cs.DL]},
  year = {2014},
  url = {https://arxiv.org/abs/1403.2036},
}"
tfile <- tempfile(fileext = ".bib")
writeLines(bib.text, tfile)
bib <- ReadBib(tfile)
bib[1] <- list(c(date = "2014-03", key = "mwm2014"))
bib
unlink(tfile)
```

```
## Not run:
file.name <- system.file("Bib", "RJC.bib", package="RefManageR")
bib <- ReadBib(file.name)
print(bib[seq_len(3L)], .opts = list(sorting = "none", bib.style = "alphabetic"))
## add month to Serban et al., add URL and urldate to Jennings et al., and
## add DOI and correct journal to Garcia et al.
bib[seq_len(3L)] <- list(c(date="2013-12"),
  c(url="https://bsb.eurasipjournals.com/content/2013/1/13",
    urldate = "2014-02-02"),
  c(doi="10.1093/bioinformatics/btt608",
    journal = "Bioinformatics"))
print(bib[seq_len(3L)], .opts = list(sorting = "none", bib.style = "alphabetic"))
bib2 <- bib[seq_len(3L)]
bib2[2:3] <- bib[5:6]
bib2
bib2[3] <- c(journal='', eprinttype = "arxiv", eprint = "1308.5427",
  eprintclass = "math.ST", pubstate = "submitted", bibtype = "misc")
bib2

## End(Not run)
```

[[.BibEntry

Extract entries from a BibEntry object by index

Description

Operator for extracting BibEntry objects by index.

Usage

```
## S3 method for class 'BibEntry'
x[[i, drop = FALSE]]
```

Arguments

| | |
|------|--|
| x | a BibEntry object |
| i | numeric indices of entries to extract, or a character vector of keys corresponding to the entries to be extracted. |
| drop | logical, should attributes besides class be dropped from result? |

Value

an object of class BibEntry.

Note

This method is different than the usual operator [[] for lists in that a vector of indices may be specified.

This method behaves differently than the [] operator for BibEntry objects in that it does not expand crossreferences when returning, so that a parent entry or xdata entry will be dropped if it is not also indexed when indexing the child entry.

This method is not affected by the value of BibOptions()\$return.ind.

See Also

Other operators: \$.BibEntry(), \$<-.BibEntry(), +.BibEntry(), [.BibEntry(), [<-.BibEntry(), [[<-.BibEntry(), c.BibEntry()

Examples

```
if (requireNamespace("bibtex")) {
  file.name <- system.file("Bib", "biblatexExamples.bib", package="RefManager")
  bib <- suppressMessages(ReadBib(file.name))
  bib[[20:21]]
  bib[c("hyman", "loh")]

  ## Note this is FALSE because [[] does not inherit from the dropped parent entry while [] does.
  identical(bib[1], bib[[1]])
}
```

[[<-.BibEntry

Assign a BibEntry entry to another BibEntry object

Description

Replace one entry in a BibEntry object with another

Usage

```
## S3 replacement method for class 'BibEntry'
x[[i]] <- value
```

Arguments

x - a BibEntry object
i - a numeric index or a string entry key
value - a single entry BibEntry object or an object that can be coerced to BibEntry using [as.BibEntry](#)

Details

This function will replace the specified entry in x with the entry given by value. To replace multiple entries see [\[\[<-.BibEntry](#).

Value

an object of class BibEntry

See Also

Other operators: [\\$.BibEntry\(\)](#), [\\$<-.BibEntry\(\)](#), [+.BibEntry\(\)](#), [\[.BibEntry\(\)](#), [\[<-.BibEntry\(\)](#), [\[\[.BibEntry\(\)](#), [c.BibEntry\(\)](#)

\$.BibEntry

Extract fields from a BibEntry object

Description

used to extract a single field from each entry in a BibEntry object

Usage

```
## S3 method for class 'BibEntry'
x$name
```

Arguments

x an object of class BibEntry
name the field to extract

Value

a named list of values for the field specified by name for each entry; NULL if the field is not present for a particular entry. The names attribute of the returned list contains the entry keys (potentially back-quoted).

Note

name may be “bibtype” to extract entry types or “key” to extract keys.

See Also

Other operators: [\\$<-.BibEntry\(\)](#), [+.BibEntry\(\)](#), [\[.BibEntry\(\)](#), [\[<-.BibEntry\(\)](#), [\[\[.BibEntry\(\)](#), [\[\[<-.BibEntry\(\)](#), [c.BibEntry\(\)](#)

Examples

```
if (requireNamespace("bibtex")) {
  file.name <- system.file("Bib", "biblatexExamples.bib", package="RefManager")
  bib <- suppressMessages(ReadBib(file.name))
  bib[[50:55]]$author
  bib[[seq_len(5)]]$bibtype
}
```

| | |
|-------------------------------|---|
| <code>\$<-.BibEntry</code> | <i>Replace values for a particular field in a BibEntry object</i> |
|-------------------------------|---|

Description

Used to replace the values stored for a specified field in a BibEntry object.

Usage

```
## S3 replacement method for class 'BibEntry'  
x$name <- value
```

Arguments

| | |
|--------------------|--|
| <code>x</code> | a BibEntry object |
| <code>name</code> | string; the field to assign the new values to. |
| <code>value</code> | character vector; the replacement field values to be assigned. |

Value

an object of class BibEntry with the updated fields.

Note

The method expects date and name list fields to be in the format expected by Biblatex. The field specified by name does not have to be one currently in x.

See Also

Other operators: [\\$.BibEntry\(\)](#), [+.BibEntry\(\)](#), [\[.BibEntry\(\)](#), [\[<-.BibEntry\(\)](#), [\[\[.BibEntry\(\)](#), [\[\[<-.BibEntry\(\)](#), [c.BibEntry\(\)](#)

Examples

```
bib <- BibEntry(bibtype = "misc", key = "mclean", author = "Mathew W. McLean",  
  title = "My Work", year = "2012")  
bib$year <- 2014  
bib$author <- "McLean, M. W. and Carroll, R. J."  
bib$url <- "https://example.com"  
bib  
  
bib <- c(bib, as.BibEntry(citation()))  
bib[1]$author[2] <- person(c("Raymond", "J."), "Carroll")  
bib$author
```

Index

- * **IO**
 - toBiblatex, 38
 - WriteBib, 41
- * **attribute**
 - names<- .BibEntry, 22
- * **connection**
 - open.BibEntry, 23
- * **database**
 - [.BibEntry, 42
 - [[.BibEntry, 46
 - BibEntry, 7
 - GetPubMedByID, 17
 - GetPubMedRelated, 18
 - LookupPubMedID, 21
 - ReadCrossRef, 27
 - ReadGS, 29
 - ReadZotero, 33
 - RelistBibEntry, 35
 - toBiblatex, 38
- * **list**
 - [.BibEntry, 42
 - [[.BibEntry, 46
 - RelistBibEntry, 35
- * **manip**
 - [.BibEntry, 42
 - [<- .BibEntry, 44
 - [[.BibEntry, 46
 - RelistBibEntry, 35
 - sort.BibEntry, 36
 - UpdateFieldName, 40
- * **methods**
 - +.BibEntry, 3
 - [<- .BibEntry, 44
 - [[<- .BibEntry, 47
 - \$<- .BibEntry, 49
 - c.BibEntry, 12
 - Cite, 13
 - levels.BibEntry, 20
 - sort.BibEntry, 36
- * **operators**
 - +.BibEntry, 3
 - [.BibEntry, 42
 - [<- .BibEntry, 44
 - [[.BibEntry, 46
 - [[<- .BibEntry, 47
 - \$.BibEntry, 48
 - \$<- .BibEntry, 49
 - c.BibEntry, 12
- * **print**
 - Cite, 13
- * **pubmed**
 - GetPubMedByID, 17
 - GetPubMedRelated, 18
 - LookupPubMedID, 21
 - ReadCrossRef, 27
 - ReadPubMed, 32
- * **utilities**
 - as.BibEntry, 4
 - open.BibEntry, 23
 - ReadPDFs, 31
 - toBiblatex, 38
 - UpdateFieldName, 40
- +.BibEntry, 3, 12, 13, 43, 45, 47–49
- [.BibEntry, 4, 10, 13, 42, 45, 47–49
- [<- .BibEntry, 10, 44
- [[.BibEntry, 4, 13, 43, 45, 46, 48, 49
- [[<- .BibEntry, 47
- \$.BibEntry, 4, 13, 43, 45, 47, 48, 48, 49
- \$<- .BibEntry, 49
- as.BibEntry, 4, 6, 36, 47
- as.data.frame.BibEntry, 6
- AutoCite (Cite), 13
- BibEntry, 5, 6, 7, 11, 12, 16, 24, 25, 28, 30, 32, 34, 37, 40, 41, 45
- bibentry, 5, 7–9
- BibOptions, 10, 14, 24, 26, 43
- bibstyle, 25

- browseURL, 23
- c.BibEntry, 4, 12, 43, 45, 47–49
- Cite, 11, 13
- citeNatbib, 14
- Citep(Cite), 13
- Citet, 11
- Citet(Cite), 13
- duplicate, 3, 4, 12
- fields(levels.BibEntry), 20
- GetBibEntryWithDOI, 16
- GetPubMedByID, 17, 19, 21, 28, 33
- GetPubMedRelated, 17, 18, 21, 28, 33
- head.BibEntry, 19
- invisible, 19
- is.BibEntry(as.BibEntry), 4
- levels.BibEntry, 20
- list.files, 31
- LookupPubMedID, 17, 19, 21, 28, 33
- make.unique, 26, 36
- merge.BibEntry, 12
- merge.BibEntry(+.BibEntry), 3
- message, 19
- names.BibEntry(names<- .BibEntry), 22
- names<- .BibEntry, 22
- NoCite(Cite), 13
- open.BibEntry, 11, 23, 31, 32
- options, 10, 12
- order, 37
- print.BibEntry, 10, 12, 14, 24, 36, 37, 40
- PrintBibliography, 10
- PrintBibliography(Cite), 13
- read.bib, 26
- ReadBib, 25, 25, 41
- ReadCrossRef, 16, 17, 19, 21, 27, 31–33
- ReadGS, 29
- ReadPDFs, 31
- ReadPubMed, 17, 19, 21, 28, 32
- ReadZotero, 28, 33
- RelistBibEntry, 35
- SearchBib, 10, 14
- SearchBib(ℓ.BibEntry), 42
- sort.BibEntry, 11, 24, 25, 36
- stdout, 41
- tail.BibEntry(head.BibEntry), 19
- TextCite(Cite), 13
- toBiblatex, 38, 41
- toBibtex, 39, 40
- toBibtex(toBiblatex), 38
- toBibtex.BibEntry, 41
- unique, 4
- unlist.BibEntry(RelistBibEntry), 35
- UpdateFieldName, 40
- WriteBib, 27, 41
- writeLines, 41