

Package: aeolus (via r-universe)

December 19, 2024

Title Unleash Useful Linebreaks in Markdown Documents

Version 0.0.0.9000

Description Add linebreaks at the end of sentences and remove other linebreaks.

License MIT + file LICENSE

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.2.9000

Imports brio, cli, purrr, rlang, rstudioapi, tinkr (>= 0.2.0.9001), tokenizers, xml2

URL <https://docs.ropensci.org/aeolus/>,
<https://github.com/maelle/aeolus>

BugReports <https://github.com/maelle/aeolus/issues>

Suggests testthat (>= 3.0.0), withr

Config/testthat/edition 3

Remotes ropensci/tinkr

Config/pak/sysreqs libicu-dev libxml2-dev

Repository <https://ropensci.r-universe.dev>

RemoteUrl <https://github.com/ropenscilabs/aeolus>

RemoteRef main

RemoteSha 10cf57b4f1ad4d2607ec411831837a3609fbda4a

Contents

unleash	2
use_sentence_linebreaks	2
Index	3

unleash *Create better line breaks*

Description

Currently `unleash()` only adds line breaks after sentences. For better results, you should also add line breaks after long sentence parts, manually.

Usage

```
unleash(path, new_path = path)
```

Arguments

<code>path</code>	Path to the Markdown file
<code>new_path</code>	Path where to save the new file

Value

Path to the new file (invisibly)

Examples

```
markdown_file <- system.file("example.md", package = "aeolus")
readLines(markdown_file)
unleash(markdown_file)
readLines(markdown_file)
```

`use_sentence_linebreaks`
Set Visual editor's Markdown wrapping option to "Sentence" (RStudio IDE).

Description

Set Visual editor's Markdown wrapping option to "Sentence" (RStudio IDE).

Usage

```
use_sentence_linebreaks(scope = c("user", "project"))
```

Arguments

<code>scope</code>	Edit globally for the current <i>user</i> , or locally for the current <i>project</i> .
--------------------	---

Value

Nothing, used for its side-effects.

Index

`unleash`, [2](#)

`use_sentence_linebreaks`, [2](#)