

Package: brapiR2 (via r-universe)

September 24, 2026

Title A Tidyverse-Native Client for the 'BrAPI' v2 (Breeding API) Specification

Version 0.2.0

Description Provides pipe-friendly, stateless read access to the Breeding API ('BrAPI') v2.1 specification, an open community standard for plant breeding data interchange maintained by the BrAPI project <<https://brapi.org>>. Wraps 32 of the 37 'BrAPI' v2.1 entities across all four modules, Core, Germplasm, Phenotyping, and Genotyping, covering 49 of the specification's 138 retrieval ('GET' and search) endpoints and returning tidy tibbles ready for analysis. Write and update endpoints are out of scope by design. Features include automatic pagination, async search handling, response caching, parallel batch fetching, and convenience functions for genomic selection workflows (e.g. dosage matrix extraction). Designed for plant breeders and bioinformaticians who need programmatic access to plant breeding databases that implement the 'BrAPI' v2 specification.

License MIT + file LICENSE

URL <https://github.com/ropensci/brapiR2>,
<https://docs.ropensci.org/brapiR2/>

BugReports <https://github.com/ropensci/brapiR2/issues>

Encoding UTF-8

Language en-GB

Roxygen list(markdown = TRUE)

Depends R (>= 4.1.0)

Imports cli (>= 3.6.0), dplyr (>= 1.1.0), glue (>= 1.6.0), httr2 (>= 1.0.0), jsonlite (>= 1.8.0), purrr (>= 1.0.0), rlang (>= 1.1.0), stats, tibble (>= 3.2.0), tidyr (>= 1.3.0), tidyselect (>= 1.2.0), utils

Suggests furrr (>= 0.3.0), future (>= 1.33.0), httptest2, keyring, knitr, rappdirs, rmarkdown, testthat (>= 3.0.0), withr

Config/testthat/edition 3

VignetteBuilder knitr

Config/Needs/website rmarkdown, AlphaSimR, AGHmatrix, BGLR, rrBLUP,
sommer, metan, lme4

Config/roxygen2/version 8.1.0

Config/pak/sysreqs libicu-dev libssl-dev

Repository <https://ropensci.r-universe.dev>

Date/Publication 2026-09-24 12:16:24 UTC

RemoteUrl <https://github.com/ropensci/brapiR2>

RemoteRef main

RemoteSha 8bb2d32144e6a821f704b96198411b1ea58413f6

Contents

brapi_allele_matrix	3
brapi_cache_clear	4
brapi_cache_enable	5
brapi_call_sets	6
brapi_calls	6
brapi_connection	7
brapi_crosses	8
brapi_crossing_projects	9
brapi_endpoints	10
brapi_events	11
brapi_fetch_parallel	12
brapi_germplasm	13
brapi_germplasm_attributes	14
brapi_germplasm_detail	15
brapi_germplasm_pedigree	15
brapi_germplasm_progeny	16
brapi_get	17
brapi_get_dosage_matrix	18
brapi_get_marker_map	19
brapi_images	20
brapi_list	21
brapi_lists	22
brapi_location	22
brapi_locations	23
brapi_login	24
brapi_login_oauth2	25
brapi_map	26
brapi_map_linkage_groups	26
brapi_maps	27
brapi_marker_positions	28
brapi_methods	29

brapi_observation_units	30
brapi_observation_variables	31
brapi_observations	32
brapi_ontologies	33
brapi_ontology	34
brapi_pedigree	35
brapi_people	36
brapi_ping	37
brapi_post_search	38
brapi_program	39
brapi_programs	40
brapi_reference_sets	41
brapi_references	41
brapi_samples	42
brapi_scales	43
brapi_search_calls	44
brapi_search_germplasm	44
brapi_search_marker_positions	45
brapi_search_observations	47
brapi_search_pedigree	48
brapi_search_variables	49
brapi_search_variants	50
brapi_seasons	50
brapi_seed_lots	51
brapi_server_info	52
brapi_set_token	53
brapi_studies	53
brapi_study	54
brapi_study_data	55
brapi_traits	56
brapi_trial	57
brapi_trials	57
brapi_variant_sets	58
brapi_variants	59
print.brapi_con	60

Index	61
--------------	-----------

brapi_allele_matrix	<i>Get Allele Matrix</i>
---------------------	--------------------------

Description

Retrieves genotype calls from the `/allelematrix` endpoint and returns a tidy tibble with one row per (variant, callSet) combination. The `/allelematrix` response has a unique structure (2-D pagination, no `result$data` envelope) so it cannot use the generic `brapi_get()`.

Usage

```
brapi_allele_matrix(con, variantSetDbId = NULL, ...)
```

Arguments

`con` A [brapi_connection\(\)](#) object.

`variantSetDbId` Character or NULL. Filter by variant set.

`...` Additional query parameters (e.g. `expandHomozygotes`, `unknownString`, `sepPhased`, `sepUnphased`).

Value

A tibble with columns `variantDbId`, `callSetDbId`, `genotype`.

BrAPI endpoint

GET /allelematrix - see the [v2.1 specification](#).

Query parameters the specification defines, which may be passed through `...`:

`dimensionVariantPage`, `dimensionVariantPageSize`, `dimensionCallSetPage`, `dimensionCallSetPageSize`.

Examples

```
con <- brapi_connection("https://test-server.brapi.org")
if (brapi_ping(con)) {
  brapi_allele_matrix(con, variantSetDbId = "variantset1")
}
```

brapi_cache_clear	<i>Clear the Response Cache</i>
-------------------	---------------------------------

Description

Removes all cached responses from the cache directory.

Usage

```
brapi_cache_clear(con)
```

Arguments

`con` A [brapi_connection\(\)](#) object with caching enabled.

Value

Invisibly returns `con`.

Examples

```
con <- brapi_connection("https://test-server.brapi.org")
con <- brapi_cache_enable(con, dir = tempdir())
brapi_cache_clear(con)
```

brapi_cache_enable	<i>Enable Response Caching</i>
--------------------	--------------------------------

Description

Returns a new connection object with caching enabled. Cached responses are stored as JSON files in the specified directory, keyed by URL and query parameters.

Usage

```
brapi_cache_enable(con, dir = NULL, ttl = 3600)
```

Arguments

con	A brapi_connection() object.
dir	Character. Directory to store cached responses. Defaults to a user cache directory via <code>rappdirs::user_cache_dir()</code> .
ttl	Numeric. Time-to-live for cached entries in seconds. Default 3600 (1 hour).

Value

A new `brapi_con` object with caching configured.

Examples

```
con <- brapi_connection("https://test-server.brapi.org")
con <- brapi_cache_enable(con, dir = tempdir(), ttl = 7200)
con
```

brapi_call_sets	<i>List Call Sets (Samples with Genotype Data)</i>
-----------------	--

Description

List Call Sets (Samples with Genotype Data)

Usage

```
brapi_call_sets(con, ...)
```

Arguments

con	A brapi_connection() object.
...	Additional query parameters.

Value

A tibble with one row per call set.

BrAPI endpoint

GET /callsets - see the [v2.1 specification](#).

Query parameters the specification defines, which may be passed through ...:

callSetDbId, callSetName, variantSetDbId, sampleDbId.

Examples

```
con <- brapi_connection("https://test-server.brapi.org")
if (brapi_ping(con)) {
  brapi_call_sets(con)
}
```

brapi_calls	<i>List Genotype Calls</i>
-------------	----------------------------

Description

List Genotype Calls

Usage

```
brapi_calls(con, variantSetDbId = NULL, ...)
```

Arguments

con A `brapi_connection()` object.
 variantSetDbId Character or NULL. Filter by variant set.
 ... Additional query parameters.

Value

A tibble with one row per genotype call.

BrAPI endpoint

GET /calls - see the [v2.1 specification](#).

Query parameters the specification defines, which may be passed through ...:

callSetDbId, variantDbId, variantSetDbId, expandHomozygotes, unknownString, sepPhased, sepUnphased.

Examples

```
con <- brapi_connection("https://test-server.brapi.org")
if (brapi_ping(con)) {
  brapi_calls(con, variantSetDbId = "variantset1")
}
```

brapi_connection	<i>Create a BrAPI Connection Object</i>
------------------	---

Description

Creates a connection object that holds server URL, authentication token, and configuration. This object is passed as the first argument to all brapiR2 functions. No global state is used.

Usage

```
brapi_connection(
  url,
  token = NULL,
  version = "v2",
  path = "brapi",
  user_agent = NULL,
  page_size = 1000L,
  timeout = 120
)
```

Arguments

url	Character. Base URL of the BrAPI server (e.g. "https://test-server.brapi.org"). Trailing slashes are removed.
token	Character or NULL. An existing Bearer token for authentication. If NULL, you can authenticate later with brapi_login() or brapi_login_oauth2() .
version	Character. BrAPI version path segment. Default "v2".
path	Character. URL path segment before the version, for servers that do not serve BrAPI at /brapi/. Default "brapi". GRIN-Global instances, for example, use "gringlobal/brapi".
user_agent	Character or NULL. Overrides the user agent brapiR2 sends with each request. The default identifies the package, its version, and the httr2 and R versions in use.
page_size	Integer. Number of records per page for paginated requests. Default 1000.
timeout	Numeric. Request timeout in seconds. Default 120.

Value

An S3 object of class "brapi_con" (a named list).

Examples

```
# Connect to the public BrAPI test server (no auth needed)
con <- brapi_connection("https://test-server.brapi.org")
con

# Connect with an existing token
con <- brapi_connection("https://my-breedbase.org", token = "my_token_here")

# Connect to a server that serves BrAPI under a different path
con <- brapi_connection("https://npgsweb.ars-grin.gov",
  path = "gringlobal/brapi")
```

brapi_crosses	<i>List Crosses</i>
---------------	---------------------

Description

List Crosses

Usage

```
brapi_crosses(con, ...)
```

Arguments

con A `brapi_connection()` object.
 ... Additional query parameters.

Value

A tibble with one row per cross.

BrAPI endpoint

GET /crosses - see the [v2.1 specification](#).

Query parameters the specification defines, which may be passed through ...:
 crossingProjectDbId, crossingProjectName, crossDbId, crossName.

Examples

```
con <- brapi_connection("https://test-server.brapi.org")
if (brapi_ping(con)) {
  brapi_crosses(con)
}
```

brapi_crossing_projects

List Crossing Projects

Description

List Crossing Projects

Usage

```
brapi_crossing_projects(con, ...)
```

Arguments

con A `brapi_connection()` object.
 ... Additional query parameters.

Value

A tibble with one row per crossing project.

BrAPI endpoint

GET /crossingprojects - see the [v2.1 specification](#).

Query parameters the specification defines, which may be passed through ...:
crossingProjectDbId, crossingProjectName, includePotentialParents.

Examples

```
con <- brapi_connection("https://test-server.brapi.org")
if (brapi_ping(con)) {
  brapi_crossing_projects(con)
}
```

brapi_endpoints	<i>List Available Endpoints</i>
-----------------	---------------------------------

Description

Queries the /serverinfo endpoint to list which BrAPI calls the server supports, along with their HTTP methods and versions.

Usage

```
brapi_endpoints(con)
```

Arguments

con A [brapi_connection\(\)](#) object.

Value

A tibble with columns for endpoint service, method(s), and version(s).

BrAPI endpoint

GET /serverinfo - see the [v2.1 specification](#).

Query parameters the specification defines, which may be passed through ...:
contentType, dataType.

Examples

```
con <- brapi_connection("https://test-server.brapi.org")
if (brapi_ping(con)) {
  brapi_endpoints(con)
}
```

brapi_events	<i>List Events</i>
--------------	--------------------

Description

List Events

Usage

```
brapi_events(con, studyDbId = NULL, ...)
```

Arguments

con	A brapi_connection() object.
studyDbId	Character or NULL. Filter by study.
...	Additional query parameters.

Value

A tibble with one row per event.

BrAPI endpoint

GET /events - see the [v2.1 specification](#).

Query parameters the specification defines, which may be passed through ...:

observationUnitDbId, eventDbId, eventType, dateRangeStart, dateRangeEnd.

Examples

```
con <- brapi_connection("https://test-server.brapi.org")
if (brapi_ping(con)) {
  brapi_events(con, studyDbId = "study1")
}
```

brapi_fetch_parallel *Parallel Batch Fetching*

Description

Fetches data from multiple BrAPI endpoints or IDs in parallel using the `furrr` package. Useful for retrieving data across many studies, trials, or germplasm records simultaneously.

Usage

```
brapi_fetch_parallel(con, .fn, ids, .workers = NULL, ...)
```

Arguments

<code>con</code>	A <code>brapi_connection()</code> object.
<code>.fn</code>	A <code>brapiR2</code> function to call for each item (e.g. <code>brapi_study_data</code>).
<code>ids</code>	Character vector. A set of IDs to iterate over.
<code>.workers</code>	Deprecated. No longer used - the parallel backend is now the caller's choice, set via <code>future::plan()</code> before calling this function. Supplying a non-NULL value emits a deprecation warning and otherwise has no effect.
<code>...</code>	Additional arguments passed to <code>.fn</code> .

Details

This function uses whatever future plan is already active when it is called, and does not set or restore one itself. If you have not called `future::plan()`, `furrr::future_map_dfr()` falls back to `future::sequential`, so nothing runs in parallel until you set a plan yourself - call `future::plan(future::multisession, workers = N)` before this function to fetch in parallel, and `future::plan(future::sequential)` afterwards to shut the workers back down. Per the future package's best-practices vignette, choosing the parallel backend is the caller's decision: a package that sets and restores a plan on every call still mutates session-wide state the caller did not ask it to touch, and can silently replace a backend they configured deliberately.

Value

A tibble with results from all IDs combined.

Examples

```
con <- brapi_connection("https://test-server.brapi.org")
if (brapi_ping(con)) {
  study_ids <- c("study1", "study2", "study3")

  # Set the parallel backend yourself before calling; brapi_fetch_parallel()
  # uses whatever plan is active rather than setting one for you.
  future::plan(future::multisession, workers = 2)
  all_data <- brapi_fetch_parallel(con, brapi_study_data, study_ids)
```

```
  future::plan(future::sequential) # shut the workers back down when done
}
```

brapi_germplasm	<i>List Germplasm</i>
-----------------	-----------------------

Description

List Germplasm

Usage

```
brapi_germplasm(con, ...)
```

Arguments

con	A brapi_connection() object.
...	Additional query parameters (e.g. commonCropName, germplasmName, studyDbId).

Value

A tibble with one row per germplasm accession.

BrAPI endpoint

GET /germplasm - see the [v2.1 specification](#).

Query parameters the specification defines, which may be passed through ...:

accessionNumber, collection, binomialName, genus, species, synonym, parentDbId, progenyDbId.

Examples

```
con <- brapi_connection("https://test-server.brapi.org")
if (brapi_ping(con)) {
  brapi_germplasm(con)
}
```

brapi_germplasm_attributes
List Germplasm Attributes

Description

List Germplasm Attributes

Usage

```
brapi_germplasm_attributes(con, ...)
```

Arguments

con	A brapi_connection() object.
...	Additional query parameters.

Value

A tibble with one row per attribute definition.

BrAPI endpoint

GET /attributes - see the [v2.1 specification](#).

Query parameters the specification defines, which may be passed through ...:

attributeCategory, attributeDbId, attributeName, attributePUI.

Examples

```
con <- brapi_connection("https://test-server.brapi.org")
if (brapi_ping(con)) {
  brapi_germplasm_attributes(con)
}
```

`brapi_germplasm_detail`*Get a Single Germplasm by ID*

Description

Get a Single Germplasm by ID

Usage

```
brapi_germplasm_detail(con, germplasmDbId)
```

Arguments

`con` A `brapi_connection()` object.
`germplasmDbId` Character. The unique germplasm identifier.

Value

A single-row tibble with germplasm details.

BrAPI endpoint

GET /germplasm/{germplasmDbId} - see the [v2.1 specification](#).

Examples

```
con <- brapi_connection("https://test-server.brapi.org")
if (brapi_ping(con)) {
  brapi_germplasm_detail(con, "germplasm1")
}
```

`brapi_germplasm_pedigree`*Get Germplasm Pedigree*

Description

The /germplasm/{germplasmDbId}/pedigree endpoint this function originally called was deprecated in BrAPI v2.1. It now queries /pedigree?germplasmDbId= instead, which returns a richer record.

Usage

```
brapi_germplasm_pedigree(con, germplasmDbId)
```

Arguments

con A [brapi_connection\(\)](#) object.
 germplasmDbId Character. The unique germplasm identifier.

Value

A single-row tibble of the germplasm's pedigree node, with parents, siblings and progeny as list-columns of tidy tibbles. See [brapi_pedigree\(\)](#), which this function calls.

BrAPI endpoint

GET /pedigree - see the [v2.1 specification](#).

Query parameters the specification defines, which may be passed through ...:

accessionNumber, collection, familyCode, binomialName, genus, species, synonym, includeParents, includeSiblings, includeProgeny, includeFullTree, pedigreeDepth, progenyDepth.

Examples

```
con <- brapi_connection("https://test-server.brapi.org")
if (brapi_ping(con)) {
  brapi_germplasm_pedigree(con, "germplasm1")
}
```

brapi_germplasm_progeny

Get Germplasm Progeny

Description

Get Germplasm Progeny

Usage

```
brapi_germplasm_progeny(con, germplasmDbId)
```

Arguments

con A [brapi_connection\(\)](#) object.
 germplasmDbId Character. The unique germplasm identifier.

Value

A single-row tibble of the germplasm's pedigree node, with progeny as a list-column of a tidy tibble of descendants. See [brapi_pedigree\(\)](#), which this function calls.

BrAPI endpoint

GET /pedigree - see the [v2.1 specification](#).

Query parameters the specification defines, which may be passed through ...:

accessionNumber, collection, familyCode, binomialName, genus, species, synonym, includeParents, includeSiblings, includeProgeny, includeFullTree, pedigreeDepth, progenyDepth.

Examples

```
con <- brapi_connection("https://test-server.brapi.org")
if (brapi_ping(con)) {
  brapi_germplasm_progeny(con, "germplasm1")
}
```

brapi_get

Call Any BrAPI GET Endpoint

Description

The named functions in brapiR2 cover 32 of the 36 BrAPI v2.1 entities. This is the layer beneath them, for endpoints brapiR2 does not wrap, for servers with non-standard extensions, and for query parameters a named function does not expose. Pagination, caching, authentication and error reporting work exactly as they do for the named functions.

Usage

```
brapi_get(con, endpoint, query = list(), max_pages = Inf)
```

Arguments

con	A brapi_connection() object.
endpoint	Character. The endpoint path, with or without a leading slash (for example "/programs" or "commoncropnames"). The base URL, BrAPI path and version come from con.
query	Named list. Query parameters to append to the URL. pageSize defaults to the connection's page size; page is managed by the pagination loop and should not be set here.
max_pages	Numeric. Stop after this many pages instead of fetching all of them. Inf, the default, fetches everything. A production server may hold hundreds of thousands of records, so a small value is useful for looking at what an unfamiliar server holds. A truncated result is never cached.

Value

A tibble of results, or an empty tibble if the endpoint returned no data.

Return shape

The response passes through the same parser the named functions use, so a well-formed BrAPI collection returns one row per record. An endpoint returning something the parser does not recognise may come back with list-columns or a shape you need to reshape yourself. The named functions are the better choice wherever one exists.

See Also

[brapi_post_search\(\)](#) for the POST search endpoints.

Examples

```
con <- brapi_connection("https://test-server.brapi.org")
if (brapi_ping(con)) {

  # An endpoint brapiR2 does not wrap
  brapi_get(con, "/commoncropnames")

  # A query parameter no named function exposes
  brapi_get(con, "/studies", query = list(active = "true"))
}
```

brapi_get_dosage_matrix

Get Dosage Matrix for Genomic Selection

Description

Fetches genotype data from a BrAPI server and converts it into a numeric dosage matrix (samples $\times$ markers) compatible with genomic selection packages like rrBLUP, BGLR, and sommer.

Usage

```
brapi_get_dosage_matrix(con, variantSetDbId, sep = "/", unknown_string = ".")
```

Arguments

con	A brapi_connection() object.
variantSetDbId	Character. The variant set to retrieve.
sep	Character. Unphased allele separator. Default "/" (e.g. "0/1"). Phased calls using " " are also handled automatically.
unknown_string	Character. String representing missing data. Default ".".

Details

Allele dosage is computed by splitting each genotype string on sep (or "|" for phased calls) and counting how many alleles are non-reference (i.e. not "0"). Missing calls (unknown_string, ".", or "") become NA.

Value

A numeric matrix: rows = samples (callSetDbIds), columns = markers (variantDbIds). Values are integer dosages (0, 1, 2 for diploids; 0–N for polyploids). Missing calls are NA.

Examples

```
con <- brapi_connection("https://test-server.brapi.org")
if (brapi_ping(con)) {
  dosage <- brapi_get_dosage_matrix(con, "variantset1")
  dim(dosage)
  # Use with rrBLUP:
  # library(rrBLUP)
  # result <- mixed.solve(y = pheno$yield, Z = dosage)
}
```

brapi_get_marker_map *Get Marker Map*

Description

Convenience function that retrieves marker positions on a genome map as a tidy tibble. Positions come from the Genome Maps entity ([brapi_marker_positions\(\)](#) / `/markerpositions`), which places a marker on a named [brapi_map\(\)](#) - genetic (cM) or physical (bp), per the map's type and unit - not from [brapi_variants\(\)](#)'s start/referenceName, which places a variant on a reference assembly instead. A server may populate either, both, or neither; the two are independent coordinate systems, not duplicates of each other.

Usage

```
brapi_get_marker_map(con, variantSetDbId = NULL, mapDbId = NULL)
```

Arguments

con	A brapi_connection() object.
variantSetDbId	Character or NULL. A variant set to retrieve marker positions for. Mutually exclusive with mapDbId.
mapDbId	Character or NULL. A single genome map to retrieve all marker positions from. Mutually exclusive with variantSetDbId.

Details

Supply exactly one of mapDbId (every marker placed on that one map) or variantSetDbId (positions for every variant in that set, wherever they have been placed). The variantSetDbId path looks variant IDs up first via `brapi_variants()`, then retrieves their positions in one call via `brapi_search_marker_positions()` rather than the GET /markerpositions filter, which only accepts a single variantDbId.

If a marker is placed on more than one map, it contributes one row per placement - the result is never collapsed to one row per marker.

Value

A tibble with columns variantDbId, variantName, mapDbId, mapName, type, unit, linkageGroupName, and position - one row per marker-map placement, so a marker on several maps appears more than once. type and unit are joined in from `brapi_maps()` so a caller can tell a genetic (cM) map from a physical (bp) one.

Examples

```
con <- brapi_connection("https://test-server.brapi.org")
if (brapi_ping(con)) {
  brapi_get_marker_map(con, mapDbId = "genome_map1")
  brapi_get_marker_map(con, variantSetDbId = "variantset1")
}
```

brapi_images

List Images

Description

List Images

Usage

```
brapi_images(con, ...)
```

Arguments

con	A <code>brapi_connection()</code> object.
...	Additional query parameters.

Value

A tibble with one row per image record.

BrAPI endpoint

GET /images - see the [v2.1 specification](#).

Query parameters the specification defines, which may be passed through . . .:

imageDbId, imageName, observationUnitDbId, observationDbId, descriptiveOntologyTerm.

Examples

```
con <- brapi_connection("https://test-server.brapi.org")
if (brapi_ping(con)) {
  brapi_images(con)
}
```

brapi_list

*Get a Single List by ID, With Its Contents***Description**

Unlike [brapi_lists\(\)](#), which returns only list metadata, this returns a single list together with its members in the data list-column. listType says what the members are (for example "germplasm").

Usage

```
brapi_list(con, listDbId)
```

Arguments

con	A brapi_connection() object.
listDbId	Character. The unique list identifier.

Value

A single-row tibble of list metadata, with the list's members as a character vector in the data list-column.

BrAPI endpoint

GET /lists/{listDbId} - see the [v2.1 specification](#).

Examples

```
con <- brapi_connection("https://test-server.brapi.org")
if (brapi_ping(con)) {
  lst <- brapi_list(con, "list1")
  lst$data[[1]]
}
```

brapi_lists	<i>List Generic Lists</i>
-------------	---------------------------

Description

List Generic Lists

Usage

```
brapi_lists(con, ...)
```

Arguments

con	A brapi_connection() object.
...	Additional query parameters (e.g. listType).

Value

A tibble with one row per list.

BrAPI endpoint

GET /lists - see the [v2.1 specification](#).

Query parameters the specification defines, which may be passed through ...:

listType, listName, listDbId, listSource.

Examples

```
con <- brapi_connection("https://test-server.brapi.org")
if (brapi_ping(con)) {
  brapi_lists(con)
}
```

brapi_location	<i>Get a Single Location by ID</i>
----------------	------------------------------------

Description

Get a Single Location by ID

Usage

```
brapi_location(con, locationDbId)
```

Arguments

con A `brapi_connection()` object.
locationDbId Character. The unique location identifier.

Value

A single-row tibble with location metadata, including coordinates where the server provides them.

BrAPI endpoint

GET /locations/{locationDbId} - see the [v2.1 specification](#).

Examples

```
con <- brapi_connection("https://test-server.brapi.org")
if (brapi_ping(con)) {
  brapi_location(con, "location_01")
}
```

brapi_locations	<i>List Locations</i>
-----------------	-----------------------

Description

List Locations

Usage

```
brapi_locations(con, ...)
```

Arguments

con A `brapi_connection()` object.
... Additional query parameters (e.g. `locationType`).

Value

A tibble with one row per location.

BrAPI endpoint

GET /locations - see the [v2.1 specification](#).

Query parameters the specification defines, which may be passed through ...:

`locationType`, `locationDbId`, `locationName`, `parentLocationDbId`, `parentLocationName`.

Examples

```
con <- brapi_connection("https://test-server.brapi.org")
if (brapi_ping(con)) {
  brapi_locations(con)
}
```

brapi_login

*Login to a BrAPI Server with Username and Password***Description**

Authenticates using the BrAPI /token endpoint and returns an updated connection object with the Bearer token set.

Usage

```
brapi_login(con, username, password)
```

Arguments

con	A brapi_connection() object.
username	Character. Your username.
password	Character. Your password.

Value

A new brapi_con object with the token populated.

See Also

The "Handling Credentials Safely" section of `vignette("brapiR2")` for how to keep username/password out of your script, using `.Renviron` or the `keyring` package.

Examples

```
con <- brapi_connection("https://test-server.brapi.org")
if (brapi_ping(con)) {
  con <- brapi_login(con, "brapi_reader", "brapi_reader")
  con
}
```

brapi_login_oauth2	<i>Login to a BrAPI Server with OAuth 2.0</i>
--------------------	---

Description

Performs an OAuth 2.0 authorization code flow or client credentials flow. Returns an updated connection object with the Bearer token set.

Usage

```
brapi_login_oauth2(con, client_id, client_secret, authorize_url, access_url)
```

Arguments

con	A <code>brapi_connection()</code> object.
client_id	Character. OAuth client ID.
client_secret	Character. OAuth client secret.
authorize_url	Character. The authorization endpoint URL.
access_url	Character. The token endpoint URL.

Value

A new `brapi_con` object with the token populated.

Examples

```
con <- brapi_connection("https://test-server.brapi.org")
if (brapi_ping(con)) {
  con <- brapi_login_oauth2(
    con,
    client_id = "brapi_client",
    client_secret = "brapi_secret",
    authorize_url = "https://test-server.brapi.org/brapi/v2/authorize",
    access_url = "https://test-server.brapi.org/brapi/v2/token"
  )
  con
}
```

brapi_map

*Get a Single Genome Map by ID***Description**

Get a Single Genome Map by ID

Usage

```
brapi_map(con, mapDbId)
```

Arguments

con A [brapi_connection\(\)](#) object.
mapDbId Character. The unique genome map identifier.

Value

A single-row tibble with genome map details, including type (e.g. "Genetic" or "Physical") and unit (e.g. "cM" or "bp").

BrAPI endpoint

GET /maps/{mapDbId} - see the [v2.1 specification](#).

Examples

```
con <- brapi_connection("https://test-server.brapi.org")
if (brapi_ping(con)) {
  brapi_map(con, "genome_map1")
}
```

brapi_map_linkage_groups

*List the Linkage Groups of a Genome Map***Description**

A linkage group is BrAPI's generic term for a named section of a map - it may represent a chromosome, a scaffold, or a generic linkage group.

Usage

```
brapi_map_linkage_groups(con, mapDbId)
```

Arguments

con A `brapi_connection()` object.

mapDbId Character. The unique genome map identifier.

Value

A tibble with one row per linkage group on the map.

BrAPI endpoint

GET /maps/{mapDbId}/linkagegroups - see the [v2.1 specification](#).

Examples

```
con <- brapi_connection("https://test-server.brapi.org")
if (brapi_ping(con)) {
  brapi_map_linkage_groups(con, "genome_map1")
}
```

brapi_maps

*List Genome Maps***Description**

List Genome Maps

Usage

```
brapi_maps(con, ...)
```

Arguments

con A `brapi_connection()` object.

... Additional query parameters.

Value

A tibble with one row per genome map.

BrAPI endpoint

GET /maps - see the [v2.1 specification](#).

Query parameters the specification defines, which may be passed through ...:

mapDbId, mapPUI, scientificName, type.

Examples

```
con <- brapi_connection("https://test-server.brapi.org")
if (brapi_ping(con)) {
  brapi_maps(con)
}
```

brapi_marker_positions

List Marker Positions

Description

Retrieves marker placements on genome maps from /markerpositions. A position here is relative to a named `brapi_map()` (genetic, in cM, or physical, in bp) - a different coordinate system from `brapi_variants()`'s start/referenceName, which places a variant on a reference assembly instead. A server may populate either, both, or neither; one being empty does not imply the other is.

Usage

```
brapi_marker_positions(
  con,
  mapDbId = NULL,
  variantDbId = NULL,
  linkageGroupName = NULL,
  minPosition = NULL,
  maxPosition = NULL,
  ...
)
```

Arguments

con	A <code>brapi_connection()</code> object.
mapDbId	Character or NULL. Filter by genome map.
variantDbId	Character or NULL. Filter by a single marker/variant ID. For multiple IDs at once, use <code>brapi_search_marker_positions()</code> instead.
linkageGroupName	Character or NULL. Filter by linkage group (e.g. chromosome) name.
minPosition	Integer or NULL. Minimum position, inclusive.
maxPosition	Integer or NULL. Maximum position, inclusive.
...	Additional query parameters.

Value

A tibble with one row per marker placement.

BrAPI endpoint

GET /markerpositions - see the [v2.1 specification](#).

Query parameters the specification defines, which may be passed through ...:

mapDbId, linkageGroupName, variantDbId, minPosition, maxPosition.

Examples

```
con <- brapi_connection("https://test-server.brapi.org")
if (brapi_ping(con)) {
  brapi_marker_positions(con, mapDbId = "genome_map1")
}
```

brapi_methods

*List Methods***Description**

List Methods

Usage

```
brapi_methods(con, ...)
```

Arguments

con	A brapi_connection() object.
...	Additional query parameters.

Value

A tibble with one row per measurement method.

BrAPI endpoint

GET /methods - see the [v2.1 specification](#).

Query parameters the specification defines, which may be passed through ...:

methodDbId, observationVariableDbId.

See Also

[brapi_ontologies\(\)](#) and [brapi_ontology\(\)](#) to resolve the ontology a method's ontologyDbId/ontologyReference points to.

Examples

```
con <- brapi_connection("https://test-server.brapi.org")
if (brapi_ping(con)) {
  brapi_methods(con)
}
```

brapi_observation_units

List Observation Units

Description

List Observation Units

Usage

```
brapi_observation_units(con, studyDbId = NULL, ...)
```

Arguments

con	A brapi_connection() object.
studyDbId	Character or NULL. Filter by study.
...	Additional query parameters.

Value

A tibble with one row per observation unit (plot/plant/sample).

BrAPI endpoint

GET /observationunits - see the [v2.1 specification](#).

Query parameters the specification defines, which may be passed through ...:

observationUnitDbId, observationUnitName, locationDbId, seasonDbId, includeObservations.

Examples

```
con <- brapi_connection("https://test-server.brapi.org")
if (brapi_ping(con)) {
  brapi_observation_units(con, studyDbId = "study1")
}
```

brapi_observation_variables
List Observation Variables

Description

Returns the ontology of observation variables (trait + method + scale).

Usage

```
brapi_observation_variables(con, ...)
```

Arguments

con	A brapi_connection() object.
...	Additional query parameters.

Value

A tibble with one row per variable definition.

BrAPI endpoint

GET /variables - see the [v2.1 specification](#).

Query parameters the specification defines, which may be passed through ...:

observationVariableDbId, observationVariableName, observationVariablePUI, traitClass.

See Also

[brapi_ontologies\(\)](#) and [brapi_ontology\(\)](#) to resolve the ontology a variable's ontologyDbId/ontologyReference points to.

Examples

```
con <- brapi_connection("https://test-server.brapi.org")
if (brapi_ping(con)) {
  brapi_observation_variables(con)
}
```

brapi_observations	<i>List Observations</i>
--------------------	--------------------------

Description

List Observations

Usage

```
brapi_observations(con, studyDbId = NULL, ...)
```

Arguments

con	A brapi_connection() object.
studyDbId	Character or NULL. Filter by study.
...	Additional query parameters.

Value

A tibble with one row per observation (trait measurement).

BrAPI endpoint

GET /observations - see the [v2.1 specification](#).

Query parameters the specification defines, which may be passed through ...:

observationDbId, observationUnitDbId, observationVariableDbId, locationDbId, seasonDbId,
observationTimeStampRangeStart, observationTimeStampRangeEnd.

Examples

```
con <- brapi_connection("https://test-server.brapi.org")
if (brapi_ping(con)) {
  brapi_observations(con, studyDbId = "study1")
}
```

brapi_ontologies	<i>List Ontologies</i>
------------------	------------------------

Description

Retrieves the ontologies registered on the server: metadata about each ontology (name, version, authors, description, ...), not the trait terms that belong to it. [brapi_traits\(\)](#), [brapi_scales\(\)](#), [brapi_methods\(\)](#), and [brapi_observation_variables\(\)](#) each carry an ontology reference back to one of these records.

Usage

```
brapi_ontologies(con, ...)
```

Arguments

con	A brapi_connection() object.
...	Additional query parameters.

Value

A tibble with one row per ontology.

BrAPI endpoint

GET /ontologies - see the [v2.1 specification](#).

Query parameters the specification defines, which may be passed through ...:
ontologyName.

See Also

[brapi_ontology\(\)](#) for a single ontology by ID; [brapi_traits\(\)](#), [brapi_scales\(\)](#), [brapi_methods\(\)](#), and [brapi_observation_variables\(\)](#) for the records that reference these ontologies.

Examples

```
con <- brapi_connection("https://test-server.brapi.org")
if (brapi_ping(con)) {
  brapi_ontologies(con)
}
```

brapi_ontology	<i>Get a Single Ontology by ID</i>
----------------	------------------------------------

Description

Get a Single Ontology by ID

Usage

```
brapi_ontology(con, ontologyDbId)
```

Arguments

con	A brapi_connection() object.
ontologyDbId	Character. The unique ontology identifier.

Value

A single-row tibble with ontology details.

BrAPI endpoint

GET /ontologies/{ontologyDbId} - see the [v2.1 specification](#).

See Also

[brapi_ontologies\(\)](#), [brapi_traits\(\)](#), [brapi_scales\(\)](#), [brapi_methods\(\)](#), and [brapi_observation_variables\(\)](#) for the records that reference ontologies.

Examples

```
con <- brapi_connection("https://test-server.brapi.org")
if (brapi_ping(con)) {
  brapi_ontology(con, "O_001")
}
```

brapi_pedigree

*List Pedigree Nodes***Description**

Retrieves a filtered subset of a pedigree tree via /pedigree - a batch endpoint for pulling pedigree records across many germplasm in one call. This is different from [brapi_germplasm_pedigree\(\)](#), which retrieves one germplasm's immediate pedigree via the germplasm sub-resource (/germplasm/{germplasmDbId}/pedigree) and must be called once per germplasm. Use [brapi_pedigree\(\)](#) (or [brapi_search_pedigree\(\)](#)) to pull pedigree records for many germplasm at once - e.g. everything in a crop, program, or family - in one or a few requests; use [brapi_germplasm_pedigree\(\)](#) when you already have a single germplasm ID in hand.

Usage

```
brapi_pedigree(
  con,
  germplasmDbId = NULL,
  includeParents = NULL,
  includeSiblings = NULL,
  includeProgeny = NULL,
  includeFullTree = NULL,
  pedigreeDepth = NULL,
  progenyDepth = NULL,
  ...
)
```

Arguments

con	A brapi_connection() object.
germplasmDbId	Character or NULL. Filter by germplasm.
includeParents	Logical or NULL. Include each node's parents.
includeSiblings	Logical or NULL. Include each node's siblings.
includeProgeny	Logical or NULL. Include each node's progeny.
includeFullTree	Logical or NULL. Recursively include every node reachable in the pedigree tree.
pedigreeDepth	Integer or NULL. Number of levels to include up the tree (parents, grandparents, ...).
progenyDepth	Integer or NULL. Number of levels to include down the tree (children, grandchildren, ...).
...	Additional query parameters.

Details

Each row is one pedigree node (one germplasm). The server only includes a node’s relatives if asked: set includeParents, includeSiblings, and/or includeProgeny to TRUE to populate the parents, siblings, and progeny list-columns, each holding a small tibble of related germplasm (germplasmDbId, germplasmName, and parentType - NA for siblings, which have none) that you can `tidyr::unnest()` when you need one row per relationship rather than one row per node. Nodes are never collapsed or flattened by default: a pedigree is graph-shaped (each node has its own parents, siblings, and progeny edges), and the three relation types don’t share a common row shape, so there is no lossless single flat table to fall back to.

Value

A tibble with one row per pedigree node. parents, siblings, and progeny, when requested, are list-columns of small tibbles (one row per relative) rather than raw nested lists or a flattened table.

BrAPI endpoint

GET /pedigree - see the [v2.1 specification](#).
Query parameters the specification defines, which may be passed through ...:
accessionNumber, collection, familyCode, binomialName, genus, species, synonym, includeParents, includeSiblings, includeProgeny, includeFullTree, pedigreeDepth, progenyDepth.

See Also

[brapi_germplasm_pedigree\(\)](#) for one germplasm’s pedigree via the germplasm sub-resource;
[brapi_search_pedigree\(\)](#) for the same batch retrieval via POST, with a fuller set of filters.

Examples

```
con <- brapi_connection("https://test-server.brapi.org")
if (brapi_ping(con)) {
  brapi_pedigree(con, includeParents = TRUE, includeProgeny = TRUE)
}
```

brapi_people	List People
--------------	-------------

Description

List People

Usage

```
brapi_people(con, ...)
```

Arguments

con A `brapi_connection()` object.
... Additional query parameters.

Value

A tibble with one row per person.

BrAPI endpoint

GET /people - see the [v2.1 specification](#).

Query parameters the specification defines, which may be passed through ...:

firstName, lastName, personDbId, userID.

Examples

```
con <- brapi_connection("https://test-server.brapi.org")
if (brapi_ping(con)) {
  brapi_people(con)
}
```

brapi_ping	<i>Ping a BrAPI Server</i>
------------	----------------------------

Description

Tests whether the BrAPI server is reachable and responding.

Usage

```
brapi_ping(con)
```

Arguments

con A `brapi_connection()` object.

Value

Logical. TRUE if the server responds, FALSE otherwise.

BrAPI endpoint

GET /serverinfo - see the [v2.1 specification](#).

Query parameters the specification defines, which may be passed through ...:

contentType, dataType.

Examples

```
con <- brapi_connection("https://test-server.brapi.org")
brapi_ping(con)
```

brapi_post_search	<i>Call Any BrAPI Search Endpoint</i>
-------------------	---------------------------------------

Description

The companion to `brapi_get()` for the POST `/search/{entity}` endpoints, which take a filter body rather than query parameters and may run asynchronously. Use it for search endpoints `brapiR2` does not wrap, or for filter fields a named search function does not expose.

Usage

```
brapi_post_search(
  con,
  endpoint,
  body = list(),
  poll_interval = 2,
  max_polls = 30L
)
```

Arguments

<code>con</code>	A <code>brapi_connection()</code> object.
<code>endpoint</code>	Character. The search endpoint, with or without a leading slash (for example <code>/search/germplasm</code>).
<code>body</code>	Named list. The search request body. Filter fields are sent as JSON arrays, as BrAPI expects, even when you supply a single value.
<code>poll_interval</code>	Numeric. Seconds between polling attempts for an asynchronous search. Default 2.
<code>max_polls</code>	Integer. Maximum polling attempts before giving up. Default 30.

Value

A tibble of search results.

Asynchronous searches

A server may answer immediately with the results, or with HTTP 202 and a `searchResultsDbId` to be polled until the results are ready. Both are handled here; the polling happens inside the call and you get the finished results either way.

Return shape

As with `brapi_get()`, the response passes through the same parser the named functions use. A well-formed BrAPI result returns one row per record; an unusual one may need reshaping yourself.

See Also

`brapi_get()` for the GET endpoints.

Examples

```
con <- brapi_connection("https://test-server.brapi.org")
if (brapi_ping(con)) {
  brapi_post_search(con, "/search/germplasm",
    body = list(germplasmNames = "Tomatillo Fantastico"))
}
```

brapi_program	<i>Get a Single Program by ID</i>
---------------	-----------------------------------

Description

Get a Single Program by ID

Usage

```
brapi_program(con, programDbId)
```

Arguments

con	A <code>brapi_connection()</code> object.
programDbId	Character. The unique program identifier.

Value

A single-row tibble with program details.

BrAPI endpoint

GET /programs/{programDbId} - see the [v2.1 specification](#).

Examples

```
con <- brapi_connection("https://test-server.brapi.org")
if (brapi_ping(con)) {
  brapi_program(con, "program1")
}
```

brapi_programs	<i>List Breeding Programs</i>
----------------	-------------------------------

Description

Retrieves a list of breeding programs from the BrAPI server.

Usage

```
brapi_programs(con, ...)
```

Arguments

con	A brapi_connection() object.
...	Additional query parameters passed to the API (e.g. <code>commonCropName = "rice"</code> , <code>programName = "IRRI"</code>).

Value

A tibble with one row per program.

BrAPI endpoint

GET /programs - see the [v2.1 specification](#).

Query parameters the specification defines, which may be passed through ...:

abbreviation, programType.

Examples

```
con <- brapi_connection("https://test-server.brapi.org")
if (brapi_ping(con)) {
  brapi_programs(con)
  brapi_programs(con, commonCropName = "rice")
}
```

brapi_reference_sets *List Reference Sets (Genome Assemblies)*

Description

List Reference Sets (Genome Assemblies)

Usage

```
brapi_reference_sets(con, ...)
```

Arguments

con	A brapi_connection() object.
...	Additional query parameters.

Value

A tibble with one row per reference set.

BrAPI endpoint

GET /referencesets - see the [v2.1 specification](#).

Query parameters the specification defines, which may be passed through ...:

referenceSetDbId, accession, assemblyPUI, md5checksum.

Examples

```
con <- brapi_connection("https://test-server.brapi.org")
if (brapi_ping(con)) {
  brapi_reference_sets(con)
}
```

brapi_references *List References (Chromosomes/Contigs)*

Description

List References (Chromosomes/Contigs)

Usage

```
brapi_references(con, ...)
```

Arguments

con A `brapi_connection()` object.
 ... Additional query parameters.

Value

A tibble with one row per reference sequence.

BrAPI endpoint

GET /references - see the [v2.1 specification](#).

Query parameters the specification defines, which may be passed through ...:

referenceDbId, referenceSetDbId, accession, md5checksum, isDerived, minLength, maxLength.

Examples

```
con <- brapi_connection("https://test-server.brapi.org")
if (brapi_ping(con)) {
  brapi_references(con)
}
```

brapi_samples

List Samples

Description

List Samples

Usage

```
brapi_samples(con, ...)
```

Arguments

con A `brapi_connection()` object.
 ... Additional query parameters (e.g. studyDbId, germplasmDbId, observationUnitDbId).

Value

A tibble with one row per sample.

BrAPI endpoint

GET /samples - see the [v2.1 specification](#).

Query parameters the specification defines, which may be passed through ...:

sampleDbId, sampleName, sampleGroupDbId, observationUnitDbId, plateDbId, plateName.

Examples

```
con <- brapi_connection("https://test-server.brapi.org")
if (brapi_ping(con)) {
  brapi_samples(con)
}
```

brapi_scales

*List Scales***Description**

List Scales

Usage

```
brapi_scales(con, ...)
```

Arguments

con A [brapi_connection\(\)](#) object.

... Additional query parameters.

Value

A tibble with one row per scale definition.

BrAPI endpointGET /scales - see the [v2.1 specification](#).

Query parameters the specification defines, which may be passed through ...:

scaleDbId, observationVariableDbId.

See Also

[brapi_ontologies\(\)](#) and [brapi_ontology\(\)](#) to resolve the ontology a scale's ontologyDbId/ontologyReference points to.

Examples

```
con <- brapi_connection("https://test-server.brapi.org")
if (brapi_ping(con)) {
  brapi_scales(con)
}
```

brapi_search_calls *Search Genotype Calls*

Description

Search Genotype Calls

Usage

```
brapi_search_calls(con, variantSetDbIds = NULL, callSetDbIds = NULL, ...)
```

Arguments

con A [brapi_connection\(\)](#) object.
variantSetDbIds Character vector. Filter by variant set IDs.
callSetDbIds Character vector. Filter by call set IDs.
... Additional search body parameters.

Value

A tibble of matching genotype calls.

BrAPI endpoint

POST /search/calls - see the [v2.1 specification](#).

Examples

```
con <- brapi_connection("https://test-server.brapi.org")
if (brapi_ping(con)) {
  brapi_search_calls(con, variantSetDbIds = "variantset1")
}
```

brapi_search_germplasm *Search Germplasm*

Description

Performs a BrAPI search for germplasm records matching the given criteria.

Usage

```
brapi_search_germplasm(  
  con,  
  germplasmNames = NULL,  
  germplasmDbIds = NULL,  
  commonCropNames = NULL,  
  ...  
)
```

Arguments

con	A brapi_connection() object.
germplasmNames	Character vector. Filter by germplasm names.
germplasmDbIds	Character vector. Filter by database IDs.
commonCropNames	Character vector. Filter by crop name.
...	Additional body parameters for the search request.

Value

A tibble of matching germplasm records.

BrAPI endpoint

POST /search/germplasm - see the [v2.1 specification](#).

Examples

```
con <- brapi_connection("https://test-server.brapi.org")  
if (brapi_ping(con)) {  
  brapi_search_germplasm(con, commonCropNames = "Tomatillo")  
}
```

brapi_search_marker_positions

Search Marker Positions

Description

The /markerpositions GET filter (see [brapi_marker_positions\(\)](#)) takes a single variantDbId; this search endpoint accepts many IDs at once, which is what [brapi_get_marker_map\(\)](#) uses internally when looking up positions for an entire variant set.

Usage

```
brapi_search_marker_positions(  
  con,  
  mapDbIds = NULL,  
  variantDbIds = NULL,  
  linkageGroupNames = NULL,  
  minPosition = NULL,  
  maxPosition = NULL,  
  ...  
)
```

Arguments

con	A brapi_connection() object.
mapDbIds	Character vector. Filter by genome map IDs.
variantDbIds	Character vector. Filter by marker/variant IDs.
linkageGroupNames	Character vector. Filter by linkage group names.
minPosition	Integer. Minimum position, inclusive.
maxPosition	Integer. Maximum position, inclusive.
...	Additional search body parameters.

Value

A tibble of matching marker positions.

BrAPI endpoint

POST /search/markerpositions - see the [v2.1 specification](#).

Examples

```
con <- brapi_connection("https://test-server.brapi.org")  
if (brapi_ping(con)) {  
  brapi_search_marker_positions(con, variantDbIds = c("variant01", "variant02"))  
}
```

brapi_search_observations
Search Observations

Description

Search Observations

Usage

```
brapi_search_observations(  
  con,  
  studyDbIds = NULL,  
  observationVariableDbIds = NULL,  
  ...  
)
```

Arguments

con	A brapi_connection() object.
studyDbIds	Character vector. Filter by study IDs.
observationVariableDbIds	Character vector. Filter by variable IDs.
...	Additional search body parameters.

Value

A tibble of matching observations.

BrAPI endpoint

POST /search/observations - see the [v2.1 specification](#).

Examples

```
con <- brapi_connection("https://test-server.brapi.org")  
if (brapi_ping(con)) {  
  brapi_search_observations(con, studyDbIds = "study1")  
}
```

brapi_search_pedigree *Search Pedigree Nodes*

Description

The POST equivalent of [brapi_pedigree\(\)](#), taking the same tree-shaping parameters plus the fuller set of filters /search/pedigree accepts (crop, program, trial, study, accession number, collection, family code, genus/species, and more - pass any of these through ...). See [brapi_pedigree\(\)](#) for the shape of the returned tibble and its relationship to [brapi_germplasm_pedigree\(\)](#).

Usage

```
brapi_search_pedigree(
  con,
  germplasmDbIds = NULL,
  includeParents = NULL,
  includeSiblings = NULL,
  includeProgeny = NULL,
  includeFullTree = NULL,
  pedigreeDepth = NULL,
  progenyDepth = NULL,
  ...
)
```

Arguments

con	A brapi_connection() object.
germplasmDbIds	Character vector. Filter by germplasm IDs.
includeParents	Logical. Include each node's parents.
includeSiblings	Logical. Include each node's siblings.
includeProgeny	Logical. Include each node's progeny.
includeFullTree	Logical. Recursively include every node reachable in the pedigree tree.
pedigreeDepth	Integer. Number of levels to include up the tree.
progenyDepth	Integer. Number of levels to include down the tree.
...	Additional search body parameters.

Value

A tibble with one row per pedigree node; see [brapi_pedigree\(\)](#) for column details.

BrAPI endpoint

POST /search/pedigree - see the [v2.1 specification](#).

See Also

[brapi_pedigree\(\)](#), [brapi_germplasm_pedigree\(\)](#)

Examples

```
con <- brapi_connection("https://test-server.brapi.org")
if (brapi_ping(con)) {
  brapi_search_pedigree(con, includeParents = TRUE)
}
```

brapi_search_variables

Search Observation Variables

Description

Search Observation Variables

Usage

```
brapi_search_variables(con, traitClasses = NULL, ...)
```

Arguments

con	A brapi_connection() object.
traitClasses	Character vector. Filter by trait class.
...	Additional search body parameters.

Value

A tibble of matching observation variables.

BrAPI endpoint

POST /search/variables - see the [v2.1 specification](#).

Examples

```
con <- brapi_connection("https://test-server.brapi.org")
if (brapi_ping(con)) {
  brapi_search_variables(con, traitClasses = "agronomic")
}
```

brapi_search_variants	<i>Search Variants</i>
-----------------------	------------------------

Description

Search Variants

Usage

```
brapi_search_variants(con, variantSetDbIds = NULL, ...)
```

Arguments

con	A brapi_connection() object.
variantSetDbIds	Character vector. Filter by variant set IDs.
...	Additional search body parameters.

Value

A tibble of matching variants.

BrAPI endpoint

POST /search/variants - see the [v2.1 specification](#).

Examples

```
con <- brapi_connection("https://test-server.brapi.org")
if (brapi_ping(con)) {
  brapi_search_variants(con, variantSetDbIds = "variantset1")
}
```

brapi_seasons	<i>List Seasons</i>
---------------	---------------------

Description

List Seasons

Usage

```
brapi_seasons(con, ...)
```

Arguments

con A `brapi_connection()` object.
... Additional query parameters (e.g. year).

Value

A tibble with one row per season.

BrAPI endpoint

GET /seasons - see the [v2.1 specification](#).

Query parameters the specification defines, which may be passed through ...:
seasonDbId, season, seasonName, year.

Examples

```
con <- brapi_connection("https://test-server.brapi.org")
if (brapi_ping(con)) {
  brapi_seasons(con)
}
```

brapi_seed_lots	<i>List Seed Lots</i>
-----------------	-----------------------

Description

List Seed Lots

Usage

```
brapi_seed_lots(con, ...)
```

Arguments

con A `brapi_connection()` object.
... Additional query parameters.

Value

A tibble with one row per seed lot.

BrAPI endpoint

GET /seedlots - see the [v2.1 specification](#).

Query parameters the specification defines, which may be passed through ...:
seedLotDbId, crossDbId, crossName.

Examples

```
con <- brapi_connection("https://test-server.brapi.org")
if (brapi_ping(con)) {
  brapi_seed_lots(con)
}
```

brapi_server_info	<i>Get Server Info</i>
-------------------	------------------------

Description

Returns a tibble of BrAPI calls supported by the server. Each row is one supported endpoint with columns for service name, HTTP methods, BrAPI versions, and content/data types.

Usage

```
brapi_server_info(con)
```

Arguments

con A [brapi_connection\(\)](#) object.

Value

A tibble of supported endpoints and their methods.

BrAPI endpoint

GET /serverinfo - see the [v2.1 specification](#).

Query parameters the specification defines, which may be passed through ...:

contentType, dataType.

Examples

```
con <- brapi_connection("https://test-server.brapi.org")
if (brapi_ping(con)) {
  brapi_server_info(con)
}
```

`brapi_set_token`*Manually Set an Authentication Token*

Description

If you already have a token (e.g. from a web browser session), you can set it directly without going through a login flow.

Usage

```
brapi_set_token(con, token)
```

Arguments

<code>con</code>	A <code>brapi_connection()</code> object.
<code>token</code>	Character. The Bearer token string.

Value

A new `brapi_con` object with the token populated.

See Also

The "Handling Credentials Safely" section of `vignette("brapiR2")` for how to keep token out of your script, using `.Renvirom` or the `keyring` package.

Examples

```
con <- brapi_connection("https://test-server.brapi.org")
con <- brapi_set_token(con, "my_existing_token")
```

`brapi_studies`*List Studies*

Description

Retrieves studies (occurrences/environments), optionally filtered by trial.

Usage

```
brapi_studies(con, trialDbId = NULL, ...)
```

Arguments

con	A <code>brapi_connection()</code> object.
trialDbId	Character or NULL. Filter by trial.
...	Additional query parameters.

Value

A tibble with one row per study.

BrAPI endpoint

GET /studies - see the [v2.1 specification](#).

Query parameters the specification defines, which may be passed through ...:

studyType, locationDbId, seasonDbId, studyCode, studyPUI, observationVariableDbId, active, sortBy, sortOrder.

Examples

```
con <- brapi_connection("https://test-server.brapi.org")
if (brapi_ping(con)) {
  brapi_studies(con)
  brapi_studies(con, trialDbId = "trial1")
}
```

brapi_study

Get a Single Study by ID

Description

Get a Single Study by ID

Usage

```
brapi_study(con, studyDbId)
```

Arguments

con	A <code>brapi_connection()</code> object.
studyDbId	Character. The unique study identifier.

Value

A single-row tibble with study metadata.

BrAPI endpoint

GET /studies/{studyDbId} - see the [v2.1 specification](#).

Examples

```
con <- brapi_connection("https://test-server.brapi.org")
if (brapi_ping(con)) {
  brapi_study(con, "study1")
}
```

brapi_study_data	<i>Get Study Data in Wide Format</i>
------------------	--------------------------------------

Description

A convenience function that fetches observation units and observations for a given study and pivots them into a wide-format tibble with one row per observation unit and one column per trait — ready for analysis.

Usage

```
brapi_study_data(con, studyDbId)
```

Arguments

con	A brapi_connection() object.
studyDbId	Character. The unique study identifier.

Value

A wide-format tibble with columns for plot metadata and one column per observed trait containing the measurement values.

Examples

```
con <- brapi_connection("https://test-server.brapi.org")
if (brapi_ping(con)) {
  data <- brapi_study_data(con, "study1")
  head(data)
}
```

`brapi_traits`*List Traits*

Description

List Traits

Usage

```
brapi_traits(con, ...)
```

Arguments

<code>con</code>	A brapi_connection() object.
<code>...</code>	Additional query parameters.

Value

A tibble with one row per trait.

BrAPI endpoint

GET /traits - see the [v2.1 specification](#).

Query parameters the specification defines, which may be passed through `...`:

`traitDbId`, `observationVariableDbId`.

See Also

[brapi_ontologies\(\)](#) and [brapi_ontology\(\)](#) to resolve the ontology a trait's `ontologyDbId/ontologyReference` points to.

Examples

```
con <- brapi_connection("https://test-server.brapi.org")
if (brapi_ping(con)) {
  brapi_traits(con)
}
```

brapi_trial	<i>Get a Single Trial by ID</i>
-------------	---------------------------------

Description

Get a Single Trial by ID

Usage

```
brapi_trial(con, trialDbId)
```

Arguments

con	A brapi_connection() object.
trialDbId	Character. The unique trial identifier.

Value

A single-row tibble with trial details.

BrAPI endpoint

GET /trials/{trialDbId} - see the [v2.1 specification](#).

Examples

```
con <- brapi_connection("https://test-server.brapi.org")
if (brapi_ping(con)) {
  brapi_trial(con, "trial1")
}
```

brapi_trials	<i>List Trials</i>
--------------	--------------------

Description

Retrieves trials, optionally filtered by program.

Usage

```
brapi_trials(con, programDbId = NULL, ...)
```

Arguments

con A `brapi_connection()` object.
 programDbId Character or NULL. Filter by program.
 ... Additional query parameters.

Value

A tibble with one row per trial.

BrAPI endpoint

GET /trials - see the [v2.1 specification](#).

Query parameters the specification defines, which may be passed through ...:

active, contactDbId, locationDbId, searchDateRangeStart, searchDateRangeEnd, trialPUI, sortBy, sortOrder.

Examples

```
con <- brapi_connection("https://test-server.brapi.org")
if (brapi_ping(con)) {
  brapi_trials(con)
}
```

brapi_variant_sets	<i>List Variant Sets (Datasets)</i>
--------------------	-------------------------------------

Description

List Variant Sets (Datasets)

Usage

```
brapi_variant_sets(con, studyDbId = NULL, ...)
```

Arguments

con A `brapi_connection()` object.
 studyDbId Character or NULL. Filter by study.
 ... Additional query parameters.

Value

A tibble with one row per variant set.

BrAPI endpoint

GET /variantsets - see the [v2.1 specification](#).

Query parameters the specification defines, which may be passed through ...:

variantSetDbId, variantDbId, callSetDbId, referenceSetDbId.

Examples

```
con <- brapi_connection("https://test-server.brapi.org")
if (brapi_ping(con)) {
  brapi_variant_sets(con)
}
```

brapi_variants	<i>List Variants (Markers/SNPs)</i>
----------------	-------------------------------------

Description

List Variants (Markers/SNPs)

Usage

```
brapi_variants(con, variantSetDbId = NULL, ...)
```

Arguments

con A [brapi_connection\(\)](#) object.

variantSetDbId Character or NULL. Filter by variant set.

... Additional query parameters.

Value

A tibble with one row per variant.

BrAPI endpoint

GET /variants - see the [v2.1 specification](#).

Query parameters the specification defines, which may be passed through ...:

variantDbId, variantSetDbId, referenceDbId, referenceSetDbId.

Examples

```
con <- brapi_connection("https://test-server.brapi.org")
if (brapi_ping(con)) {
  brapi_variants(con, variantSetDbId = "variantset1")
}
```

print.brapi_con	<i>Print a BrAPI Connection Object</i>
-----------------	--

Description

Print a BrAPI Connection Object

Usage

```
## S3 method for class 'brapi_con'
print(x, ...)
```

Arguments

x	A brapi_con object.
...	Additional arguments (ignored).

Value

Invisibly returns x.

Examples

```
con <- brapi_connection("https://test-server.brapi.org")
print(con)
```

Index

`brapi_allele_matrix`, 3
`brapi_cache_clear`, 4
`brapi_cache_enable`, 5
`brapi_call_sets`, 6
`brapi_calls`, 6
`brapi_connection`, 7
`brapi_connection()`, 4–7, 9–35, 37–59
`brapi_crosses`, 8
`brapi_crossing_projects`, 9
`brapi_endpoints`, 10
`brapi_events`, 11
`brapi_fetch_parallel`, 12
`brapi_germplasm`, 13
`brapi_germplasm_attributes`, 14
`brapi_germplasm_detail`, 15
`brapi_germplasm_pedigree`, 15
`brapi_germplasm_pedigree()`, 35, 36, 48, 49
`brapi_germplasm_progeny`, 16
`brapi_get`, 17
`brapi_get()`, 38, 39
`brapi_get_dosage_matrix`, 18
`brapi_get_marker_map`, 19
`brapi_get_marker_map()`, 45
`brapi_images`, 20
`brapi_list`, 21
`brapi_lists`, 22
`brapi_lists()`, 21
`brapi_location`, 22
`brapi_locations`, 23
`brapi_login`, 24
`brapi_login()`, 8
`brapi_login_oauth2`, 25
`brapi_login_oauth2()`, 8
`brapi_map`, 26
`brapi_map()`, 19, 28
`brapi_map_linkage_groups`, 26
`brapi_maps`, 27
`brapi_maps()`, 20
`brapi_marker_positions`, 28
`brapi_marker_positions()`, 19, 45
`brapi_methods`, 29
`brapi_methods()`, 33, 34
`brapi_observation_units`, 30
`brapi_observation_variables`, 31
`brapi_observation_variables()`, 33, 34
`brapi_observations`, 32
`brapi_ontologies`, 33
`brapi_ontologies()`, 29, 31, 34, 43, 56
`brapi_ontology`, 34
`brapi_ontology()`, 29, 31, 33, 43, 56
`brapi_pedigree`, 35
`brapi_pedigree()`, 16, 48, 49
`brapi_people`, 36
`brapi_ping`, 37
`brapi_post_search`, 38
`brapi_post_search()`, 18
`brapi_program`, 39
`brapi_programs`, 40
`brapi_reference_sets`, 41
`brapi_references`, 41
`brapi_samples`, 42
`brapi_scales`, 43
`brapi_scales()`, 33, 34
`brapi_search_calls`, 44
`brapi_search_germplasm`, 44
`brapi_search_marker_positions`, 45
`brapi_search_marker_positions()`, 20, 28
`brapi_search_observations`, 47
`brapi_search_pedigree`, 48
`brapi_search_pedigree()`, 35, 36
`brapi_search_variables`, 49
`brapi_search_variants`, 50
`brapi_seasons`, 50
`brapi_seed_lots`, 51
`brapi_server_info`, 52
`brapi_set_token`, 53
`brapi_studies`, 53

`brapi_study`, [54](#)
`brapi_study_data`, [55](#)
`brapi_traits`, [56](#)
`brapi_traits()`, [33](#), [34](#)
`brapi_trial`, [57](#)
`brapi_trials`, [57](#)
`brapi_variant_sets`, [58](#)
`brapi_variants`, [59](#)
`brapi_variants()`, [19](#), [20](#), [28](#)

`future::plan()`, [12](#)

`print.brapi_con`, [60](#)

`tidyr::unnest()`, [36](#)