

# Package: ckanr (via r-universe)

October 28, 2024

**Title** Client for the Comprehensive Knowledge Archive Network ('CKAN') API

**Description** Client for 'CKAN' API (<<https://ckan.org/>>). Includes interface to 'CKAN' 'APIs' for search, list, show for packages, organizations, and resources. In addition, provides an interface to the 'datastore' API.

**Version** 0.7.0.9000

**License** MIT + file LICENSE

**LazyData** true

**URL** <https://docs.ropensci.org/ckanr/> (website)  
<https://github.com/ropensci/ckanr> (devel)

**BugReports** <https://github.com/ropensci/ckanr/issues>

**Encoding** UTF-8

**Language** en-US

**Roxygen** list(markdown = TRUE)

**Depends** DBI (>= 0.3.1)

**Imports** methods, stats, utils, crul, jsonlite (>= 0.9.17), dplyr (>= 0.7.0), dbplyr, magrittr

**Suggests** sf, readxl, testthat, xml2, lazyeval

**RoxygenNote** 7.2.3

**X-schema.org-keywords** database, open-data, ckan, api, data, dataset

**X-schema.org-applicationCategory** Data Access

**X-schema.org-isPartOf** `` <https://ropensci.org>``

**Repository** <https://ropensci.r-universe.dev>

**RemoteUrl** <https://github.com/ropensci/ckanr>

**RemoteRef** master

**RemoteSha** f45afeaf9a41b35f38fa96054e97ca446d73c90c

## Contents

ckanr-package . . . . .	3
as.ckan_group . . . . .	5
as.ckan_organization . . . . .	5
as.ckan_package . . . . .	6
as.ckan_related . . . . .	7
as.ckan_resource . . . . .	8
as.ckan_tag . . . . .	9
as.ckan_user . . . . .	9
changes . . . . .	10
ckanr-deprecated . . . . .	11
ckanr_settings . . . . .	11
ckanr_setup . . . . .	12
ckan_classes . . . . .	14
ckan_fetch . . . . .	15
ckan_info . . . . .	17
dashboard_activity_list . . . . .	18
dashboard_count . . . . .	19
ds_create . . . . .	20
ds_create_dataset . . . . .	21
ds_search . . . . .	23
ds_search_sql . . . . .	24
group_create . . . . .	25
group_delete . . . . .	27
group_list . . . . .	28
group_patch . . . . .	29
group_show . . . . .	30
group_update . . . . .	31
license_list . . . . .	32
organization_create . . . . .	33
organization_delete . . . . .	35
organization_list . . . . .	36
organization_purge . . . . .	37
organization_show . . . . .	38
package_activity_list . . . . .	39
package_create . . . . .	40
package_delete . . . . .	42
package_list . . . . .	43
package_list_current . . . . .	44
package_patch . . . . .	45
package_revision_list . . . . .	46
package_search . . . . .	48
package_show . . . . .	50
package_update . . . . .	51
ping . . . . .	52
related_create . . . . .	53
related_delete . . . . .	54

related_list . . . . .	55
related_show . . . . .	56
related_update . . . . .	57
resource_create . . . . .	59
resource_delete . . . . .	61
resource_patch . . . . .	62
resource_search . . . . .	63
resource_show . . . . .	64
resource_update . . . . .	65
revision_list . . . . .	68
servers . . . . .	69
src_ckan . . . . .	70
tag_create . . . . .	70
tag_list . . . . .	71
tag_search . . . . .	73
tag_show . . . . .	74
user_activity_list . . . . .	75
user_create . . . . .	76
user_delete . . . . .	77
user_followee_count . . . . .	78
user_follower_count . . . . .	79
user_follower_list . . . . .	80
user_list . . . . .	81
user_show . . . . .	82
<b>Index</b>	<b>84</b>

---

ckanr-package                      *R client for the CKAN API*

---

## Description

ckanr is a full client for the CKAN API, wrapping all APIs, including for reading and writing data. Please get in touch (<https://github.com/ropensci/ckanr/issues> or <https://discuss.ropensci.org/>) if you have problems, or have use cases that we don't cover yet.

## CKAN API

Document for the CKAN API is at <https://docs.ckan.org/en/latest/api/index.html>. We'll always be following the latest version of the API.

## ckanr package API

The functions can be grouped into those for setup, packages, resources, tags, organizations, groups, and users.

- Setup - The main one is [ckanr\\_setup\(\)](#) - and many related functions, e.g., [get\\_default\\_key\(\)](#)

- Packages - Create a package with `package_create()`, and see other functions starting with `package_*`
- Resources - Create a package with `resource_create()`, and see other functions starting with `resource_*`
- Tags - List tags with `tag_list()`, and see other functions starting with `tag_*`
- Organizations - List organizations with `organization_list()`, show a specific organization with `organization_show()`, and create with `organization_create()`
- Groups - List groups with `group_list()`, and see other functions starting with `group_*`
- Users - List users with `user_list()`, and see other functions starting with `user_*`
- Related items - See functions starting with `related_*`

### Datastore

We are also working on supporting the Datastore extension (<https://docs.ckan.org/en/latest/maintaining/datastore.html>). We currently have these functions:

- `ds_create()`
- `ds_create_dataset()`
- `ds_search()`
- `ds_search_sql()`

### Fetch

Data can come back in a huge variety of formats. We've attempted a function to help you fetch not just metadata but the actual data for a link to a file on a CKAN instance. Though if you know what you're doing, you can easily use whatever is your preferred tool for the job (e.g., maybe you like `read.csv()` for reading csv files).

### CKAN Instances

We have a helper function (`servers()`) that spits out the current CKAN instances we know about, with URLs to their base URLs that should work using this package. That is, not necessarily landing pages of each instance, although, the URL may be the landing page and the base API URL.

### Author(s)

Scott Chamberlain <myrmecocystus@gmail.com>

Florian Mayer <florian.wendelin.mayer@gmail.com>

Wush Wu

Immanuel Costigan <i.costigan@me.com>

---

as.ckan\_group      *ckan\_group class helpers*

---

**Description**

ckan\_group class helpers

**Usage**

```
as.ckan_group(x, ...)
```

```
is.ckan_group(x)
```

**Arguments**

x	Variety of things, character, list, or ckan_group class object
...	Further args passed on to <a href="#">group_show()</a> if character given

**Examples**

```
## Not run:
ckanr_setup(url = "https://demo.ckan.org/", key = getOption("ckan_demo_key"))

(grps <- group_list())
grps[[3]]

# create item class from only an item ID
as.ckan_group(grps[[3]]$id)

# gives back itself
(x <- as.ckan_group(grps[[3]]$id))
as.ckan_group(x)

## End(Not run)
```

---

as.ckan\_organization      *ckan\_organization class helpers*

---

**Description**

ckan\_organization class helpers

**Usage**

```
as.ckan_organization(x, ...)
```

```
is.ckan_organization(x)
```

**Arguments**

x                    Variety of things, character, list, or ckan\_organization class object  
 ...                  Further args passed on to `organization_show()` if character given

**Examples**

```
## Not run:
ckanr_setup(url = "https://demo.ckan.org/",
key = getOption("ckan_demo_key"))

(orgs <- organization_list(limit = 3))
orgs[[3]]

# create item class from only an item ID
as.ckan_organization(orgs[[3]]$id)

# gives back itself
(x <- as.ckan_organization(orgs[[3]]$id))
as.ckan_organization(x)

## End(Not run)
```

---

as.ckan\_package            *ckan\_package class helpers*

---

**Description**

ckan\_package class helpers

**Usage**

```
as.ckan_package(x, ...)
```

```
is.ckan_package(x)
```

**Arguments**

x                    Variety of things, character, list, or ckan\_package class object  
 ...                  Further args passed on to `package_show()` if character given. In particular, if GET is not supported you can try the `http_method` parameter to set a different HTTP verb

**Examples**

```
## Not run:
ckanr_setup(url = "https://demo.ckan.org/",
  key = getOption("ckan_demo_key"))

(pkgs <- package_search())
pkgs$results
pkgs$results[[3]]

# create item class from only an item ID
as.ckan_package(pkgs$results[[3]]$id)

# gives back itself
(x <- as.ckan_package(pkgs$results[[3]]$id))
as.ckan_package(x)

## End(Not run)
```

---

as.ckan\_related      *ckan\_related class helpers*

---

**Description**

ckan\_related class helpers

**Usage**

```
as.ckan_related(x, ...)
```

```
is.ckan_related(x)
```

**Arguments**

x	Variety of things, character, list, or ckan_related class object
...	Further args passed on to <a href="#">related_show()</a> if character given

**Examples**

```
## Not run:
ckanr_setup(url = "https://demo.ckan.org/",
  key = getOption("ckan_demo_key"))

(x <- package_create("foobbbbarrrrr") %>%
  related_create(title = "my resource",
    type = "visualization"))

# create item class from only an item ID
as.ckan_related(x$id)
```

```
# gives back itself
(x <- as.ckan_related(x$id))
as.ckan_related(x)

## End(Not run)
```

---

as.ckan\_resource      *ckan\_resource class helpers*

---

## Description

ckan\_resource class helpers

## Usage

```
as.ckan_resource(x, ...)

is.ckan_resource(x)
```

## Arguments

x	Variety of things, character, list, or ckan_package class object
...	Further args passed on to <a href="#">resource_show()</a> if character given

## Examples

```
## Not run:
ckanr_setup(url = "https://demo.ckan.org/",
key = getOption("ckan_demo_key"))

(resrcs <- resource_search(q = 'name:data'))
resrcs$results
resrcs$results[[3]]

# create item class from only an item ID
as.ckan_resource(resrcs$results[[3]]$id)

# gives back itself
(x <- as.ckan_resource(resrcs$results[[3]]$id))
as.ckan_resource(x)

## End(Not run)
```



---

as.ckan\_tag                    *ckan\_tag class helpers*

---

**Description**

ckan\_tag class helpers

**Usage**

```
as.ckan_tag(x, ...)
```

```
is.ckan_tag(x)
```

**Arguments**

x                    Variety of things, character, list, or ckan\_tag class object  
...                    Further args passed on to [tag\\_show\(\)](#) if character given

**Examples**

```
## Not run:  
ckanr_setup(url = "https://demo.ckan.org/",  
key = getOption("ckan_demo_key"))  
  
(tags <- tag_search(query = 'ta'))  
tags[[3]]  
  
# create item class from only an item ID  
as.ckan_tag(tags[[3]]$id)  
  
# gives back itself  
(x <- as.ckan_tag(tags[[3]]$id))  
as.ckan_tag(x)  
  
## End(Not run)
```

---

as.ckan\_user                    *ckan\_user class helpers*

---

**Description**

ckan\_user class helpers

**Usage**

```
as.ckan_user(x, ...)
```

```
is.ckan_user(x)
```

**Arguments**

x                   Variety of things, character, list, or ckan\_user class object  
 ...                 Further args passed on to `user_show()` if character given

**Examples**

```
## Not run:
ckanr_setup(url = "https://demo.ckan.org/",
  key = getOption("ckan_demo_key"))

(usr <- user_list())
usr[1:3]
usr[[3]]

# create item class from only an item ID
as.ckan_user(usr[[3]]$id)

# gives back itself
(x <- as.ckan_user(usr[[3]]$id))
as.ckan_user(x)

## End(Not run)
```

---

 changes

---

*Get an activity stream of recently changed datasets on a site.*


---

**Description**

Get an activity stream of recently changed datasets on a site.

**Usage**

```
changes(
  offset = 0,
  limit = 31,
  url = get_default_url(),
  key = get_default_key(),
  as = "list",
  ...
)
```

**Arguments**

offset             (numeric) Where to start getting activity items from (optional, default: 0)  
 limit             (numeric) The maximum number of activities to return (optional, default: 31)  
 url               Base url to use. Default: `https://data.ontario.ca/` See also `ckanr_setup` and `get_default_url`.

key            A privileged CKAN API key, Default: your key set with [ckanr\\_setup](#)

as             (character) One of list (default), table, or json. Parsing with table option uses `jsonlite::fromJSON(..., simplifyDataFrame = TRUE)`, which attempts to parse data to `data.frame`'s when possible, so the result can vary from a vector, list or `data.frame`. (required)

...            Curl args passed on to [verb-POST](#) (optional)

### Examples

```
## Not run:
changes()
changes(as = 'json')
changes(as = 'table')
```

```
## End(Not run)
```

---

ckanr-deprecated            *Deprecated functions in **ckanr***

---

### Description

These functions still work but will be removed (defunct) in the next version.

### Details

- [ds\\_create\\_dataset\(\)](#): The functionality of this function is already in another function in this package. See function [resource\\_create\(\)](#)

---

ckanr\_settings            *Get or set ckanr CKAN settings*

---

### Description

Get or set ckanr CKAN settings

### Usage

```
ckanr_settings()

get_default_url()

get_default_key()

get_test_url()
```

```

get_test_key()

get_test_did()

get_test_rid()

get_test_gid()

get_test_oid()

get_test_behaviour()

```

### Value

ckanr\_settings prints your base url, API key (if used), and optional test server settings (URL, API key, a dataset ID and a resource ID). ckanr\_setup sets your production and test settings, while get\_test\_\* get each of those respective settings. test\_behaviour indicates whether the CKANR test suite will skip ("SKIP") or fail ("FAIL") writing tests in case the configured test CKAN settings don't work.

### See Also

[ckanr\\_setup\(\)](#), [get\\_default\\_url\(\)](#), [get\\_default\\_key\(\)](#), [get\\_test\\_url\(\)](#), [get\\_test\\_key\(\)](#), [get\\_test\\_did\(\)](#), [get\\_test\\_rid\(\)](#), [get\\_test\\_gid\(\)](#), [get\\_test\\_oid](#), [get\\_test\\_behaviour](#)

### Examples

```
ckanr_settings()
```

---

ckanr_setup	<i>Configure default CKAN settings</i>
-------------	--

---

### Description

Configure default CKAN settings

### Usage

```

ckanr_setup(
  url = "https://data.ontario.ca/",
  key = NULL,
  test_url = NULL,
  test_key = NULL,
  test_did = NULL,
  test_rid = NULL,
  test_gid = NULL,
  test_oid = NULL,
  test_behaviour = NULL,

```

```

    proxy = NULL
  )

```

### Arguments

url	A CKAN URL (optional), default: <a href="https://data.ontario.ca">https://data.ontario.ca</a>
key	A CKAN API key (optional, character)
test_url	(optional, character) A valid CKAN URL for testing purposes
test_key	(optional, character) A valid CKAN API key privileged to create datasets at test_url
test_did	(optional, character) A valid CKAN dataset ID, existing at test_url
test_rid	(optional, character) A valid CKAN resource ID, attached to did
test_gid	(optional, character) A valid CKAN group name at test_url
test_oid	(optional, character) A valid CKAN organization name at test_url
test_behaviour	(optional, character) Whether to fail ("FAIL") or skip ("SKIP") writing tests in case of problems with the configured test CKAN.
proxy	an object of class request from a call to <a href="#">crul::proxy()</a>

### Details

[ckanr\\_setup\(\)](#) sets CKAN connection details. `ckanr`'s functions default to use the default URL and API key unless specified explicitly.

`ckanr`'s automated tests require a valid CKAN URL, a privileged API key for that URL, plus the IDs of an existing dataset and an existing resource, respectively.

The writing tests (create, update, delete) can fail for two reasons: failures in `ckanr`'s code which the tests aim to detect, or failures in the configured CKAN, which are not necessarily a problem with `ckanr`'s code but prevent the tests to prove otherwise.

Setting `test_behaviour` to "SKIP" will allow writing tests to skip if the configured test CKAN fails. This is desirable to e.g. test the other functions even if the tester has no write access to a CKAN instance.

Setting `test_behaviour` to "FAIL" will let the tester find any problems with both the configured test CKAN and the writing functions.

### Examples

```

# CKAN users without admin/editor privileges could run:
ckanr_setup(url = "https://data.ontario.ca/")

# Privileged CKAN editor/admin users can run:
ckanr_setup(url = "https://data.ontario.ca/", key = "some-CKAN-API-key")

# ckanR developers/testers can run:
ckanr_setup(url = "https://data.ontario.ca/", key = "some-CKAN-API-key",
            test_url = "http://test-ckan.gov/", test_key = "test-ckan-API-key",
            test_did = "test-ckan-dataset-id", test_rid = "test-ckan-resource-id",
            test_gid = "test-group-name", test_oid = "test-organization-name",

```

```

        test_behaviour = "FAIL")

# Not specifying the default CKAN URL will reset the CKAN URL to its default
# "https://data.ontario.ca/":
ckanr_setup()

# set a proxy
ckanr_setup(proxy = crul::proxy("64.251.21.73:8080"))
ckanr_settings()
## run without setting proxy to reset to no proxy
ckanr_setup()
ckanr_settings()

```

---

ckan\_classes

*ckanr S3 classes*


---

## Description

ckanr S3 classes

## The classes

- `ckan_package` - CKAN package
- `ckan_resource` - CKAN resource
- `ckan_related` - CKAN related item

## Coercion

The functions `as.ckan_*` for each CKAN object type coerce something to a S3 class of that type. For example, you can coerce a package ID as a character string into an `ckan_package` object by calling `as.ckan_package(<id>)`.

## Testing for classes

To test whether an object is of a particular `ckan_*` class, there is a `is._ckan_*` function for all of the classes listed above. You can use one of those functions to get a logical back, TRUE or FALSE.

## Manipulation

These are simple S3 classes, basically an R list with an attached class so we can know what to do with the object and have flexible inputs and outputs from functions. You can edit one of these classes yourself by simply changing values in the list.

---

`ckan_fetch`*Download a file*

---

### Description

Download a file

### Usage

```
ckan_fetch(  
  x,  
  store = "session",  
  path = "file",  
  format = NULL,  
  key = get_default_key(),  
  ...  
)
```

### Arguments

<code>x</code>	URL for the file
<code>store</code>	One of session (default) or disk. session stores in R session, and disk saves the file to disk.
<code>path</code>	if store="disk", you must give a path to store file to
<code>format</code>	Format of the file. Required if format is not detectable through file URL.
<code>key</code>	A CKAN API key (optional, character)
<code>...</code>	Arguments passed on to the function used to read the file, if store="session". See details.

### Details

The `...` argument can be used to pass additional arguments to the function that actually reads the file. It is only used when store="session" and if the file is *not* a ZIP file.

This list shows what function is used to read what file format, so that you can see what additional arguments are available:

- csv: [read.csv](#)
- xls, xlsx: [read\\_excel](#)
- xml: [read\\_xml](#)
- html: [read\\_html](#)
- json: [fromJSON](#)
- shp, geojson: [st\\_read](#)
- txt: [read.table](#)

**Examples**

```

## Not run:
# CSV file
ckanr_setup("http://datamx.io")
res <- resource_show(id = "6145a539-cbde-4b0d-a3d3-d1a5eb013f5c",
as = "table")
head(ckan_fetch(res$url))
ckan_fetch(res$url, "disk", "myfile.csv")

# CSV file, format not available
ckanr_setup("https://ckan0.cf.opendata.inter.prod-toronto.ca")
res <- resource_show(id = "c57c3e1c-20e2-470f-bc82-e39a0264be31",
as = "table")
res$url
res$format
head(ckan_fetch(res$url, format = res$format))

# Excel file - requires readxl package
ckanr_setup("http://datamx.io")
res <- resource_show(id = "e883510e-a082-435c-872a-c5b915857ae1",
as = "table")
head(ckan_fetch(res$url))

# Excel file, multiple sheets - requires readxl package
ckanr_setup()
res <- resource_show(id = "ce02a1cf-35f1-41df-91d9-11ed1fdd4186",
as = "table")
x <- ckan_fetch(res$url)
names(x)
head(x[["Mayor - Maire"]])

# XML file - requires xml2 package
# ckanr_setup("http://data.ottawa.ca")
# res <- resource_show(id = "380061c1-6c46-4da6-a01b-7ab0f49a881e",
# as = "table")
# ckan_fetch(res$url)

# HTML file - requires xml2 package
ckanr_setup("http://open.canada.ca/data/en")
res <- resource_show(id = "80321bac-4283-487c-93bd-c65acaa660f5",
as = "table")
ckan_fetch(res$url)
library("xml2")
xml_text(xml_find_first(xml_children(ckan_fetch(res$url)))[[1]], "title"))

# JSON file, by default reads in to a data.frame for ease of use
ckanr_setup("http://data.surrey.ca")
res <- resource_show(id = "8d07c662-800d-4977-9e3e-5a3d2d1e99ab",
as = "table")
head(ckan_fetch(res$url))

# SHP file (spatial data, ESRI format) - requires sf package

```



```

ckanr_setup("https://ckan0.cf.opendata.inter.prod-toronto.ca")
res <- resource_show(id = "27362290-8bbf-434b-a9de-325a6c2ef923",
as = "table")
x <- ckan_fetch(res$url)
class(x)
plot(x[, c("AREA_NAME", "geometry")])

# GeoJSON file - requires sf package
ckanr_setup("http://datamx.io")
res <- resource_show(id = "b1cd35b7-479e-4fa0-86e9-e897d3c617e6",
as = "table")
x <- ckan_fetch(res$url)
class(x)
plot(x[, c("mun_name", "geometry")])

# ZIP file - packages required depends on contents
ckanr_setup("https://ckan0.cf.opendata.inter.prod-toronto.ca")
res <- resource_show(id = "bb21e1b8-a466-41c6-8bc3-3c362cb1ed55",
as = "table")
x <- ckan_fetch(res$url)
names(x)
head(x[["ChickenpoxAgegroups2017.csv"]])

# TXT file
ckanr_setup("https://ckan0.cf.opendata.inter.prod-toronto.ca")
res <- resource_show(id = "e4211f49-611f-438c-a444-aaa7f3f84117",
as = "table")
x <- ckan_fetch(res$url)
head(x)

# TXT file, semicolon used as separator
ckanr_setup("https://data.coat.no")
res <- resource_show(id = "384fe537-e0bd-4e57-8a0d-420b7a745196",
as = "table")
x <- ckan_fetch(res$url, sep = ";")
head(x)

## End(Not run)

```

---

ckan\_info

*Get information on a CKAN server*


---

## Description

Get information on a CKAN server

## Usage

```
ckan_info(url = get_default_url(), ...)
```

```
ckan_version(url = get_default_url(), ...)
```

**Arguments**

url	Base url to use. Default: <a href="https://data.ontario.ca">https://data.ontario.ca</a> . See also <a href="#">ckanr_setup()</a> and <a href="#">get_default_url()</a> . (required)
...	Curl args passed on to <a href="#">crul::verb-GET</a> (optional)

**Value**

for `ckan_info` a list with many slots with various info. for `ckan_version`, list of length two, with actual version as character, and another with version converted to numeric (any dots or letters removed)

**Examples**

```
## Not run:
ckan_info()
ckan_info(servers()[5])

ckan_version(servers()[5])

## End(Not run)
```

---

dashboard\_activity\_list

*Authorized user's dashboard activity stream*

---

**Description**

Authorized user's dashboard activity stream

**Usage**

```
dashboard_activity_list(
  limit = 31,
  offset = 0,
  url = get_default_url(),
  key = get_default_key(),
  as = "list",
  ...
)
```

**Arguments**

limit	(integer) The maximum number of activities to return (optional). Default: 31
offset	(integer) Where to start getting activity items from (optional). Default: 0
url	Base url to use. Default: <a href="https://data.ontario.ca/">https://data.ontario.ca/</a> See also <a href="#">ckanr_setup</a> and <a href="#">get_default_url</a> .

key A privileged CKAN API key, Default: your key set with [ckanr\\_setup](#)

as (character) One of list (default), table, or json. Parsing with table option uses `jsonlite::fromJSON(..., simplifyDataFrame = TRUE)`, which attempts to parse data to data.frame's when possible, so the result can vary from a vector, list or data.frame. (required)

... Curl args passed on to [verb-POST](#) (optional)

### Examples

```
## Not run:
# Setup
ckanr_setup(url = "https://demo.ckan.org/", key = getOption("ckan_demo_key"))

# get activity
(res <- dashboard_activity_list())

## End(Not run)
```

---

dashboard_count	<i>Number of new activities of an authorized user</i>
-----------------	---

---

### Description

Number of new activities of an authorized user

### Usage

```
dashboard_count(
  url = get_default_url(),
  key = get_default_key(),
  as = "list",
  ...
)
```

### Arguments

url Base url to use. Default: <https://data.ontario.ca/> See also [ckanr\\_setup](#) and [get\\_default\\_url](#).

key A privileged CKAN API key, Default: your key set with [ckanr\\_setup](#)

as (character) One of list (default), table, or json. Parsing with table option uses `jsonlite::fromJSON(..., simplifyDataFrame = TRUE)`, which attempts to parse data to data.frame's when possible, so the result can vary from a vector, list or data.frame. (required)

... Curl args passed on to [verb-POST](#) (optional)

## Details

Important: Activities from the user herself are not counted by this function even though they appear in the dashboard (users don't want to be notified about things they did themselves).

## Examples

```
## Not run:
# Setup
ckanr_setup(url = "https://demo.ckan.org/", key = getOption("ckan_demo_key"))

# count
dashboard_count()

## End(Not run)
```

---

ds\_create

*Add a new table to a datastore*


---

## Description

BEWARE: This function still doesn't quite work yet.

## Usage

```
ds_create(
  resource_id = NULL,
  resource = NULL,
  force = FALSE,
  aliases = NULL,
  fields = NULL,
  records = NULL,
  primary_key = NULL,
  indexes = NULL,
  url = get_default_url(),
  key = get_default_key(),
  as = "list",
  ...
)
```

## Arguments

resource_id	(string) Resource id that the data is going to be stored against.
resource	(dictionary) Resource dictionary that is passed to <a href="#">resource_create()</a> . Use instead of resource_id (optional)
force	(logical) Set to TRUE to edit a read-only resource. Default: FALSE
aliases	(character) Names for read only aliases of the resource. (optional)

fields	(list) Fields/columns and their extra metadata. (optional)
records	(list) The data, eg: [{"dob": "2005", "some_stuff": ["a", "b"]}]] (optional)
primary_key	(character) Fields that represent a unique key (optional)
indexes	(character) Indexes on table (optional)
url	Base url to use. Default: <a href="https://data.ontario.ca/">https://data.ontario.ca/</a> See also <a href="#">ckanr_setup</a> and <a href="#">get_default_url</a> .
key	A privileged CKAN API key, Default: your key set with <a href="#">ckanr_setup</a>
as	(character) One of list (default), table, or json. Parsing with table option uses <code>jsonlite::fromJSON(..., simplifyDataFrame = TRUE)</code> , which attempts to parse data to <code>data.frame</code> 's when possible, so the result can vary from a vector, list or <code>data.frame</code> . (required)
...	Curl args passed on to <a href="#">verb-POST</a> (optional)

## References

[http://bit.ly/ds\\_create](http://bit.ly/ds_create)

## Examples

```
## Not run:
ckanr_setup(url = "https://demo.ckan.org/",
  key = getOption("ckan_demo_key"))

# create a package
(res <- package_create("foobarrrrr", author="Jane Doe"))

# then create a resource
file <- system.file("examples", "actinidiaceae.csv", package = "ckanr")
(xx <- resource_create(package_id = res$id,
  description = "my resource",
  name = "bears",
  upload = file,
  rcurl = "http://google.com"
))
ds_create(resource_id = xx$id, records = iris, force = TRUE)
resource_show(xx$id)

## End(Not run)
```

---

ds\_create\_dataset

*Datstore - create a new resource on an existing dataset*

---

## Description

Datstore - create a new resource on an existing dataset

**Usage**

```
ds_create_dataset(
  package_id,
  name,
  path,
  url = get_default_url(),
  key = get_default_key(),
  as = "list",
  ...
)
```

**Arguments**

package_id	(character) Existing package ID (required)
name	(character) Name of the new resource (required)
path	(character) Path of the file to add (required)
url	Base url to use. Default: <a href="https://data.ontario.ca/">https://data.ontario.ca/</a> See also <a href="#">ckanr_setup</a> and <a href="#">get_default_url</a> .
key	A privileged CKAN API key, Default: your key set with <a href="#">ckanr_setup</a>
as	(character) One of list (default), table, or json. Parsing with table option uses <code>jsonlite::fromJSON(..., simplifyDataFrame = TRUE)</code> , which attempts to parse data to <code>data.frame</code> 's when possible, so the result can vary from a vector, list or <code>data.frame</code> . (required)
...	Curl args passed on to <a href="#">verb-POST</a> (optional)

**Details**

This function is deprecated - will be defunct in the next version of this package

**References**

[http://docs.ckan.org/en/latest/api/index.html#ckan.logic.action.create.resource\\_create](http://docs.ckan.org/en/latest/api/index.html#ckan.logic.action.create.resource_create)

**Examples**

```
## Not run:
path <- system.file("examples", "actinidiaceae.csv", package = "ckanr")
ckanr_setup(url = "https://demo.ckan.org/", key = "my-demo-ckan-org-api-key")
ds_create_dataset(package_id='testingagain', name="mydata", path = path)

# Testing: see ?ckanr_setup to set test settings
ckanr_setup(test_url = "http://my-ckan.org/",
            test_key = "my-ckan-api-key",
            test_did="an-existing-package-id",
            test_rid="an-existing-resource-id")
ds_create_dataset(package_id=get_test_pid(), name="mydata",
                 path=system.file("examples",
                                 "actinidiaceae.csv",
```

```

                                package = "ckanr"),
key = get_test_key(),
url = get_test_url())

## End(Not run)

```

---

ds\_search

*Datastore - search or get a dataset from CKAN datastore*


---

## Description

Datastore - search or get a dataset from CKAN datastore

## Usage

```

ds_search(
  resource_id = NULL,
  filters = NULL,
  q = NULL,
  plain = NULL,
  language = NULL,
  fields = NULL,
  offset = NULL,
  limit = NULL,
  sort = NULL,
  url = get_default_url(),
  key = get_default_key(),
  as = "list",
  ...
)

```

## Arguments

resource_id	(character) id or alias of the resource to be searched against
filters	(character) matching conditions to select, e.g {"key1": "a", "key2": "b"} (optional)
q	(character) full text query (optional)
plain	(character) treat as plain text query (optional, default: TRUE)
language	(character) language of the full text query (optional, default: english)
fields	(character) fields to return (optional, default: all fields in original order)
offset	(numeric) Where to start getting activity items from (optional, default: 0)
limit	(numeric) The maximum number of activities to return (optional, default: 100)
sort	Field to sort on. You can specify ascending (e.g., score desc) or descending (e.g., score asc), sort by two fields (e.g., score desc, price asc), or sort by a function (e.g., sum(x_f, y_f) desc, which sorts by the sum of x_f and y_f in a descending order). (optional)

url	Base url to use. Default: <a href="https://data.ontario.ca/">https://data.ontario.ca/</a> See also <a href="#">ckanr_setup</a> and <a href="#">get_default_url</a> .
key	A privileged CKAN API key, Default: your key set with <a href="#">ckanr_setup</a>
as	(character) One of list (default), table, or json. Parsing with table option uses <code>jsonlite::fromJSON(..., simplifyDataFrame = TRUE)</code> , which attempts to parse data to <code>data.frame</code> 's when possible, so the result can vary from a vector, list or <code>data.frame</code> . (required)
...	Curl args passed on to <code>verb-POST</code> (optional)

### Details

From the help for this method "The `datastore_search` action allows you to search data in a resource. DataStore resources that belong to private CKAN resource can only be read by you if you have access to the CKAN resource and send the appropriate authorization."

Setting `plain=FALSE` enables the entire PostgreSQL *full text search query language*. A listing of all available resources can be found at the alias *table\_metadata* full text search query language: <http://www.postgresql.org/docs/9.1/static/datatype-textsearch.html#DATATYPE-TSQUERY>

### Examples

```
## Not run:
ckanr_setup(url = 'https://data.nhm.ac.uk/')

ds_search(resource_id = '8f0784a6-82dd-44e7-b105-6194e046eb8d')
ds_search(resource_id = '8f0784a6-82dd-44e7-b105-6194e046eb8d',
  as = "table")
ds_search(resource_id = '8f0784a6-82dd-44e7-b105-6194e046eb8d',
  as = "json")

ds_search(resource_id = '8f0784a6-82dd-44e7-b105-6194e046eb8d', limit = 1,
  as = "table")
ds_search(resource_id = '8f0784a6-82dd-44e7-b105-6194e046eb8d', q = "a*")

## End(Not run)
```

---

ds\_search\_sql

*Datastore - search or get a dataset from CKAN datastore*

---

### Description

Datastore - search or get a dataset from CKAN datastore

### Usage

```
ds_search_sql(
  sql,
  url = get_default_url(),
```



```

    key = get_default_key(),
    as = "list",
    ...
)

```

### Arguments

sql	(character) A single SQL select statement. (required)
url	Base url to use. Default: <a href="https://data.ontario.ca/">https://data.ontario.ca/</a> See also <a href="#">ckanr_setup</a> and <a href="#">get_default_url</a> .
key	A privileged CKAN API key, Default: your key set with <a href="#">ckanr_setup</a>
as	(character) One of list (default), table, or json. Parsing with table option uses <code>jsonlite::fromJSON(..., simplifyDataFrame = TRUE)</code> , which attempts to parse data to <code>data.frame</code> 's when possible, so the result can vary from a vector, list or <code>data.frame</code> . (required)
...	Curl args passed on to <a href="#">verb-POST</a> (optional)

### Examples

```

## Not run:
url <- 'https://demo.ckan.org/'
sql <- 'SELECT * from "f4129802-22aa-4437-b9f9-8a8f3b7b2a53" LIMIT 2'
ds_search_sql(sql, url = url, as = "table")
sql2 <- 'SELECT "Species", "Genus", "Family" from "f4129802-22aa-4437-b9f9-8a8f3b7b2a53" LIMIT 2'
ds_search_sql(sql2, url = url, as = "table")

## End(Not run)

```

---

group_create	<i>Create a group</i>
--------------	-----------------------

---

### Description

Create a group

### Usage

```

group_create(
  name = NULL,
  id = NULL,
  title = NULL,
  description = NULL,
  image_url = NULL,
  type = NULL,
  state = "active",
  approval_status = NULL,
  extras = NULL,

```

```

    packages = NULL,
    groups = NULL,
    users = NULL,
    url = get_default_url(),
    key = get_default_key(),
    as = "list",
    ...
)

```

### Arguments

name	(character) the name of the new dataset, must be between 2 and 100 characters long and contain only lowercase alphanumeric characters, <ul style="list-style-type: none"> <li>• and _, e.g. 'warandpeace'</li> </ul>
id	(character) The id of the group (optional)
title	(character) The title of the dataset (optional, default: same as name)
description	(character) The description of the group (optional)
image_url	(character) The URL to an image to be displayed on the group's page (optional)
type	(character) The type of the dataset (optional), IDatasetForm plugins associate themselves with different dataset types and provide custom dataset handling behaviour for these types
state	(character) The current state of the dataset, e.g. 'active' or 'deleted', only active datasets show up in search results and other lists of datasets, this parameter will be ignored if you are not authorized to change the state of the dataset (optional, default: 'active')
approval_status	(character) Approval status (optional)
extras	(list of dataset extra dictionaries) The dataset's extras (optional), extras are arbitrary (key: value) metadata items that can be added to datasets, each extra dictionary should have keys 'key' (a string), 'value' (a string)
packages	(data.frame) The datasets (packages) that belong to the group, a data.frame, where each row has column 'name' (string, the id or name of the dataset) and optionally 'title' (string, the title of the dataset)
groups	(data.frame) The groups to which the dataset belongs (optional), each data.frame row should have one or more of the following columns which identify an existing group: 'id' (the id of the group, string), or 'name' (the name of the group, string), to see which groups exist call <a href="#">group_list()</a>
users	(list of dictionaries) The users that belong to the group, a list of dictionaries each with key 'name' (string, the id or name of the user) and optionally 'capacity' (string, the capacity in which the user is a member of the group)
url	Base url to use. Default: <a href="https://data.ontario.ca/">https://data.ontario.ca/</a> See also <a href="#">ckanr_setup</a> and <a href="#">get_default_url</a> .
key	A privileged CKAN API key, Default: your key set with <a href="#">ckanr_setup</a>

as (character) One of list (default), table, or json. Parsing with table option uses `jsonlite::fromJSON(..., simplifyDataFrame = TRUE)`, which attempts to parse data to `data.frame`'s when possible, so the result can vary from a vector, list or `data.frame`. (required)

... Curl args passed on to `verb-POST` (optional)

### Examples

```
## Not run:
# Setup
ckanr_setup(url = "https://demo.ckan.org", key = getOption("ckan_demo_key"))

# create a group
(res <- group_create("fruitloops2", description="A group about fruitloops"))
res$users
res$num_followers

## End(Not run)
```

---

group_delete	<i>Delete a group</i>
--------------	-----------------------

---

### Description

Delete a group

### Usage

```
group_delete(id, url = get_default_url(), key = get_default_key(), ...)
```

### Arguments

id (character) The id of the group. Required.

url Base url to use. Default: `https://data.ontario.ca` See also `ckanr_setup()` and `get_default_url()`

key A privileged CKAN API key, Default: your key set with `ckanr_setup`

... Curl args passed on to `curl::verb-POST` (optional)

### Examples

```
## Not run:
# Setup
ckanr_setup(url = "https://demo.ckan.org", key = getOption("ckan_demo_key"))

# create a group
(res <- group_create("lions", description="A group about lions"))

# show the group
```

```

group_show(res$id)

# delete the group
group_delete(res)
## or with it's id
# group_delete(res$id)

## End(Not run)

```

---

group\_list

*List groups.*


---

## Description

List groups.

## Usage

```

group_list(
  offset = 0,
  limit = 31,
  sort = NULL,
  groups = NULL,
  all_fields = FALSE,
  url = get_default_url(),
  key = get_default_key(),
  as = "list",
  ...
)

```

## Arguments

offset	(numeric) Where to start getting activity items from (optional, default: 0)
limit	(numeric) The maximum number of activities to return (optional, default: 31)
sort	Field to sort on. You can specify ascending (e.g., score desc) or descending (e.g., score asc), sort by two fields (e.g., score desc, price asc), or sort by a function (e.g., sum(x_f, y_f) desc, which sorts by the sum of x_f and y_f in a descending order).
groups	(character) A list of names of the groups to return, if given only groups whose names are in this list will be returned
all_fields	(logical) Return full group dictionaries instead of just names. Default: FALSE
url	Base url to use. Default: <a href="https://data.ontario.ca/">https://data.ontario.ca/</a> See also <a href="#">ckanr_setup</a> and <a href="#">get_default_url</a> .
key	A privileged CKAN API key, Default: your key set with <a href="#">ckanr_setup</a>

as (character) One of list (default), table, or json. Parsing with table option uses `jsonlite::fromJSON(..., simplifyDataFrame = TRUE)`, which attempts to parse data to `data.frame`'s when possible, so the result can vary from a vector, list or `data.frame`. (required)

... Curl args passed on to `verb-POST` (optional)

### Examples

```
## Not run:
group_list(limit = 3)
group_list(limit = 3, as = 'json')
group_list(limit = 3, as = 'table')

## End(Not run)
```

---

group_patch	<i>Update a group's metadata</i>
-------------	----------------------------------

---

### Description

Update a group's metadata

### Usage

```
group_patch(
  x,
  id,
  url = get_default_url(),
  key = get_default_key(),
  as = "list",
  ...
)
```

### Arguments

x (list) A list with key-value pairs

id (character) Resource ID to update (required)

url Base url to use. Default: `https://data.ontario.ca/` See also [ckanr\\_setup](#) and [get\\_default\\_url](#).

key A privileged CKAN API key, Default: your key set with [ckanr\\_setup](#)

as (character) One of list (default), table, or json. Parsing with table option uses `jsonlite::fromJSON(..., simplifyDataFrame = TRUE)`, which attempts to parse data to `data.frame`'s when possible, so the result can vary from a vector, list or `data.frame`. (required)

... Curl args passed on to `verb-POST` (optional)

## Examples

```
## Not run:
# Setup
ckanr_setup(url = "https://demo.ckan.org", key = getOption("ckan_demo_key"))

# Create a package
(res <- group_create("hello-my-world2"))

# Get a resource
grp <- group_show(res$id)
grp$title
grp$author_email

# Make some changes
x <- list(title = "!hello world!", maintainer_email = "hello@world.com")
group_patch(x, id = grp)

## End(Not run)
```

---

group\_show

*Show a package*

---

## Description

Show a package

## Usage

```
group_show(
  id,
  include_datasets = TRUE,
  url = get_default_url(),
  key = get_default_key(),
  as = "list",
  ...
)
```

## Arguments

**id** (character) Package identifier.

**include\_datasets** (logical) Include a list of the group's datasets. Default: TRUE

**url** Base url to use. Default: <https://data.ontario.ca/> See also [ckanr\\_setup](#) and [get\\_default\\_url](#).

**key** A privileged CKAN API key, Default: your key set with [ckanr\\_setup](#)

as (character) One of list (default), table, or json. Parsing with table option uses `jsonlite::fromJSON(..., simplifyDataFrame = TRUE)`, which attempts to parse data to `data.frame`'s when possible, so the result can vary from a vector, list or `data.frame`. (required)

... Curl args passed on to `verb-POST` (optional)

### Details

By default the help and success slots are dropped, and only the result slot is returned. You can request raw json with `as = 'json'` then parse yourself to get the help slot.

### Examples

```
## Not run:
res <- group_list()

# via a group name/id
group_show(res[[1]]$name)

# or via an object of class ckan_group
group_show(res[[1]])

# return different data formats
group_show(res[[1]]$name, as = 'json')
group_show(res[[1]]$name, as = 'table')

## End(Not run)
```

---

group_update	<i>Update a group</i>
--------------	-----------------------

---

### Description

Update a group

### Usage

```
group_update(
  x,
  id,
  url = get_default_url(),
  key = get_default_key(),
  as = "list",
  ...
)
```

**Arguments**

x	(list) A list with key-value pairs
id	(character) Package identifier
url	Base url to use. Default: <a href="https://data.ontario.ca/">https://data.ontario.ca/</a> See also <a href="#">ckanr_setup</a> and <a href="#">get_default_url</a> .
key	A privileged CKAN API key, Default: your key set with <a href="#">ckanr_setup</a>
as	(character) One of list (default), table, or json. Parsing with table option uses <code>jsonlite::fromJSON(..., simplifyDataFrame = TRUE)</code> , which attempts to parse data to <code>data.frame</code> 's when possible, so the result can vary from a vector, list or <code>data.frame</code> . (required)
...	Curl args passed on to <a href="#">verb-POST</a> (optional)

**Examples**

```
## Not run:
# Setup
ckanr_setup(url = "https://demo.ckan.org/", key = getOption("ckan_demo_key"))

# First, create a group
grp <- group_create("water-bears2")
group_show(grp)

## update just chosen things
# Make some changes
x <- list(description = "A group about water bears and people that love them")

# Then update the packge
group_update(x, id = grp)

## End(Not run)
```

---

license\_list

*Return the list of licenses available for datasets on the site.*

---

**Description**

Return the list of licenses available for datasets on the site.

**Usage**

```
license_list(
  id,
  url = get_default_url(),
  key = get_default_key(),
  as = "list",
  ...
)
```



**Arguments**

id	(character) Package identifier.
url	Base url to use. Default: <a href="https://data.ontario.ca/">https://data.ontario.ca/</a> See also <a href="#">ckanr_setup</a> and <a href="#">get_default_url</a> .
key	A privileged CKAN API key, Default: your key set with <a href="#">ckanr_setup</a>
as	(character) One of list (default), table, or json. Parsing with table option uses <code>jsonlite::fromJSON(..., simplifyDataFrame = TRUE)</code> , which attempts to parse data to <code>data.frame</code> 's when possible, so the result can vary from a vector, list or <code>data.frame</code> . (required)
...	Curl args passed on to <a href="#">verb-POST</a> (optional)

**Examples**

```
## Not run:
license_list()
license_list(as = "table")
license_list(as = "json")

## End(Not run)
```

---

organization\_create    *Create an organization*

---

**Description**

Create an organization

**Usage**

```
organization_create(
  name = NULL,
  id = NULL,
  title = NULL,
  description = NULL,
  image_url = NULL,
  state = "active",
  approval_status = NULL,
  extras = NULL,
  packages = NULL,
  users = NULL,
  url = get_default_url(),
  key = get_default_key(),
  as = "list",
  ...
)
```

**Arguments**

name	(character) the name of the organization, a string between 2 and 100 characters long, containing only lowercase alphanumeric characters, <ul style="list-style-type: none"> <li>• and _</li> </ul>
id	the id of the organization (optional)
title	(character) the title of the organization (optional)
description	(character) the description of the organization (optional)
image_url	(character) the URL to an image to be displayed on the organization's page (optional)
state	(character) the current state of the organization, e.g. 'active' or 'deleted', only active organization show up in search results and other lists of organization, this parameter will be ignored if you are not authorized to change the state of the organization (optional). Default: 'active'
approval_status	(character) Approval status
extras	The organization's extras (optional), extras are arbitrary (key: value) metadata items that can be added to organizations, each extra dictionary should have keys 'key' (a string), 'value' (a string) package_relationship_create for the format of relationship dictionaries (optional)
packages	(list of dictionaries) the datasets (packages) that belong to the organization, a list of dictionaries each with keys 'name' (string, the id or name of the dataset) and optionally 'title' (string, the title of the dataset)
users	(character) the users that belong to the organization, a list of dictionaries each with key 'name' (string, the id or name of the user) and optionally 'capacity' (string, the capacity in which the user is a member of the organization)
url	Base url to use. Default: <a href="https://data.ontario.ca/">https://data.ontario.ca/</a> See also <a href="#">ckanr_setup</a> and <a href="#">get_default_url</a> .
key	A privileged CKAN API key, Default: your key set with <a href="#">ckanr_setup</a>
as	(character) One of list (default), table, or json. Parsing with table option uses <code>jsonlite::fromJSON(..., simplifyDataFrame = TRUE)</code> , which attempts to parse data to data.frame's when possible, so the result can vary from a vector, list or data.frame. (required)
...	Curl args passed on to <a href="#">verb-POST</a> (optional)

**Examples**

```
## Not run:
# Setup
ckanr_setup(url = "https://demo.ckan.org/", key = getOption("ckan_demo_key"))

# create an organization
(res <- organization_create("foobar", title = "Foo bars",
  description = "love foo bars"))
res$name

## End(Not run)
```

---

organization\_delete    *Delete an organization*

---

### Description

Delete an organization

### Usage

```
organization_delete(  
  id,  
  url = get_default_url(),  
  key = get_default_key(),  
  as = "list",  
  ...  
)
```

### Arguments

id	(character) name or id of the organization
url	Base url to use. Default: <a href="https://data.ontario.ca/">https://data.ontario.ca/</a> See also <a href="#">ckanr_setup</a> and <a href="#">get_default_url</a> .
key	A privileged CKAN API key, Default: your key set with <a href="#">ckanr_setup</a>
as	(character) One of list (default), table, or json. Parsing with table option uses <code>jsonlite::fromJSON(..., simplifyDataFrame = TRUE)</code> , which attempts to parse data to <code>data.frame</code> 's when possible, so the result can vary from a vector, list or <code>data.frame</code> . (required)
...	Curl args passed on to <a href="#">verb-POST</a> (optional)

### Value

an empty list on success

### Examples

```
## Not run:  
ckanr_setup(url = "https://demo.ckan.org", key=getOption("ckan_demo_key"))  
  
# create an organization  
(res <- organization_create("foobar", title = "Foo bars",  
  description = "love foo bars"))  
  
# delete the organization just created  
res$id  
organization_delete(id = res$id)  
  
## End(Not run)
```

---

organization\_list      *List organization*

---

### Description

List organization

### Usage

```
organization_list(
  order_by = c("name", "package"),
  decreasing = FALSE,
  organizations = NULL,
  all_fields = TRUE,
  limit = 31,
  url = get_default_url(),
  key = get_default_key(),
  as = "list",
  ...
)
```

### Arguments

order_by	(character, only the first element is used). The field to sort the list by, must be name or packages.
decreasing	(logical). Is the sort-order is decreasing or not.
organizations	(character or NULL). A list of names of the organizations to return. NULL returns all organizations.
all_fields	(logical). Return the name or all fields of the object.
limit	(numeric) The maximum number of organizations to return (optional, default: 31)
url	Base url to use. Default: <a href="https://data.ontario.ca/">https://data.ontario.ca/</a> See also <a href="#">ckanr_setup</a> and <a href="#">get_default_url</a> .
key	A privileged CKAN API key, Default: your key set with <a href="#">ckanr_setup</a>
as	(character) One of list (default), table, or json. Parsing with table option uses <code>jsonlite::fromJSON(..., simplifyDataFrame = TRUE)</code> , which attempts to parse data to data.frame's when possible, so the result can vary from a vector, list or data.frame. (required)
...	Curl args passed on to <a href="#">verb-POST</a> (optional)

### Examples

```
## Not run:
ckanr_setup(url = "https://demo.ckan.org/")
```

```
# list organizations
res <- organization_list()
res[1:2]

# Different data formats
organization_list(as = 'json')
organization_list(as = 'table')

## End(Not run)
```

---

organization\_purge      *Purge an organization*

---

## Description

IMPORTANT: You must be a sysadmin to purge an organization. Once an organization is purged, it is permanently removed from the system.

## Usage

```
organization_purge(
  id,
  url = get_default_url(),
  key = get_default_key(),
  as = "list",
  ...
)
```

## Arguments

id	(character) name or id of the organization
url	Base url to use. Default: <a href="https://data.ontario.ca/">https://data.ontario.ca/</a> See also <a href="#">ckanr_setup</a> and <a href="#">get_default_url</a> .
key	A privileged CKAN API key, Default: your key set with <a href="#">ckanr_setup</a>
as	(character) One of list (default), table, or json. Parsing with table option uses <code>jsonlite::fromJSON(..., simplifyDataFrame = TRUE)</code> , which attempts to parse data to data.frame's when possible, so the result can vary from a vector, list or data.frame. (required)
...	Curl args passed on to <a href="#">verb-POST</a> (optional)

## Value

an empty list on success

**Examples**

```
## Not run:
ckanr_setup(url = "https://demo.ckan.org", key=getOption("ckan_demo_key"))

# create an organization
(res <- organization_create("foobar", title = "Foo bars",
  description = "love foo bars"))

# delete the organization just created
res$id
organization_delete(id = res$id)

# purge the organization just deleted
res$id
organization_purge(id = res$id)

## End(Not run)
```

---

organization\_show      *Show an organization*

---

**Description**

Show an organization

**Usage**

```
organization_show(
  id,
  include_datasets = FALSE,
  url = get_default_url(),
  key = get_default_key(),
  as = "list",
  ...
)
```

**Arguments**

id	(character) Organization id or name.
include_datasets	(logical). Whether to include a list of the organization datasets
url	Base url to use. Default: <a href="https://data.ontario.ca/">https://data.ontario.ca/</a> See also <a href="#">ckanr_setup</a> and <a href="#">get_default_url</a> .
key	A privileged CKAN API key, Default: your key set with <a href="#">ckanr_setup</a>
as	(character) One of list (default), table, or json. Parsing with table option uses <code>jsonlite::fromJSON(..., simplifyDataFrame = TRUE)</code> , which attempts to parse data to <code>data.frame</code> 's when possible, so the result can vary from a vector, list or <code>data.frame</code> . (required)
...	Curl args passed on to <a href="#">verb-POST</a> (optional)

**Details**

By default the help and success slots are dropped, and only the result slot is returned. You can request raw json with `as = 'json'` then parse yourself to get the help slot.

**Examples**

```
## Not run:
ckanr_setup(url = "https://demo.ckan.org/", key = getOption("ckan_demo_key"))

res <- organization_create("stuffthings2")
organization_show(res$id)

## End(Not run)
```

---

`package_activity_list` *Return a list of the package's activity*

---

**Description**

Return a list of the package's activity

**Usage**

```
package_activity_list(
  id,
  offset = 0,
  limit = 31,
  url = get_default_url(),
  key = get_default_key(),
  as = "list",
  ...
)
```

**Arguments**

<code>id</code>	(character) Package identifier.
<code>offset</code>	(numeric) Where to start getting activity items from (optional, default: 0)
<code>limit</code>	(numeric) The maximum number of activities to return (optional, default: 31)
<code>url</code>	Base url to use. Default: <code>https://data.ontario.ca/</code> See also <a href="#">ckanr_setup</a> and <a href="#">get_default_url</a> .
<code>key</code>	A privileged CKAN API key, Default: your key set with <a href="#">ckanr_setup</a>
<code>as</code>	(character) One of <code>list</code> (default), <code>table</code> , or <code>json</code> . Parsing with <code>table</code> option uses <code>jsonlite::fromJSON(..., simplifyDataFrame = TRUE)</code> , which attempts to parse data to <code>data.frame</code> 's when possible, so the result can vary from a vector, list or <code>data.frame</code> . (required)
<code>...</code>	Curl args passed on to <code>verb-POST</code> (optional)

## Examples

```
## Not run:
# Setup
ckanr_setup(url = "https://demo.ckan.org/", key = getOption("ckan_demo_key"))

# create a package
(res <- package_create("owls64"))

# list package activity
package_activity_list(res$id)

# make a change
x <- list(maintainer = "Jane Forest")
package_update(x, res)

# list activity again
package_activity_list(res)

# output different data formats
package_activity_list(res$id, as = "table")
package_activity_list(res$id, as = "json")

## End(Not run)
```

---

package_create	<i>Create a package</i>
----------------	-------------------------

---

## Description

Create a package

## Usage

```
package_create(
  name = NULL,
  title = NULL,
  private = FALSE,
  author = NULL,
  author_email = NULL,
  maintainer = NULL,
  maintainer_email = NULL,
  license_id = NULL,
  notes = NULL,
  package_url = NULL,
  version = NULL,
  state = "active",
  type = NULL,
  resources = NULL,
```



```

    tags = NULL,
    extras = NULL,
    relationships_as_object = NULL,
    relationships_as_subject = NULL,
    groups = NULL,
    owner_org = NULL,
    url = get_default_url(),
    key = get_default_key(),
    as = "list",
    ...
)

```

### Arguments

name	(character) the name of the new dataset, must be between 2 and 100 characters long and contain only lowercase alphanumeric characters, - and _, e.g. 'warand-peace'
title	(character) the title of the dataset (optional, default: same as name)
private	(logical) whether the dataset should be private (optional, default: FALSE), requires a value for owner_org if TRUE
author	(character) the name of the dataset's author (optional)
author_email	(character) the email address of the dataset's author (optional)
maintainer	(character) the name of the dataset's maintainer (optional)
maintainer_email	(character) the email address of the dataset's maintainer (optional)
license_id	(license id string) - the id of the dataset's license, see <a href="#">license_list()</a> for available values (optional)
notes	(character) a description of the dataset (optional)
package_url	(character) a URL for the dataset's source (optional)
version	(string, no longer than 100 characters) - (optional)
state	(character) the current state of the dataset, e.g. 'active' or 'deleted', only active datasets show up in search results and other lists of datasets, this parameter will be ignored if you are not authorized to change the state of the dataset (optional, default: 'active')
type	(character) the type of the dataset (optional), IDatasetForm plugins associate themselves with different dataset types and provide custom dataset handling behaviour for these types
resources	(list of resource dictionaries) - the dataset's resources, see <a href="#">resource_create()</a> for the format of resource dictionaries (optional)
tags	(list of tag dictionaries) - the dataset's tags, see <a href="#">tag_create()</a> for the format of tag dictionaries (optional)
extras	(list of dataset extra dictionaries) - the dataset's extras (optional), extras are arbitrary (key: value) metadata items that can be added to datasets, each extra dictionary should have keys 'key' (a string), 'value' (a string)

relationships_as_object	(list of relationship dictionaries) - see <code>package_relationship_create</code> for the format of relationship dictionaries (optional)
relationships_as_subject	(list of relationship dictionaries) - see <code>package_relationship_create</code> for the format of relationship dictionaries (optional)
groups	(data.frame) the groups to which the dataset belongs, each row should have one or more of the following columns which identify an existing group: 'id' (the id of the group, string), or 'name' (the name of the group, string), to see which groups exist call <code>group_list()</code> . see example (optional)
owner_org	(character) the id of the dataset's owning organization, see <code>organization_list()</code> or <code>organization_list_for_user</code> for available values (optional)
url	Base url to use. Default: <code>https://data.ontario.ca/</code> See also <code>ckanr_setup</code> and <code>get_default_url</code> .
key	A privileged CKAN API key, Default: your key set with <code>ckanr_setup</code>
as	(character) One of list (default), table, or json. Parsing with table option uses <code>jsonlite::fromJSON(..., simplifyDataFrame = TRUE)</code> , which attempts to parse data to data.frame's when possible, so the result can vary from a vector, list or data.frame. (required)
...	Curl args passed on to <code>verb-POST</code> (optional)

### Examples

```
## Not run:
# Setup
ckanr_setup(url = "https://demo.ckan.org/", key = getOption("ckan_demo_key"))

# create a package
## Example 1
(res <- package_create("foobar4", author="Jane Doe"))
res$author

## Example 2 - create package, add a resource
(res <- package_create("helloworld", author="Jane Doe"))

# include a group
# package_create("brownbear", groups = data.frame(id = "some-id"))

## End(Not run)
```

---

package\_delete

*Delete a package*

---

### Description

Delete a package

**Usage**

```
package_delete(id, url = get_default_url(), key = get_default_key(), ...)
```

**Arguments**

`id` (character) The id of the package. Required.

`url` Base url to use. Default: <https://data.ontario.ca> See also [ckanr\\_setup\(\)](#) and [get\\_default\\_url\(\)](#)

`key` A privileged CKAN API key, Default: your key set with [ckanr\\_setup](#)

`...` Curl args passed on to [crul::verb-POST](#) (optional)

**Examples**

```
## Not run:
# Setup
ckanr_setup(url = "https://demo.ckan.org", key = getOption("ckan_demo_key"))

# create a package
(res <- package_create("lions-bears-tigers"))

# show the package
package_show(res)

# delete the package
package_delete(res)

## End(Not run)
```

---

package\_list

*List datasets.*

---

**Description**

List datasets.

**Usage**

```
package_list(
  offset = 0,
  limit = 31,
  url = get_default_url(),
  key = get_default_key(),
  as = "list",
  ...
)
```

**Arguments**

offset	(numeric) Where to start getting activity items from (optional, default: 0)
limit	(numeric) The maximum number of activities to return (optional, default: 31)
url	Base url to use. Default: <a href="https://data.ontario.ca/">https://data.ontario.ca/</a> See also <a href="#">ckanr_setup</a> and <a href="#">get_default_url</a> .
key	A privileged CKAN API key, Default: your key set with <a href="#">ckanr_setup</a>
as	(character) One of list (default), table, or json. Parsing with table option uses <code>jsonlite::fromJSON(..., simplifyDataFrame = TRUE)</code> , which attempts to parse data to <code>data.frame</code> 's when possible, so the result can vary from a vector, list or <code>data.frame</code> . (required)
...	Curl args passed on to <a href="#">verb-POST</a> (optional)

**Examples**

```
## Not run:
package_list()
package_list(as = 'json')
package_list(as = 'table')

package_list(url = 'https://data.nhm.ac.uk')

## End(Not run)
```

---

package\_list\_current *List current packages with resources.*

---

**Description**

List current packages with resources.

**Usage**

```
package_list_current(
  offset = 0,
  limit = 31,
  url = get_default_url(),
  key = get_default_key(),
  as = "list",
  ...
)
```

**Arguments**

offset	(numeric) Where to start getting activity items from (optional, default: 0)
limit	(numeric) The maximum number of activities to return (optional, default: 31)
url	Base url to use. Default: <a href="https://data.ontario.ca/">https://data.ontario.ca/</a> See also <a href="#">ckanr_setup</a> and <a href="#">get_default_url</a> .
key	A privileged CKAN API key, Default: your key set with <a href="#">ckanr_setup</a>
as	(character) One of list (default), table, or json. Parsing with table option uses <code>jsonlite::fromJSON(..., simplifyDataFrame = TRUE)</code> , which attempts to parse data to <code>data.frame</code> 's when possible, so the result can vary from a vector, list or <code>data.frame</code> . (required)
...	Curl args passed on to <a href="#">verb-POST</a> (optional)

**Examples**

```
## Not run:
package_list_current()
package_list_current(as = 'json')
package_list_current(as = 'table')

## End(Not run)
```

---

package_patch	<i>Update a package's metadata</i>
---------------	------------------------------------

---

**Description**

Update a package's metadata

**Usage**

```
package_patch(
  x,
  id = NULL,
  extras = NULL,
  http_method = "GET",
  key = get_default_key(),
  url = get_default_url(),
  as = "list",
  ...
)
```

**Arguments**

x	(list) A list with key-value pairs
id	(character) Resource ID to update (optional, required if x does not have an "id" field)
extras	(character vector) - the dataset's extras (optional), extras are arbitrary (key: value) metadata items that can be added to datasets, each extra dictionary should have keys 'key' (a string), 'value' (a string)
http_method	(character) which HTTP method (verb) to use; one of "GET" or "POST". Default: "GET"
key	A privileged CKAN API key, Default: your key set with <a href="#">ckanr_setup</a>
url	Base url to use. Default: <a href="https://data.ontario.ca/">https://data.ontario.ca/</a> See also <a href="#">ckanr_setup</a> and <a href="#">get_default_url</a> .
as	(character) One of list (default), table, or json. Parsing with table option uses <code>jsonlite::fromJSON(..., simplifyDataFrame = TRUE)</code> , which attempts to parse data to <code>data.frame</code> 's when possible, so the result can vary from a vector, list or <code>data.frame</code> . (required)
...	Curl args passed on to <code>verb-POST</code> (optional)

**Examples**

```
## Not run:
# Setup
ckanr_setup(url = "https://demo.ckan.org", key = getOption("ckan_demo_key"))

# Create a package
(res <- package_create("hello-world13", author="Jane Doe"))

# Get a resource
res <- package_show(res$id)
res$title

# patch
package_patch(res, extras = list(list(key = "foo", value = "bar")))
unclass(package_show(res))

## End(Not run)
```

---

`package_revision_list` *Return a dataset (package's) revisions as a list of dictionaries.*

---

**Description**

Return a dataset (package's) revisions as a list of dictionaries.

## Usage

```
package_revision_list(  
  id,  
  url = get_default_url(),  
  key = get_default_key(),  
  as = "list",  
  ...  
)
```

## Arguments

id	(character) Package identifier.
url	Base url to use. Default: <a href="https://data.ontario.ca/">https://data.ontario.ca/</a> See also <a href="#">ckanr_setup</a> and <a href="#">get_default_url</a> .
key	A privileged CKAN API key, Default: your key set with <a href="#">ckanr_setup</a>
as	(character) One of list (default), table, or json. Parsing with table option uses <code>jsonlite::fromJSON(..., simplifyDataFrame = TRUE)</code> , which attempts to parse data to <code>data.frame</code> 's when possible, so the result can vary from a vector, list or <code>data.frame</code> . (required)
...	Curl args passed on to <a href="#">verb-POST</a> (optional)

## Examples

```
## Not run:  
# Setup  
ckanr_setup(url = "https://demo.ckan.org/", key = getOption("ckan_demo_key"))  
  
# create a package  
(res <- package_create("dolphins"))  
  
# list package revisions  
package_revision_list(res$id)  
  
# Make change to the package  
x <- list(title = "dolphins and things")  
package_patch(x, id = res$id)  
  
# list package revisions  
package_revision_list(res$id)  
  
# Output different formats  
package_revision_list(res$id, as = "table")  
package_revision_list(res$id, as = "json")  
  
## End(Not run)
```

---

package_search	<i>Search for packages.</i>
----------------	-----------------------------

---

**Description**

Search for packages.

**Usage**

```
package_search(
  q = "*:*",
  fq = NULL,
  sort = NULL,
  rows = NULL,
  start = NULL,
  facet = FALSE,
  facet.limit = NULL,
  facet.field = NULL,
  facet.mincount = NULL,
  include_drafts = FALSE,
  include_private = FALSE,
  use_default_schema = FALSE,
  url = get_default_url(),
  key = get_default_key(),
  as = "list",
  ...
)
```

**Arguments**

q	Query terms, defaults to ':', or everything.
fq	Filter query, this does not affect the search, only what gets returned
sort	Field to sort on. You can specify ascending (e.g., score desc) or descending (e.g., score asc), sort by two fields (e.g., score desc, price asc), or sort by a function (e.g., sum(x_f, y_f) desc, which sorts by the sum of x_f and y_f in a descending order).
rows	Number of records to return. Defaults to 10.
start	Record to start at, default to beginning.
facet	(logical) Whether to return facet results or not. Default: FALSE
facet.limit	(numeric) This param indicates the maximum number of constraint counts that should be returned for the facet fields. A negative value means unlimited. Default: 100. Can be specified on a per field basis.
facet.field	(character) This param allows you to specify a field which should be treated as a facet. It will iterate over each Term in the field and generate a facet count using that Term as the constraint. This parameter can be specified multiple times to



indicate multiple facet fields. None of the other params in this section will have any effect without specifying at least one field name using this param.

facet.mincount	(integer) the minimum counts for facet fields should be included in the results
include_drafts	(logical) if TRUE draft datasets will be included. A user will only be returned their own draft datasets, and a sysadmin will be returned all draft datasets. default: FALSE. first CKAN version: 2.6.1; dropped from request if CKAN version is older or if CKAN version isn't available via <a href="#">ckan_version()</a>
include_private	(logical) if TRUE private datasets will be included. Only private datasets from the user's organizations will be returned and sysadmins will be returned all private datasets. default: FALSE first CKAN version: 2.6.1; dropped from request if CKAN version is older or if CKAN version isn't available via <a href="#">ckan_version()</a>
use_default_schema	(logical) use default package schema instead of a custom schema defined with an IDatasetForm plugin. default: FALSE first CKAN version: 2.3.5; dropped from request if CKAN version is older or if CKAN version isn't available via <a href="#">ckan_version()</a>
url	Base url to use. Default: <a href="https://data.ontario.ca/">https://data.ontario.ca/</a> See also <a href="#">ckanr_setup</a> and <a href="#">get_default_url</a> .
key	A privileged CKAN API key, Default: your key set with <a href="#">ckanr_setup</a>
as	(character) One of list (default), table, or json. Parsing with table option uses <code>jsonlite::fromJSON(..., simplifyDataFrame = TRUE)</code> , which attempts to parse data to <code>data.frame</code> 's when possible, so the result can vary from a vector, list or <code>data.frame</code> . (required)
...	Curl args passed on to <a href="#">verb-POST</a> (optional)

## Examples

```
## Not run:
ckanr_setup(url = "https://demo.ckan.org", key=getOption("ckan_demo_key"))

package_search(q = '*:*')
package_search(q = '*:*', rows = 2, as = 'json')
package_search(q = '*:*', rows = 2, as = 'table')

package_search(q = '*:*', sort = 'score asc')
package_search(q = '*:*', fq = 'num_tags:[3 TO *]')$count
package_search(q = '*:*', fq = 'num_tags:[2 TO *]')$count
package_search(q = '*:*', fq = 'num_tags:[1 TO *]')$count

## End(Not run)
```

---

package_show	<i>Show a package.</i>
--------------	------------------------

---

### Description

Show a package.

### Usage

```
package_show(
  id,
  use_default_schema = FALSE,
  http_method = "GET",
  url = get_default_url(),
  key = get_default_key(),
  as = "list",
  ...
)
```

### Arguments

id	(character/ckan_package) Package identifier, or a ckan_package object
use_default_schema	(logical) Use default package schema instead of a custom schema defined with an IDatasetForm plugin. Default: FALSE
http_method	(character) which HTTP method (verb) to use; one of "GET" or "POST". Default: "GET"
url	Base url to use. Default: <a href="https://data.ontario.ca/">https://data.ontario.ca/</a> See also <a href="#">ckanr_setup</a> and <a href="#">get_default_url</a> .
key	A privileged CKAN API key, Default: your key set with <a href="#">ckanr_setup</a>
as	(character) One of list (default), table, or json. Parsing with table option uses <code>jsonlite::fromJSON(..., simplifyDataFrame = TRUE)</code> , which attempts to parse data to <code>data.frame</code> 's when possible, so the result can vary from a vector, list or <code>data.frame</code> . (required)
...	Curl args passed on to <a href="#">verb-POST</a> (optional)

### Details

By default the help and success slots are dropped, and only the result slot is returned. You can request raw json with `as = 'json'` then parse yourself to get the help slot.

**Examples**

```
## Not run:
# Setup
ckanr_setup(url = "https://demo.ckan.org/",
  key = getOption("ckan_demo_key"))

# create a package
(res <- package_create("purposeful155"))

# show package
## From the output of package_create
package_show(res)
## Or, from the ID
package_show(res$id)

# get data back in different formats
package_show(res$id, as = 'json')
package_show(res$id, as = 'table')

# use default schema or not
package_show(res$id, TRUE)

## End(Not run)
```

---

package_update	<i>Update a package</i>
----------------	-------------------------

---

**Description**

Update a package

**Usage**

```
package_update(
  x,
  id,
  http_method = "GET",
  url = get_default_url(),
  key = get_default_key(),
  as = "list",
  ...
)
```

**Arguments**

x	(list) A list with key-value pairs
id	(character) Package identifier

http_method	(character) which HTTP method (verb) to use; one of "GET" or "POST". Default: "GET"
url	Base url to use. Default: <code>https://data.ontario.ca/</code> See also <code>ckanr_setup</code> and <code>get_default_url</code> .
key	A privileged CKAN API key, Default: your key set with <code>ckanr_setup</code>
as	(character) One of list (default), table, or json. Parsing with table option uses <code>jsonlite::fromJSON(..., simplifyDataFrame = TRUE)</code> , which attempts to parse data to <code>data.frame</code> 's when possible, so the result can vary from a vector, list or <code>data.frame</code> . (required)
...	Curl args passed on to <code>verb-POST</code> (optional)

### Examples

```
## Not run:
# Setup
ckanr_setup(url = "https://demo.ckan.org/", key = getOption("ckan_demo_key"))

# Create a package
(pkg <- package_create("hello-world11", author="Jane Doe"))

# Next show the package to see the fields
(res <- package_show(pkg$id))

## update just chosen things
# Make some changes
x <- list(maintainer_email = "heythere2@things.com")

# Then update the package
package_update(x, pkg$id)

## End(Not run)
```

---

ping

*Ping a CKAN server to test that it's up or down.*

---

### Description

Ping a CKAN server to test that it's up or down.

### Usage

```
ping(url = get_default_url(), key = get_default_key(), as = "logical", ...)
```

**Arguments**

url	Base url to use. Default: <a href="https://data.ontario.ca/">https://data.ontario.ca/</a> See also <a href="#">ckanr_setup</a> and <a href="#">get_default_url</a> .
key	A privileged CKAN API key, Default: your key set with <a href="#">ckanr_setup</a>
as	(character) One of list (default), table, or json. Parsing with table option uses <code>jsonlite::fromJSON(..., simplifyDataFrame = TRUE)</code> , which attempts to parse data to <code>data.frame</code> 's when possible, so the result can vary from a vector, list or <code>data.frame</code> . (required)
...	Curl args passed on to <a href="#">verb-POST</a> (optional)

**Examples**

```
## Not run:
ping()
ping(as = "json")

## End(Not run)
```

---

related_create	<i>Create a related item</i>
----------------	------------------------------

---

**Description**

Create a related item

**Usage**

```
related_create(
  id,
  title,
  type,
  description = NULL,
  related_id = NULL,
  related_url = NULL,
  image_url = NULL,
  url = get_default_url(),
  key = get_default_key(),
  as = "list",
  ...
)
```

**Arguments**

id	(character) id of package that the related item should be added to. This should be an alphanumeric string. Required.
title	(character) Title of the related item. Required.

type	(character) The type of the related item. One of API, application, idea, news article, paper, post or visualization. Required.
description	(character) description (optional). Optional
related_id	(character) An id to assign to the related item. If blank, an ID will be assigned for you. Optional
related_url	(character) A url to associated with the related item. Optional
image_url	(character) A url to associated image. Optional
url	Base url to use. Default: <a href="https://data.ontario.ca/">https://data.ontario.ca/</a> See also <a href="#">ckanr_setup</a> and <a href="#">get_default_url</a> .
key	A privileged CKAN API key, Default: your key set with <a href="#">ckanr_setup</a>
as	(character) One of list (default), table, or json. Parsing with table option uses <code>jsonlite::fromJSON(..., simplifyDataFrame = TRUE)</code> , which attempts to parse data to <code>data.frame</code> 's when possible, so the result can vary from a vector, list or <code>data.frame</code> . (required)
...	Curl args passed on to <a href="#">verb-POST</a> (optional)

### Examples

```
## Not run:
# Setup
ckanr_setup(url = "https://demo.ckan.org/", key = getOption("ckan_demo_key"))

# create a package
(res <- package_create("hello-mars"))

# create a related item
related_create(res, title = "asfdaf", type = "idea")

# pipe operations together
package_create("foobbbbbarrrr") %>%
  related_create(title = "my resource",
                type = "visualization")

## End(Not run)
```

---

related_delete	<i>Delete a related item.</i>
----------------	-------------------------------

---

### Description

Delete a related item.

### Usage

```
related_delete(id, url = get_default_url(), key = get_default_key(), ...)
```

**Arguments**

id	(character) Resource identifier.
url	Base url to use. Default: <a href="https://data.ontario.ca">https://data.ontario.ca</a> See also <a href="#">ckanr_setup()</a> and <a href="#">get_default_url()</a> .
key	A privileged CKAN API key, Default: your key set with <a href="#">ckanr_setup</a>
...	Curl args passed on to <a href="#">crul::verb-POST</a> (optional)

**Examples**

```
## Not run:
# Setup
ckanr_setup(url = "https://demo.ckan.org/", key = getOption("ckan_demo_key"))

# create a package and a related item
res <- package_create("hello-venus2") %>%
  related_create(title = "my resource",
                type = "visualization")

# show the related item
related_delete(res)
## or with id itself:
## related_delete(res$id)

## End(Not run)
```

---

related\_list

*List related items*


---

**Description**

List related items

**Usage**

```
related_list(
  offset = 0,
  limit = 31,
  url = get_default_url(),
  key = get_default_key(),
  as = "list",
  ...
)
```

**Arguments**

offset	(numeric) Where to start getting activity items from (optional, default: 0)
limit	(numeric) The maximum number of activities to return (optional, default: 31)
url	Base url to use. Default: <a href="https://data.ontario.ca/">https://data.ontario.ca/</a> See also <a href="#">ckanr_setup</a> and <a href="#">get_default_url</a> .
key	A privileged CKAN API key, Default: your key set with <a href="#">ckanr_setup</a>
as	(character) One of list (default), table, or json. Parsing with table option uses <code>jsonlite::fromJSON(..., simplifyDataFrame = TRUE)</code> , which attempts to parse data to <code>data.frame</code> 's when possible, so the result can vary from a vector, list or <code>data.frame</code> . (required)
...	Curl args passed on to <code>verb-POST</code> (optional)

**Examples**

```
## Not run:
related_list()
related_list(as = 'json')
related_list(as = 'table')

## End(Not run)
```

---

related_show	<i>Show a related item</i>
--------------	----------------------------

---

**Description**

Show a related item

**Usage**

```
related_show(
  id,
  url = get_default_url(),
  key = get_default_key(),
  as = "list",
  ...
)
```

**Arguments**

id	(character) Related item identifier.
url	Base url to use. Default: <a href="https://data.ontario.ca/">https://data.ontario.ca/</a> See also <a href="#">ckanr_setup</a> and <a href="#">get_default_url</a> .
key	A privileged CKAN API key, Default: your key set with <a href="#">ckanr_setup</a>



as (character) One of list (default), table, or json. Parsing with table option uses `jsonlite::fromJSON(..., simplifyDataFrame = TRUE)`, which attempts to parse data to `data.frame`'s when possible, so the result can vary from a vector, list or `data.frame`. (required)

... Curl args passed on to `verb-POST` (optional)

### Details

By default the help and success slots are dropped, and only the result slot is returned. You can request raw json with `as = 'json'` then parse yourself to get the help slot.

### Examples

```
## Not run:
# Setup
ckanr_setup(url = "https://demo.ckan.org/", key = getOption("ckan_demo_key"))

# create a package and a related item
res <- package_create("hello-pluto2") %>%
  related_create(title = "my resource",
                type = "visualization")

# show the related item
related_show(res)
related_show(res$id)

# get data back in different formats
related_show(res, as = 'json')
related_show(res, as = 'table')

## End(Not run)
```

---

related_update	<i>Update a related item</i>
----------------	------------------------------

---

### Description

Update a related item

### Usage

```
related_update(
  id,
  title,
  type,
  description = NULL,
  related_id = NULL,
  related_url = NULL,
  image_url = NULL,
```

```

url = get_default_url(),
key = get_default_key(),
as = "list",
...
)

```

## Arguments

id	(character) id of related item to update. This should be an alphanumeric string. Required.
title	(character) Title of the related item. Required.
type	(character) The type of the related item. One of API, application, idea, news article, paper, post or visualization. Required.
description	(character) description (optional). Optional
related_id	(character) An id to assign to the related item. If blank, an ID will be assigned for you. Optional
related_url	(character) A url to associated with the related item. Optional
image_url	(character) A url to associated image. Optional
url	Base url to use. Default: <a href="https://data.ontario.ca/">https://data.ontario.ca/</a> See also <a href="#">ckanr_setup</a> and <a href="#">get_default_url</a> .
key	A privileged CKAN API key, Default: your key set with <a href="#">ckanr_setup</a>
as	(character) One of list (default), table, or json. Parsing with table option uses <code>jsonlite::fromJSON(..., simplifyDataFrame = TRUE)</code> , which attempts to parse data to <code>data.frame</code> 's when possible, so the result can vary from a vector, list or <code>data.frame</code> . (required)
...	Curl args passed on to <a href="#">verb-POST</a> (optional)

## Examples

```

## Not run:
# Setup
ckanr_setup(url = "https://demo.ckan.org/", key = getOption("ckan_demo_key"))

# create a package and related item
res <- package_create("hello-saturn2") %>%
  related_create(title = "my resource",
                type = "visualization")

# update the related item
related_update(res, title = "her resource", type = "idea")

## End(Not run)

```

---

resource_create	<i>Create a resource</i>
-----------------	--------------------------

---

### Description

Create a resource

### Usage

```
resource_create(
  package_id = NULL,
  rcurl = NULL,
  revision_id = NULL,
  description = NULL,
  format = NULL,
  hash = NULL,
  name = NULL,
  resource_type = NULL,
  mimetype = NULL,
  mimetype_inner = NULL,
  webstore_url = NULL,
  cache_url = NULL,
  size = NULL,
  created = NULL,
  last_modified = NULL,
  cache_last_updated = NULL,
  webstore_last_updated = NULL,
  upload = NULL,
  extras = NULL,
  http_method = "GET",
  url = get_default_url(),
  key = get_default_key(),
  as = "list",
  ...
)
```

### Arguments

package_id	(character) id of package that the resource should be added to. This should be an alphanumeric string. Required.
rcurl	(character) url of resource. Required.
revision_id	(character) revision id (optional)
description	(character) description (optional). Required.
format	(character) format (optional)
hash	(character) hash (optional)

name	(character) name (optional). Required.
resource_type	(character) resource type (optional)
mimetype	(character) mime type (optional)
mimetype_inner	(character) mime type inner (optional)
webstore_url	(character) webstore url (optional)
cache_url	(character) cache url(optional)
size	(integer) size (optional)
created	(character) iso date string (optional)
last_modified	(character) iso date string (optional)
cache_last_updated	(character) iso date string (optional)
webstore_last_updated	(character) iso date string (optional)
upload	(character) A path to a local file (optional)
extras	(list) - the resources' extra metadata fields (optional)
http_method	(character) which HTTP method (verb) to use; one of "GET" or "POST". Default: "GET"
url	Base url to use. Default: <a href="https://data.ontario.ca/">https://data.ontario.ca/</a> See also <a href="#">ckanr_setup</a> and <a href="#">get_default_url</a> .
key	A privileged CKAN API key, Default: your key set with <a href="#">ckanr_setup</a>
as	(character) One of list (default), table, or json. Parsing with table option uses <code>jsonlite::fromJSON(..., simplifyDataFrame = TRUE)</code> , which attempts to parse data to <code>data.frame</code> 's when possible, so the result can vary from a vector, list or <code>data.frame</code> . (required)
...	Curl args passed on to <a href="#">verb-POST</a> (optional)

## Examples

```
## Not run:
# Setup
ckanr_setup(url = "https://demo.ckan.org/",
  key = getOption("ckan_demo_key"))

# create a package
(res <- package_create("foobarrrr", author="Jane Doe"))

# then create a resource
file <- system.file("examples", "actinidiaceae.csv", package = "ckanr")
(xx <- resource_create(package_id = res$id,
  description = "my resource",
  name = "bears",
  upload = file,
  extras = list(species = "grizzly"),
  rcurl = "http://google.com"
))
```

```

package_create("foobbbbbarrrr") %>%
  resource_create(description = "my resource",
                 name = "bearsareus",
                 upload = file,
                 extras = list(my_extra = "some value"),
                 rcurl = "http://google.com")

## End(Not run)

```

---

resource_delete	<i>Delete a resource.</i>
-----------------	---------------------------

---

### Description

Delete a resource.

### Usage

```
resource_delete(id, url = get_default_url(), key = get_default_key(), ...)
```

### Arguments

id	(character) Resource identifier.
url	Base url to use. Default: <a href="https://data.ontario.ca">https://data.ontario.ca</a> See also <a href="#">ckanr_setup()</a> and <a href="#">get_default_url()</a> .
key	A privileged CKAN API key, Default: your key set with <a href="#">ckanr_setup</a>
...	Curl args passed on to <a href="#">crul::verb-POST</a> (optional)

### Examples

```

## Not run:
# Setup
ckanr_setup(url = "https://demo.ckan.org/", key = Sys.getenv("CKAN_DEMO_KEY"))

# create a package
(res <- package_create("yellow9"))

# then create a resource
file <- system.file("examples", "actinidiaceae.csv", package = "ckanr")
(xx <- resource_create(res,
                     description = "my resource",
                     name = "bears",
                     upload = file,
                     rcurl = "http://google.com"
                    ))

# delete the resource
resource_delete(xx)

```

```
## End(Not run)
```

---

```
resource_patch      Update a resource's metadata
```

---

## Description

Update a resource's metadata

## Usage

```
resource_patch(
  x,
  id,
  url = get_default_url(),
  key = get_default_key(),
  as = "list",
  ...
)
```

## Arguments

x	(list) A list with key-value pairs
id	(character) Resource ID to update (required)
url	Base url to use. Default: <a href="https://data.ontario.ca/">https://data.ontario.ca/</a> See also <a href="#">ckanr_setup</a> and <a href="#">get_default_url</a> .
key	A privileged CKAN API key, Default: your key set with <a href="#">ckanr_setup</a>
as	(character) One of list (default), table, or json. Parsing with table option uses <code>jsonlite::fromJSON(..., simplifyDataFrame = TRUE)</code> , which attempts to parse data to <code>data.frame</code> 's when possible, so the result can vary from a vector, list or <code>data.frame</code> . (required)
...	Curl args passed on to <a href="#">verb-POST</a> (optional)

## Examples

```
## Not run:
# Setup
ckanr_setup(url = "https://demo.ckan.org", key = getOption("ckan_demo_key"))

# create a package
(res <- package_create("twist", author="Alexandria"))

# then create a resource
file <- system.file("examples", "actinidiaceae.csv", package = "ckanr")
(xx <- resource_create(package_id = res$id, description = "my resource"))
```

```

# Get a resource
res <- resource_show(xx$id)
res$description

# Make some changes
x <- list(description = "My newer description")
z <- resource_patch(x, id = res)
z$description

# Add an extra key:value pair
extra <- list("extra_key" = "my special value")
zz <- resource_patch(extra, id = res)
zz$extra_key

## End(Not run)

```

---

resource_search	<i>Search for resources.</i>
-----------------	------------------------------

---

### Description

Search for resources.

### Usage

```

resource_search(
  q,
  sort = NULL,
  offset = NULL,
  limit = NULL,
  url = get_default_url(),
  key = get_default_key(),
  as = "list",
  ...
)

```

### Arguments

q	Query terms. It is a string of the form <code>field:term</code> or a vector/list of strings, each of the same form. Within each string, <code>field</code> is a field or extra field on the Resource domain object. If <code>field</code> is hash, then an attempt is made to match the term as a <i>prefix</i> of the <code>Resource.hash</code> field. If <code>field</code> is an extra field, then an attempt is made to match against the extra fields stored against the Resource.
sort	Field to sort on. You can specify ascending (e.g., <code>score desc</code> ) or descending (e.g., <code>score asc</code> ), sort by two fields (e.g., <code>score desc, price asc</code> ), or sort by a function (e.g., <code>sum(x_f, y_f) desc</code> , which sorts by the sum of <code>x_f</code> and <code>y_f</code> in a descending order).
offset	Record to start at, default to beginning.

limit	Number of records to return.
url	Base url to use. Default: <a href="https://data.ontario.ca/">https://data.ontario.ca/</a> See also <a href="#">ckanr_setup</a> and <a href="#">get_default_url</a> .
key	A privileged CKAN API key, Default: your key set with <a href="#">ckanr_setup</a>
as	(character) One of list (default), table, or json. Parsing with table option uses <code>jsonlite::fromJSON(..., simplifyDataFrame = TRUE)</code> , which attempts to parse data to <code>data.frame</code> 's when possible, so the result can vary from a vector, list or <code>data.frame</code> . (required)
...	Curl args passed on to <code>verb-POST</code> (optional)

### Examples

```
## Not run:
resource_search(q = 'name:data')
resource_search(q = 'name:data', as = 'json')
resource_search(q = 'name:data', as = 'table')
resource_search(q = 'name:data', limit = 2, as = 'table')
resource_search(q=c("description:encoded", "name:No.2"),url='demo.ckan.org')

## End(Not run)
```

---

resource_show	<i>Show a resource.</i>
---------------	-------------------------

---

### Description

Show a resource.

### Usage

```
resource_show(
  id,
  url = get_default_url(),
  key = get_default_key(),
  as = "list",
  ...
)
```

### Arguments

id	(character) Resource identifier.
url	Base url to use. Default: <a href="https://data.ontario.ca/">https://data.ontario.ca/</a> See also <a href="#">ckanr_setup</a> and <a href="#">get_default_url</a> .
key	A privileged CKAN API key, Default: your key set with <a href="#">ckanr_setup</a>



as (character) One of list (default), table, or json. Parsing with table option uses `jsonlite::fromJSON(..., simplifyDataFrame = TRUE)`, which attempts to parse data to `data.frame`'s when possible, so the result can vary from a vector, list or `data.frame`. (required)

... Curl args passed on to `verb-POST` (optional)

### Examples

```
## Not run:
# Setup
ckanr_setup(url = "https://demo.ckan.org/",
key = Sys.getenv("CKAN_DEMO_KEY"))

# create a package
(res <- package_create("yellow7"))

# then create a resource
file <- system.file("examples", "actinidiaceae.csv", package = "ckanr")
(xx <- resource_create(package_id = res$id,
description = "my resource",
name = "bears",
upload = file,
rcurl = "http://google.com"
))

# show the resource
resource_show(xx$id)

# eg. from the NHM CKAN store
resource_show(id = "05ff2255-c38a-40c9-b657-4ccb55ab2feb",
url = "http://data.nhm.ac.uk")

## End(Not run)
```

---

resource\_update

*Update a resource*

---

### Description

This function can be used to update a resource's file attachment and "extra" metadata fields. Any update will also set the metadata key "last\_updated". Other metadata, such as name or description, are not updated.

The new file must exist on a local path. R objects have to be written to a file, e.g. using `tempfile()` - see example.

For convenience, CKAN base url and API key default to the global options, which are set by `ckanr_setup`.

**Usage**

```
resource_update(
  id,
  path = NULL,
  extras = list(),
  url = get_default_url(),
  key = get_default_key(),
  as = "list",
  ...
)
```

**Arguments**

id	(character) Resource ID to update (required)
path	(character) Local path of the file to upload (optional)
extras	(list) - the resources' extra metadata fields (optional)
url	Base url to use. Default: <a href="https://data.ontario.ca/">https://data.ontario.ca/</a> See also <a href="#">ckanr_setup</a> and <a href="#">get_default_url</a> .
key	A privileged CKAN API key, Default: your key set with <a href="#">ckanr_setup</a>
as	(character) One of list (default), table, or json. Parsing with table option uses <code>jsonlite::fromJSON(..., simplifyDataFrame = TRUE)</code> , which attempts to parse data to <code>data.frame</code> 's when possible, so the result can vary from a vector, list or <code>data.frame</code> . (required)
...	Curl args passed on to <a href="#">verb-POST</a> (optional)

**Value**

The HTTP response from CKAN, formatted as list (default), table, or JSON.

**References**

[http://docs.ckan.org/en/latest/api/index.html#ckan.logic.action.create.resource\\_create](http://docs.ckan.org/en/latest/api/index.html#ckan.logic.action.create.resource_create)

**Examples**

```
## Not run:
ckanr_setup(url = "https://demo.ckan.org/", key = getOption("ckan_demo_key"))

# Get file
path <- system.file("examples", "actinidiaceae.csv", package = "ckanr")

# Create package, then a resource within that package
(res <- package_create("newpackage10"))
(xx <- resource_create(package_id = res$id,
  description = "my resource",
  name = "bears",
  upload = path,
  rcurl = "http://google.com"
```

```

))

# Modify dataset, here lowercase strings in one column
dat <- read.csv(path, stringsAsFactors = FALSE)
dat$Family <- tolower(dat$Family)
newpath <- tempfile(fileext = ".csv")
write.csv(dat, file = newpath, row.names = FALSE)

# Upload modified dataset
## Directly from output of resource_create
resource_update(xx, path=newpath)

## or from the resource id
resource_update(xx$id, path=newpath)

## optionally include extra tags
resource_update(xx$id, path=newpath,
               extras = list(some="metadata"))

# Update a resource's extra tags
## add extra tags without uploading a new file
resource_update(id,
               extras = list(some="metadata"))

## or remove all extra tags
resource_update(id, extras = list())

#####
# Using default settings
ckanr_setup(url = "http://demo.ckan.org/", key = "my-demo-ckan-org-api-key")
path <- system.file("examples", "actinidiaceae.csv", package = "ckanr")
resource_update(id="an-existing-resource-id", path = path)

# Using an R object written to a tempfile, and implicit CKAN URL and API key
write.csv(data <- installed.packages(), path <- tempfile(fileext = ".csv"))
ckanr_setup(url = "http://demo.ckan.org/", key = "my-demo-ckan-org-api-key")
resource_update(id="an-existing-resource-id", path = path)

# Testing: see ?ckanr_setup to set default test CKAN url, key, package id
ckanr_setup(test_url = "http://my-ckan.org/",
            test_key = "my-ckan-api-key",
            test_did = "an-existing-package-id",
            test_rid = "an-existing-resource-id")
resource_update(id = get_test_rid(),
               path = system.file("examples",
                                "actinidiaceae.csv",
                                package = "ckanr"),
               key = get_test_key(),
               url = get_test_url())

# other file formats
## html
path <- system.file("examples", "mapbox.html", package = "ckanr")

```

```

# Create package, then a resource within that package
(res <- package_create("mappkg"))
(xx <- resource_create(package_id = res$id,
                      description = "a map, yay",
                      name = "mapyay",
                      upload = path,
                      rcurl = "http://google.com"
))
browseURL(xx$url)

# Modify dataset, here lowercase strings in one column
dat <- readLines(path)
dat <- sub("-111.06", "-115.06", dat)
newpath <- tempfile(fileext = ".html")
cat(dat, file = newpath, sep = "\n")

# Upload modified dataset
## Directly from output of resource_create
(xxx <- resource_update(xx, path=newpath))
browseURL(xxx$url)

## End(Not run)

```

---

```
revision_list
```

```
Return a list of the IDs of the site's revisions.
```

---

## Description

Return a list of the IDs of the site's revisions.

## Usage

```

revision_list(
  url = get_default_url(),
  key = get_default_key(),
  as = "list",
  ...
)

```

## Arguments

url	Base url to use. Default: <a href="https://data.ontario.ca/">https://data.ontario.ca/</a> See also <a href="#">ckanr_setup</a> and <a href="#">get_default_url</a> .
key	A privileged CKAN API key, Default: your key set with <a href="#">ckanr_setup</a>
as	(character) One of list (default), table, or json. Parsing with table option uses <code>jsonlite::fromJSON(..., simplifyDataFrame = TRUE)</code> , which attempts to parse data to <code>data.frame</code> 's when possible, so the result can vary from a vector, list or <code>data.frame</code> . (required)
...	Curl args passed on to <a href="#">verb-POST</a> (optional)

## Examples

```
## Not run:
revision_list()
revision_list(as = "table")
revision_list(as = "json")

## End(Not run)
```

---

servers

*CKAN server URLs and other info*

---

## Description

CKAN server URLs and other info

## Usage

```
servers()
```

## Details

Comes from the links at <https://ckan.org/about/instances/>

There were a number of other URLs for CKAN instances in the CKAN URL above, but some sites are now gone completely, or if they do exist, I can't figure out how to get access to the CKAN API on their instance.

## Examples

```
## Not run:
servers()
ckan_info(servers()[5])

# what version is each CKAN server running
out <- lapply(servers()[1:6], function(w) {
  cat(w, sep='\n')
  ckan_info(w)
})
vapply(out, "[[", "", "ckan_version")

## End(Not run)
```

---

src_ckan	<i>Connect to CKAN with dplyr</i>
----------	-----------------------------------

---

### Description

Use `src_ckan` to connect to an existing CKAN instance and `tbl` to connect to tables within that CKAN based on the DataStore Data API.

### Usage

```
src_ckan(url)
```

### Arguments

`url` the url of the CKAN instance

### Examples

```
## Not run:
library("dplyr")

# To connect to a CKAN instance first create a src:
my_ckan <- src_ckan("http://demo.ckan.org")

# List all tables in the CKAN instance
db_list_tables(my_ckan$con)

# Then reference a tbl within that src
my_tbl <- tbl(src = my_ckan, name = "44d7de5f-7029-4f3a-a812-d7a70895da7d")

# You can use the dplyr verbs with my_tbl. For example:
dplyr::filter(my_tbl, GABARITO == "C")

## End(Not run)
```

---

tag_create	<i>Create a tag</i>
------------	---------------------

---

### Description

IMPORTANT: You must be a sysadmin to create vocabulary tags.

**Usage**

```

tag_create(
  name,
  vocabulary_id,
  url = get_default_url(),
  key = get_default_key(),
  as = "list",
  ...
)

```

**Arguments**

name	(character) The name for the new tag, a string between 2 and 100 characters long containing only alphanumeric characters and -, _ and ., e.g. 'Jazz'
vocabulary_id	(character) The id of the vocabulary that the new tag should be added to, e.g. the id of vocabulary 'Genre'
url	Base url to use. Default: <a href="https://data.ontario.ca/">https://data.ontario.ca/</a> See also <a href="#">ckanr_setup</a> and <a href="#">get_default_url</a> .
key	A privileged CKAN API key, Default: your key set with <a href="#">ckanr_setup</a>
as	(character) One of list (default), table, or json. Parsing with table option uses <code>jsonlite::fromJSON(..., simplifyDataFrame = TRUE)</code> , which attempts to parse data to <code>data.frame</code> 's when possible, so the result can vary from a vector, list or <code>data.frame</code> . (required)
...	Curl args passed on to <a href="#">verb-POST</a> (optional)

**Examples**

```

## Not run:
ckanr_setup(url = "https://demo.ckan.org/",
  key = Sys.getenv("CKAN_DEMO_KEY"))
tag_create(name = "TestTag1", vocabulary_id = "Testing1")

## End(Not run)

```

---

tag\_list

*List tags.*


---

**Description**

List tags.

**Usage**

```

tag_list(
  query = NULL,
  vocabulary_id = NULL,
  all_fields = FALSE,
  url = get_default_url(),
  key = get_default_key(),
  as = "list",
  ...
)

```

**Arguments**

query	(character) A tag name query to search for, if given only tags whose names contain this string will be returned
vocabulary_id	(character) The id or name of a vocabulary, if given, only tags that belong to this vocabulary will be returned
all_fields	(logical) Return full tag dictionaries instead of just names. Default: FALSE
url	Base url to use. Default: <a href="https://data.ontario.ca/">https://data.ontario.ca/</a> See also <a href="#">ckanr_setup</a> and <a href="#">get_default_url</a> .
key	A privileged CKAN API key, Default: your key set with <a href="#">ckanr_setup</a>
as	(character) One of list (default), table, or json. Parsing with table option uses <code>jsonlite::fromJSON(..., simplifyDataFrame = TRUE)</code> , which attempts to parse data to <code>data.frame</code> 's when possible, so the result can vary from a vector, list or <code>data.frame</code> . (required)
...	Curl args passed on to <a href="#">verb-POST</a> (optional)

**Examples**

```

## Not run:
# list all tags
tag_list()

# search for a specific tag
tag_list(query = 'aviation')

# all fields
tag_list(all_fields = TRUE)

# give back different data formats
tag_list('aviation', as = 'json')
tag_list('aviation', as = 'table')

## End(Not run)

```



---

tag_search	<i>Search tags.</i>
------------	---------------------

---

### Description

Search tags.

### Usage

```
tag_search(
  query = NULL,
  vocabulary_id = NULL,
  offset = 0,
  limit = 31,
  url = get_default_url(),
  key = get_default_key(),
  as = "list",
  ...
)
```

### Arguments

query	(character) A tag name query to search for, if given only tags whose names contain this string will be returned; one or more search strings
vocabulary_id	(character) The id or name of a vocabulary, if give only tags that belong to this vocabulary will be returned
offset	(numeric) Where to start getting activity items from (optional, default: 0)
limit	(numeric) The maximum number of activities to return (optional, default: 31)
url	Base url to use. Default: <a href="https://data.ontario.ca/">https://data.ontario.ca/</a> See also <a href="#">ckanr_setup</a> and <a href="#">get_default_url</a> .
key	A privileged CKAN API key, Default: your key set with <a href="#">ckanr_setup</a>
as	(character) One of list (default), table, or json. Parsing with table option uses <code>jsonlite::fromJSON(..., simplifyDataFrame = TRUE)</code> , which attempts to parse data to <code>data.frame</code> 's when possible, so the result can vary from a vector, list or <code>data.frame</code> . (required)
...	Curl args passed on to <a href="#">verb-POST</a> (optional)

### Examples

```
## Not run:
tag_search(query = 'ta')
tag_search(query = c('ta', 'al'))

# different formats back
tag_search(query = 'ta', as = 'json')
```

```
tag_search(query = 'ta', as = 'table')

## End(Not run)
```

---

tag_show	<i>Show a tag.</i>
----------	--------------------

---

## Description

Show a tag.

## Usage

```
tag_show(
  id,
  include_datasets = FALSE,
  url = get_default_url(),
  key = get_default_key(),
  as = "list",
  ...
)
```

## Arguments

id	(character) The name or id of the tag
include_datasets	include a list of up to 1000 of the tag's datasets. Limit 1000 datasets, use <a href="#">package_search()</a> for more. (optional, default: FALSE)
url	Base url to use. Default: <a href="https://data.ontario.ca/">https://data.ontario.ca/</a> See also <a href="#">ckanr_setup</a> and <a href="#">get_default_url</a> .
key	A privileged CKAN API key, Default: your key set with <a href="#">ckanr_setup</a>
as	(character) One of list (default), table, or json. Parsing with table option uses <code>jsonlite::fromJSON(..., simplifyDataFrame = TRUE)</code> , which attempts to parse data to data.frame's when possible, so the result can vary from a vector, list or data.frame. (required)
...	Curl args passed on to <a href="#">verb-POST</a> (optional)

## Examples

```
## Not run:
# get tags with tag_list()
tags <- tag_list()
tags[[30]]$id

# show a tag
(x <- tag_show(tags[[30]]$id))
```

```
# give back different data formats
tag_show(tags[[30]]$id, as = 'json')
tag_show(tags[[30]]$id, as = 'table')

## End(Not run)
```

---

user\_activity\_list      *Return a list of a user's activities*

---

## Description

Return a list of a user's activities

## Usage

```
user_activity_list(
  id,
  offset = 0,
  limit = 31,
  url = get_default_url(),
  key = get_default_key(),
  as = "list",
  ...
)
```

## Arguments

id	(character) User identifier.
offset	(numeric) Where to start getting activity items from (optional, default: 0)
limit	(numeric) The maximum number of activities to return (optional, default: 31)
url	Base url to use. Default: <a href="https://data.ontario.ca/">https://data.ontario.ca/</a> See also <a href="#">ckanr_setup</a> and <a href="#">get_default_url</a> .
key	A privileged CKAN API key, Default: your key set with <a href="#">ckanr_setup</a>
as	(character) One of list (default), table, or json. Parsing with table option uses <code>jsonlite::fromJSON(..., simplifyDataFrame = TRUE)</code> , which attempts to parse data to <code>data.frame</code> 's when possible, so the result can vary from a vector, list or <code>data.frame</code> . (required)
...	Curl args passed on to <a href="#">verb-POST</a> (optional)

## Examples

```
## Not run:
# Setup
ckanr_setup(url = "https://demo.ckan.org/",
key = getOption("ckan_demo_key"))
```

```

# list package activity
user_activity_list('sckottie')

# input a ckan_user object
(x <- user_show('sckottie'))
user_activity_list(x)

# output different data formats
user_activity_list(x, as = "table")
user_activity_list(x, as = "json")

## End(Not run)

```

---

user\_create

*Create a user.*


---

## Description

Create a user.

## Usage

```

user_create(
  name,
  email,
  password,
  id = NULL,
  fullname = NULL,
  about = NULL,
  openid = NULL,
  url = get_default_url(),
  key = get_default_key(),
  as = "list",
  ...
)

```

## Arguments

name	(character) the name of the new user, a string between 2 and 100 characters in length, containing only lowercase alphanumeric characters, - and _ (required)
email	(character) the email address for the new user (required)
password	(character) the password of the new user, a string of at least 4 characters (required)
id	(character) the id of the new user (optional)
fullname	(character) user full name
about	(character) a description of the new user (optional)

openid	(character) an openid (optional)
url	Base url to use. Default: <a href="https://data.ontario.ca/">https://data.ontario.ca/</a> See also <a href="#">ckanr_setup</a> and <a href="#">get_default_url</a> .
key	A privileged CKAN API key, Default: your key set with <a href="#">ckanr_setup</a>
as	(character) One of list (default), table, or json. Parsing with table option uses <code>jsonlite::fromJSON(..., simplifyDataFrame = TRUE)</code> , which attempts to parse data to <code>data.frame</code> 's when possible, so the result can vary from a vector, list or <code>data.frame</code> . (required)
...	Curl args passed on to <a href="#">verb-POST</a> (optional)

## References

[http://docs.ckan.org/en/latest/api/index.html#ckan.logic.action.create.user\\_create](http://docs.ckan.org/en/latest/api/index.html#ckan.logic.action.create.user_create)

## Examples

```
## Not run:
# Setup
ckanr_setup(url = "https://data-demo.dpaw.wa.gov.au",
  key = "824e7c50-9577-4bfa-bf32-246ebed1a8a2")

# create a user
user_create(name = 'stacy', email = "stacy@aaaaa.com",
  password = "helloworld")

## End(Not run)
```

---

user_delete	<i>Delete a user.</i>
-------------	-----------------------

---

## Description

Delete a user.

## Usage

```
user_delete(
  id,
  url = get_default_url(),
  key = get_default_key(),
  as = "list",
  ...
)
```

**Arguments**

id	(character) the id of the new user (required)
url	Base url to use. Default: <a href="https://data.ontario.ca/">https://data.ontario.ca/</a> See also <a href="#">ckanr_setup</a> and <a href="#">get_default_url</a> .
key	A privileged CKAN API key, Default: your key set with <a href="#">ckanr_setup</a>
as	(character) One of list (default), table, or json. Parsing with table option uses <code>jsonlite::fromJSON(..., simplifyDataFrame = TRUE)</code> , which attempts to parse data to <code>data.frame</code> 's when possible, so the result can vary from a vector, list or <code>data.frame</code> . (required)
...	Curl args passed on to <a href="#">verb-POST</a> (optional)

**References**

[http://docs.ckan.org/en/latest/api/index.html#ckan.logic.action.delete.user\\_delete](http://docs.ckan.org/en/latest/api/index.html#ckan.logic.action.delete.user_delete)

**Examples**

```
## Not run:
# Setup
ckanr_setup(url = "https://data-demo.dpaw.wa.gov.au",
key = "824e7c50-9577-4bfa-bf32-246ebed1a8a2")

# create a user
res <- user_delete(name = 'stacy', email = "stacy@aaaaa.com",
password = "helloworld")

# then, delete a user
user_delete(id = "stacy")

## End(Not run)
```

---

user\_followee\_count *Return a a user's follower count*

---

**Description**

Return a a user's follower count

**Usage**

```
user_followee_count(
  id,
  url = get_default_url(),
  key = get_default_key(),
  as = "list",
  ...
)
```

**Arguments**

id	(character) User identifier.
url	Base url to use. Default: <a href="https://data.ontario.ca/">https://data.ontario.ca/</a> See also <a href="#">ckanr_setup</a> and <a href="#">get_default_url</a> .
key	A privileged CKAN API key, Default: your key set with <a href="#">ckanr_setup</a>
as	(character) One of list (default), table, or json. Parsing with table option uses <code>jsonlite::fromJSON(..., simplifyDataFrame = TRUE)</code> , which attempts to parse data to <code>data.frame</code> 's when possible, so the result can vary from a vector, list or <code>data.frame</code> . (required)
...	Curl args passed on to <a href="#">verb-POST</a> (optional)

**Examples**

```
## Not run:
# Setup
ckanr_setup(url = "https://demo.ckan.org/", key = getOption("ckan_demo_key"))

# list package activity
user_followee_count('sckottie')

# input a ckan_user object
(x <- user_show('sckottie'))
user_followee_count(x)

# output different data formats
user_followee_count(x, as = "table")
user_followee_count(x, as = "json")

## End(Not run)
```

---

user\_follower\_count    *Return a a user's follower count*

---

**Description**

Return a a user's follower count

**Usage**

```
user_follower_count(
  id,
  url = get_default_url(),
  key = get_default_key(),
  as = "list",
  ...
)
```

**Arguments**

id	(character) User identifier.
url	Base url to use. Default: <code>https://data.ontario.ca/</code> See also <code>ckanr_setup</code> and <code>get_default_url</code> .
key	A privileged CKAN API key, Default: your key set with <code>ckanr_setup</code>
as	(character) One of list (default), table, or json. Parsing with table option uses <code>jsonlite::fromJSON(..., simplifyDataFrame = TRUE)</code> , which attempts to parse data to <code>data.frame</code> 's when possible, so the result can vary from a vector, list or <code>data.frame</code> . (required)
...	Curl args passed on to <code>verb-POST</code> (optional)

**Examples**

```
## Not run:
# Setup
ckanr_setup(url = "https://demo.ckan.org/", key = getOption("ckan_demo_key"))

# list package activity
user_follower_count('sckottie')

# input a ckan_user object
(x <- user_show('sckottie'))
user_follower_count(x)

# output different data formats
user_follower_count(x, as = "table")
user_follower_count(x, as = "json")

## End(Not run)
```

---

`user_follower_list`      *Return a a user's follower count*

---

**Description**

Return a a user's follower count

**Usage**

```
user_follower_list(
  id,
  url = get_default_url(),
  key = get_default_key(),
  as = "list",
  ...
)
```



**Arguments**

id	(character) User identifier.
url	Base url to use. Default: <a href="https://data.ontario.ca/">https://data.ontario.ca/</a> See also <a href="#">ckanr_setup</a> and <a href="#">get_default_url</a> .
key	A privileged CKAN API key, Default: your key set with <a href="#">ckanr_setup</a>
as	(character) One of list (default), table, or json. Parsing with table option uses <code>jsonlite::fromJSON(..., simplifyDataFrame = TRUE)</code> , which attempts to parse data to <code>data.frame</code> 's when possible, so the result can vary from a vector, list or <code>data.frame</code> . (required)
...	Curl args passed on to <a href="#">verb-POST</a> (optional)

**Examples**

```
## Not run:
# Setup
ckanr_setup(url = "https://demo.ckan.org/", key = getOption("ckan_demo_key"))

# list package activity
user_follower_list('sckottie')

# input a ckan_user object
(x <- user_show('sckottie'))
user_follower_list(x)

# output different data formats
user_follower_list(x, as = "table")
user_follower_list(x, as = "json")

## End(Not run)
```

---

user_list	<i>Return a list of the site's user accounts.</i>
-----------	---

---

**Description**

Return a list of the site's user accounts.

**Usage**

```
user_list(
  q = NULL,
  order_by = NULL,
  url = get_default_url(),
  key = get_default_key(),
  as = "list",
  ...
)
```

**Arguments**

q	(character) Restrict the users returned to those whose names contain a string
order_by	(character) Which field to sort the list by (optional, default: 'name')
url	Base url to use. Default: <a href="https://data.ontario.ca/">https://data.ontario.ca/</a> See also <a href="#">ckanr_setup</a> and <a href="#">get_default_url</a> .
key	A privileged CKAN API key, Default: your key set with <a href="#">ckanr_setup</a>
as	(character) One of list (default), table, or json. Parsing with table option uses <code>jsonlite::fromJSON(..., simplifyDataFrame = TRUE)</code> , which attempts to parse data to <code>data.frame</code> 's when possible, so the result can vary from a vector, list or <code>data.frame</code> . (required)
...	Curl args passed on to <code>verb-POST</code> (optional)

**Examples**

```
## Not run:
# all users
user_list()

# search for a user
user_list(q = "j")

# different data formats
user_list(q = "j", as = "table")
user_list(q = "j", as = "json")

## End(Not run)
```

---

user\_show

*Show a user.*


---

**Description**

Show a user.

**Usage**

```
user_show(
  id,
  user_obj = NULL,
  include_datasets = FALSE,
  include_num_followers = FALSE,
  url = get_default_url(),
  key = get_default_key(),
  as = "list",
  ...
)
```

**Arguments**

id	(character) Package identifier.
user_obj	(user dictionary) The user dictionary of the user (optional)
include_datasets	(logical) Include a list of datasets the user has created. If it is the same user or a sysadmin requesting, it includes datasets that are draft or private. (optional, default:False, limit:50)
include_num_followers	(logical) Include the number of followers the user has (optional, default:False)
url	Base url to use. Default: <a href="https://data.ontario.ca/">https://data.ontario.ca/</a> See also <a href="#">ckanr_setup</a> and <a href="#">get_default_url</a> .
key	A privileged CKAN API key, Default: your key set with <a href="#">ckanr_setup</a>
as	(character) One of list (default), table, or json. Parsing with table option uses <code>jsonlite::fromJSON(..., simplifyDataFrame = TRUE)</code> , which attempts to parse data to <code>data.frame</code> 's when possible, so the result can vary from a vector, list or <code>data.frame</code> . (required)
...	Curl args passed on to <code>verb-POST</code> (optional)

**Examples**

```
## Not run:
# Setup
ckanr_setup(url = "https://demo.ckan.org/", key = getOption("ckan_demo_key"))

# show user
user_show('sckotttie')

# include datasets
user_show('sckotttie', include_datasets = TRUE)

# include datasets
user_show('sckotttie', include_num_followers = TRUE)

## End(Not run)
```

# Index

- \* **ckanr settings**
  - ckanr\_settings, 11
- \* **package**
  - ckanr-package, 3
  
- as.ckan\_group, 5
- as.ckan\_organization, 5
- as.ckan\_package, 6
- as.ckan\_related, 7
- as.ckan\_resource, 8
- as.ckan\_tag, 9
- as.ckan\_user, 9
  
- changes, 10
- ckan\_classes, 14
- ckan\_fetch, 15
- ckan\_info, 17
- ckan\_version(ckan\_info), 17
- ckan\_version(), 49
- ckanr(ckanr-package), 3
- ckanr-deprecated, 11
- ckanr-package, 3
- ckanr\_settings, 11
- ckanr\_setup, 10, 11, 12, 18, 19, 21, 22, 24–30, 32–39, 42–47, 49, 50, 52–56, 58, 60–62, 64, 66, 68, 71–75, 77–83
- ckanr\_setup(), 3, 12, 13, 18, 27, 43, 55, 61
- crul::proxy(), 13
- crul::verb-GET, 18
- crul::verb-POST, 27, 43, 55, 61
  
- dashboard\_activity\_list, 18
- dashboard\_count, 19
- dplyr-interface(src\_ckan), 70
- ds\_create, 20
- ds\_create(), 4
- ds\_create\_dataset, 21
- ds\_create\_dataset(), 4, 11
- ds\_search, 23
- ds\_search(), 4
  
- ds\_search\_sql, 24
- ds\_search\_sql(), 4
  
- fromJSON, 15
  
- get\_default\_key(ckanr\_settings), 11
- get\_default\_key(), 3, 12
- get\_default\_url, 10, 18, 19, 21, 22, 24–26, 28–30, 32–39, 42, 44–47, 49, 50, 52–54, 56, 58, 60, 62, 64, 66, 68, 71–75, 77–83
- get\_default\_url(ckanr\_settings), 11
- get\_default\_url(), 12, 18, 27, 43, 55, 61
- get\_test\_behaviour(ckanr\_settings), 11
- get\_test\_did(ckanr\_settings), 11
- get\_test\_did(), 12
- get\_test\_gid(ckanr\_settings), 11
- get\_test\_gid(), 12
- get\_test\_key(ckanr\_settings), 11
- get\_test\_key(), 12
- get\_test\_oid(ckanr\_settings), 11
- get\_test\_rid(ckanr\_settings), 11
- get\_test\_rid(), 12
- get\_test\_url(ckanr\_settings), 11
- get\_test\_url(), 12
- group\_create, 25
- group\_delete, 27
- group\_list, 28
- group\_list(), 4, 26, 42
- group\_patch, 29
- group\_show, 30
- group\_show(), 5
- group\_update, 31
  
- is.ckan\_group(as.ckan\_group), 5
- is.ckan\_organization(as.ckan\_organization), 5
- is.ckan\_package(as.ckan\_package), 6
- is.ckan\_related(as.ckan\_related), 7
- is.ckan\_resource(as.ckan\_resource), 8

`is.ckan_tag (as.ckan_tag)`, 9  
`is.ckan_user (as.ckan_user)`, 9

`license_list`, 32

`organization_create`, 33  
`organization_create()`, 4  
`organization_delete`, 35  
`organization_list`, 36  
`organization_list()`, 4, 42  
`organization_purge`, 37  
`organization_show`, 38  
`organization_show()`, 4, 6

`package_activity_list`, 39  
`package_create`, 40  
`package_create()`, 4  
`package_delete`, 42  
`package_list`, 43  
`package_list_current`, 44  
`package_patch`, 45  
`package_revision_list`, 46  
`package_search`, 48  
`package_search()`, 74  
`package_show`, 50  
`package_show()`, 6  
`package_update`, 51  
`ping`, 52

`read.csv`, 15  
`read.csv()`, 4  
`read.table`, 15  
`read_excel`, 15  
`read_html`, 15  
`read_xml`, 15

`related_create`, 53  
`related_delete`, 54  
`related_list`, 55  
`related_show`, 56  
`related_show()`, 7  
`related_update`, 57

`resource_create`, 59  
`resource_create()`, 4, 11, 20, 41  
`resource_delete`, 61  
`resource_patch`, 62  
`resource_search`, 63  
`resource_show`, 64  
`resource_show()`, 8  
`resource_update`, 65

`revision_list`, 68

`servers`, 69  
`servers()`, 4  
`src_ckan`, 70  
`st_read`, 15

`tag_create`, 70  
`tag_create()`, 41  
`tag_list`, 71  
`tag_list()`, 4  
`tag_search`, 73  
`tag_show`, 74  
`tag_show()`, 9

`user_activity_list`, 75  
`user_create`, 76  
`user_delete`, 77  
`user_followee_count`, 78  
`user_follower_count`, 79  
`user_follower_list`, 80  
`user_list`, 81  
`user_list()`, 4  
`user_show`, 82  
`user_show()`, 10