

Package: natserv (via r-universe)

August 7, 2026

Title 'NatureServe' Interface

Description Interface to 'NatureServe'

(<https://www.natureserve.org/>). Includes methods to get data, image metadata, search taxonomic names, and make maps.

Version 1.0.0.91

License MIT + file LICENSE

URL <https://docs.ropensci.org/natserv/>,
<https://github.com/ropensci/natserv>

BugReports <https://github.com/ropensci/natserv/issues>

LazyData true

VignetteBuilder knitr

Language en-US

Encoding UTF-8

Roxygen list(markdown = TRUE)

Depends R(>= 3.2.1)

Imports crul (>= 0.7.0), jsonlite, tibble

Suggests knitr, rmarkdown, testthat, vcr

X-schema.org-applicationCategory Taxonomy

X-schema.org-keywords taxonomy, species, API, web-services,
NatureServe, metadata, maps

X-schema.org-isPartOf <https://ropensci.org>

Config/roxygen2/version 8.1.0

Config/pak/sysreqs libssl-dev

Repository <https://ropensci.r-universe.dev>

Date/Publication 2026-08-06 18:03:37 UTC

RemoteUrl <https://github.com/ropensci/natserv>

RemoteRef master

RemoteSha 6e46addf9f51bf34388595ac4227337db3cf53f2

Contents

nat_states	2
ns_altid	2
ns_ecohier	3
ns_export	4
ns_id	5
ns_search_comb	6
ns_search_eco	7
ns_search_spp	9

Index	11
-------	----

nat_states	<i>A data.frame with 49 rows and 2 columns</i>
------------	--

Description

- state (character) state 2 letter abbreviation
- state_name (character) state full name

ns_altid	<i>Get taxon by uid, id, or elCode</i>
----------	--

Description

Get taxon by uid, id, or elCode

Usage

```
ns_altid(uid = NULL, id = NULL, el_code = NULL, ...)
```

Arguments

uid	(character) A NatureServe taxon id (The taxon’s Element Global UID)
id	The primary key value (ELEMENT_GLOBAL_ID) of the record within Central Biotics
el_code	The Biotics Element Code (ELCODE_BCD) of the record
...	Curl options passed on to verb-GET

Details

see https://explorer.natureserve.org/api-docs/#_taxon_data_model for details on the response data

Value

A list with lots of elements

References

<https://explorer.natureserve.org/api-docs/>

Examples

```
## Not run:
ns_altid(uid = "ELEMENT_GLOBAL.2.154701")
ns_altid(id = "154701")
ns_altid(el_code = "PDRAN0F010")

## End(Not run)
```

ns_ecohier

Get a summary of the upper level hierarchy for an Ecosystem record

Description

Get a summary of the upper level hierarchy for an Ecosystem record

Usage

```
ns_ecohier(uid, ...)
```

Arguments

uid	(character) A NatureServe taxon id (The taxon's Element Global UID)
...	Curl options passed on to verb-GET

Details

see https://explorer.natureserve.org/api-docs/#_taxon_data_model for details on the response data

Value

A list with lots of elements

References

<https://explorer.natureserve.org/api-docs/>

Examples

```
## Not run:
ns_ecohier("ELEMENT_GLOBAL.2.683060")

## End(Not run)
```

ns_export

*Search exports***Description**

Search exports

Usage

```

ns_export(
  text = NULL,
  text_adv = NULL,
  status = NULL,
  location = NULL,
  record_type = NULL,
  record_subtype = NULL,
  modified_since = NULL,
  format = "json",
  lang = "en",
  ...
)

ns_export_status(id, ...)

```

Arguments

text	(character) basic text search, equivalent to text_adv with matchAgainst="allNames" and operator="similarTo"
text_adv	(list) advanced search, must specify the following three elements: searchToken, matchAgainst, and operator. see https://explorer.natureserve.org/api-docs/#_advanced_text_search_parameters
status	(character) conservation status, one of G1, G2, G3, G4, G5, GH, GX, GNR, GNA, GU. case insensitive
location	(list) location, country and sub-country. specify either nation OR nation and subnation. each expects a two-letter ISO code
record_type	(character) limit results by record type, one of "species" or "ecosystem"
record_subtype	(character) limit results by record sub-type, one of: "class", "subclass", "formation", "division", "macrogroup", "group", "alliance", "association", "terrestrial_ecological_system"
modified_since	(character) search for records modified since a given time. value must be a date and time with a UTC offset in ISO 8601 format. optional
format	(character) output format, one of "json" or "xlsx"
lang	(character) language, one of "en", "es", or "fr"
...	Curl options passed on to verb-GET
id	(character) a job id, from output of ns_export()

Value

ns_export() returns a single character string (a job id) ns_export_status() returns a list of metadata concerning the status of the export

References

<https://explorer.natureserve.org/api-docs/>

Examples

```
## Not run:
x <- ns_export(text = "robin")
res <- ns_export_status(x)
str(res)
res$state
res$data$errorMessage
res$data$url

w <- ns_export(text_adv = list(searchToken = "western",
  matchAgainst="allScientificNames", operator="startsWith"))
m <- ns_export_status(w)
head(jsonlite::fromJSON(m$data$url))

## End(Not run)
```

ns_id

Get taxon by uid

Description

Get taxon by uid

Usage

```
ns_id(uid, ...)
```

Arguments

uid (character) A NatureServe taxon id (The taxon's Element Global UID). required.
 ... Curl options passed on to [verb-GET](#)

Details

see https://explorer.natureserve.org/api-docs/#_taxon_data_model for details on the response data

Value

A list with lots of elements

References

<https://explorer.natureserve.org/api-docs/>

Examples

```
## Not run:
ns_id("ELEMENT_GLOBAL.2.154701")

## End(Not run)
```

ns_search_comb	<i>Combined search</i>
----------------	------------------------

Description

Combined search

Usage

```
ns_search_comb(
  text = NULL,
  text_adv = NULL,
  status = NULL,
  location = NULL,
  record_type = NULL,
  record_subtype = NULL,
  modified_since = NULL,
  page = NULL,
  per_page = NULL,
  ...
)
```

Arguments

- text (character) basic text search, equivalent to text_adv with matchAgainst="allNames" and operator="similarTo"
- text_adv (list) advanced search, must specify the following three elements: searchToken, matchAgainst, and operator. see https://explorer.natureserve.org/api-docs/#_advanced_text_search_parameters
- status (character) conservation status, one of G1, G2, G3, G4, G5, GH, GX, GNR, GNA, GU. case insensitive
- location (list) location, country and sub-country. specify either nation OR nation and subnation. each expects a two-letter ISO code
- record_type (character) limit results by record type, one of "species" or "ecosystem"
- record_subtype (character) limit results by record sub-type, one of: "class", "subclass", "formation", "division", "macrogroup", "group", "alliance", "association", "terrestrial_ecological_system"

modified_since (character) search for records modified since a given time. value must be a date and time with a UTC offset in ISO 8601 format. optional

page (integer) Zero-indexed page number; default: 0. optional

per_page (integer) Records per page; default: 20. optional

... Curl options passed on to [verb-GET](#)

References

<https://explorer.natureserve.org/api-docs/>

See Also

Other search: [ns_search_eco\(\)](#), [ns_search_spp\(\)](#)

Examples

```
## Not run:
ns_search_comb(text = "robin")
ns_search_comb(text_adv = list(searchToken = "western",
  matchAgainst="allScientificNames", operator="startsWith"))
ns_search_comb(status = "G1")
ns_search_comb(location = list(nation = "US"))
ns_search_comb(location = list(nation = "US", subnation = "VA"))
ns_search_comb(record_type = "species")
ns_search_comb(record_subtype = "macrogroup")
ns_search_comb(modified_since = "2020-04-30T00:00:00+0000")
ns_search_comb(page = 0, per_page = 2)

## End(Not run)
```

ns_search_eco	<i>Ecosystem search</i>
---------------	-------------------------

Description

Ecosystem search

Usage

```
ns_search_eco(
  text = NULL,
  text_adv = NULL,
  status = NULL,
  location = NULL,
  ecosystem_taxonomy = NULL,
  record_subtype = NULL,
  modified_since = NULL,
  page = NULL,
```

```

    per_page = NULL,
    ...
)

```

Arguments

text	(character) basic text search, equivalent to text_adv with matchAgainst="allNames" and operator="similarTo"
text_adv	(list) advanced search, must specify the following three elements: searchToken, matchAgainst, and operator. see https://explorer.natureserve.org/api-docs/#_advanced_text_search_parameters
status	(character) conservation status, one of G1, G2, G3, G4, G5, GH, GX, GNR, GNA, GU. case insensitive
location	(list) location, country and sub-country. specify either nation OR nation and subnation. each expects a two-letter ISO code
ecosystem_taxonomy	(character) the classification code of the higher level (ancestor) ecosystem. E.g.'s: "1" (Class code), "1.B" (Subclass code), "1.B.2" (Formation code), "1.B.2.Nd" (Division code), "M886" (Macrogroup key), "G206" (Group key), "A3328" (Alliance Key)
record_subtype	(character) limit results by record sub-type, one of: "class", "subclass", "formation", "division", "macrogroup", "group", "alliance", "association", "terrestrial_ecological_system"
modified_since	(character) search for records modified since a given time. value must be a date and time with a UTC offset in ISO 8601 format. optional
page	(integer) Zero-indexed page number; default: 0. optional
per_page	(integer) Records per page; default: 20. optional
...	Curl options passed on to verb-GET

References

<https://explorer.natureserve.org/api-docs/>

See Also

Other search: [ns_search_comb\(\)](#), [ns_search_spp\(\)](#)

Examples

```

## Not run:
ns_search_eco(text = "robin")
ns_search_eco(text_adv = list(searchToken = "bird",
  matchAgainst = "allNames", operator="similarTo"))
ns_search_eco(status = "G1")
ns_search_eco(location = list(nation = "US"))
ns_search_eco(location = list(nation = "US", subnation = "VA"))
ns_search_eco(ecosystem_taxonomy = "M067")
ns_search_eco(record_subtype = "macrogroup")
ns_search_eco(modified_since = "2020-04-30T00:00:00+0000")

```



```
ns_search_eco(page = 0, per_page = 2)

## End(Not run)
```

ns_search_spp

Species search

Description

Species search

Usage

```
ns_search_spp(
  text = NULL,
  text_adv = NULL,
  status = NULL,
  location = NULL,
  species_taxonomy = NULL,
  record_subtype = NULL,
  modified_since = NULL,
  page = NULL,
  per_page = NULL,
  ...
)
```

Arguments

text	(character) basic text search, equivalent to text_adv with matchAgainst="allNames" and operator="similarTo"
text_adv	(list) advanced search, must specify the following three elements: searchToken, matchAgainst, and operator. see https://explorer.natureserve.org/api-docs/#_advanced_text_search_parameters
status	(character) conservation status, one of G1, G2, G3, G4, G5, GH, GX, GNR, GNA, GU. case insensitive
location	(list) location, country and sub-country. specify either nation OR nation and subnation. each expects a two-letter ISO code
species_taxonomy	(list) species taxonomy. either a list with level and scientificTaxonomy (a scientific name), or with just informalTaxonomy (a vernacular name). possible level values: "kingdom", "phylum", "class", "order", "family", "genus"
record_subtype	(character) limit results by record sub-type, one of: "class", "subclass", "formation", "division", "macrogroup", "group", "alliance", "association", "terrestrial_ecological_system"
modified_since	(character) search for records modified since a given time. value must be a date and time with a UTC offset in ISO 8601 format. optional

page	(integer) Zero-indexed page number; default: 0. optional
per_page	(integer) Records per page; default: 20. optional
...	Curl options passed on to verb-GET

References

<https://explorer.natureserve.org/api-docs/>

See Also

Other search: [ns_search_comb\(\)](#), [ns_search_eco\(\)](#)

Examples

```
## Not run:
ns_search_spp(text = "robin")
ns_search_spp(text_adv = list(searchToken = "bird",
  matchAgainst = "allNames", operator="similarTo"))
ns_search_spp(status = "G1")
ns_search_spp(location = list(nation = "US"))
ns_search_spp(location = list(nation = "US", subnation = "VA"))
ns_search_spp(species_taxonomy = list(scientificTaxonomy = "Animalia", level = "kingdom"))
ns_search_spp(species_taxonomy = list(informalTaxonomy = "birds"))
ns_search_spp(record_subtype = "macrogroup")
ns_search_spp(modified_since = "2020-04-30T00:00:00+0000")
ns_search_spp(page = 0, per_page = 2)

## End(Not run)
```

Index

* **data**

nat_states, [2](#)

* **search**

ns_search_comb, [6](#)

ns_search_eco, [7](#)

ns_search_spp, [9](#)

nat_states, [2](#)

ns_altid, [2](#)

ns_ecohier, [3](#)

ns_export, [4](#)

ns_export_status (ns_export), [4](#)

ns_id, [5](#)

ns_search_comb, [6](#)

ns_search_comb(), [8](#), [10](#)

ns_search_eco, [7](#)

ns_search_eco(), [7](#), [10](#)

ns_search_spp, [9](#)

ns_search_spp(), [7](#), [8](#)