

# Package: repometrics (via r-universe)

September 3, 2026

**Title** Metrics for Your Code Repository

**Version** 0.2.1.089

**Description** Metrics for your code repository. Call one function to generate an interactive dashboard displaying the state of your code.

**License** GPL-3

**URL** <https://docs.ropensci.org/repometrics/>,  
<https://github.com/ropensci-review-tools/repometrics>

**BugReports** <https://github.com/ropensci-review-tools/repometrics/issues>

**Depends** R (>= 4.1)

**Imports** checkmate, cli, dplyr, foghorn, fs, gert, gh, git2r, httr2, memoise, pbapply, pkgcheck, pkgstats, zoo

**Suggests** brio, desc, DT, httptest2, jsonlite, knitr, pkgmatch, quarto, readr, rmarkdown, testthat (>= 3.0.0), tidyr, visNetwork, withr

**Remotes** ropensci-review-tools/pkgcheck,  
ropensci-review-tools/pkgmatch, ropensci-review-tools/pkgstats

**Config/testthat/edition** 3

**Config/ropensci/maintainer** staff

**Encoding** UTF-8

**Language** en-GB

**Roxygen** list(markdown = TRUE)

**RoxygenNote** 7.3.3

**VignetteBuilder** knitr

**Config/pak/sysreqs**  
cmake git libglpk-dev make libgit2-dev libuv1-dev libxml2-dev libssl-dev libx11-dev

**Repository** <https://ropensci.r-universe.dev>

**Date/Publication** 2026-06-25 14:31:45 UTC

**RemoteUrl** <https://github.com/ropensci-review-tools/repometrics>

**RemoteRef** main

**RemoteSha** d0ff2e8cdaf04d97b05a495a8af82bc5ace10260

## Contents

|                                 |   |
|---------------------------------|---|
| repo_pkgstats_history . . . . . | 2 |
| repometrics_dashboard . . . . . | 3 |
| repometrics_data . . . . .      | 3 |
| repometrics_data_repo . . . . . | 5 |
| repometrics_data_user . . . . . | 5 |
| rm_metrics_list . . . . .       | 6 |

|              |          |
|--------------|----------|
| <b>Index</b> | <b>8</b> |
|--------------|----------|

---

repo\_pkgstats\_history Apply **pkgstats** across the git history of a package

---

### Description

Apply **pkgstats** across the git history of a package

### Usage

```
repo_pkgstats_history(path, date_interval = "month", num_cores = -1L)
```

### Arguments

|               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|---------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| path          | Path to local repository containing an R package.                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| date_interval | Interval at which to analyse package statistics, with options of "day", "week", "month", or "year". The last commit for each period is chosen.                                                                                                                                                                                                                                                                                                                                            |
| num_cores     | Number of cores to use in multi-core processing. Has no effect on Windows operating systems, on which calculations are always single-core only. Negative values are subtracted from number of available cores, determined as <code>parallel::detectCores()</code> , so default of <code>num_cores = -1L</code> uses <code>detectCores() - 1L</code> . Positive values use precisely that number, restricted to maximum available cores, and a value of zero will use all available cores. |

### Value

NULL if path is not an R package, or if no **pkgstats** results are able to be extracted. Otherwise, a list of three items:

- desc\_data Containing data from DESCRIPTION files, along with data on numbers of functions.
- loc Containing data on "lines-of-code" for all languages and sub-directories within package.
- stats Containing statistics on (mean, medium, and sum) of various properties of each function in package.

### See Also

Other data: [repometrics\\_data\(\)](#), [repometrics\\_data\\_repo\(\)](#), [repometrics\\_data\\_user\(\)](#)

---

`repometrics_dashboard` *Start quarto dashboard with results of main [repometrics\\_data\\_repo](#) function.*

---

## Description

Start quarto dashboard with results of main [repometrics\\_data\\_repo](#) function.

## Usage

```
repometrics_dashboard(  
  data,  
  action = "preview",  
  ctb_threshold = NULL,  
  max_ctbs = NULL  
)
```

## Arguments

|                            |                                                                                                                                                                                                                                       |
|----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>data</code>          | Data on repository and all contributors as returned from <a href="#">repometrics_data</a> function applied to one package.                                                                                                            |
| <code>action</code>        | One of "preview", to start and open a live preview of the dashboard website, or "render" to render a static version without previewing or opening.                                                                                    |
| <code>ctb_threshold</code> | An optional single numeric value between 0 and 1. If specified, contributions are arranged in cumulative order, and the contributor data reduced to only those who contribute to this proportion of all contributions.                |
| <code>max_ctbs</code>      | Optional maximum number of contributors to be included. This is an alternative way to reduce number of contributors presented in dashboard, and may only be specified if <code>ctb_threshold</code> is left at default value of NULL. |

## Value

(Invisibly) Path to main "index.html" document of quarto site. Note that the site must be served with `action = "preview"`, and will not work by simply opening this "index.html" file.

---

`repometrics_data` *Collate 'repometrics' data for a local R package.*

---

## Description

This function collates all data for a local R package or repository needed to create a dashboard with the [repometrics\\_dashboard](#) function. It combines data from both the [repometrics\\_data\\_repo](#) and [repometrics\\_data\\_user](#) functions.

**Usage**

```
repometrics_data(
  path,
  date_interval = "month",
  num_cores = -1L,
  end_date = Sys.Date(),
  nyears = 1
)
```

**Arguments**

|                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|----------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>path</code>          | Path to local repository containing an R package.                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <code>date_interval</code> | Interval at which to analyse package statistics, with options of "day", "week", "month", or "year". The last commit for each period is chosen.                                                                                                                                                                                                                                                                                                                                            |
| <code>num_cores</code>     | Number of cores to use in multi-core processing. Has no effect on Windows operating systems, on which calculations are always single-core only. Negative values are subtracted from number of available cores, determined as <code>parallel::detectCores()</code> , so default of <code>num_cores = -1L</code> uses <code>detectCores() - 1L</code> . Positive values use precisely that number, restricted to maximum available cores, and a value of zero will use all available cores. |
| <code>end_date</code>      | Parameter used in some aspects of resultant data to limit the end date of data collection. Defaults to <code>Sys.Date()</code> .                                                                                                                                                                                                                                                                                                                                                          |
| <code>nyears</code>        | Parameter $\leq 1$ determining fraction of a year over which data up until <code>end_date</code> are collected.                                                                                                                                                                                                                                                                                                                                                                           |

**Value**

A list of five items:

1. "pkgstats" containing statistics on the historical development of package code, derived from the **pkgstats** package;
2. "rm" containing data from GitHub on the repository, including data on contributors, issues, pull requests, and people watching and starring the repository.
3. "contributors" as a named list of data on every individual contributor to the repository, whether by code contributions or GitHub issues or discussions.
4. "rm\_metrics" as a list of values for all CHAOSS metrics defined in the output of [rm\\_metrics\\_list](#).
5. "rm\_models" as a list of values for CHAOSS models, derived from aggregating various metrics.

**See Also**

Other data: [repo\\_pkgstats\\_history\(\)](#), [repometrics\\_data\\_repo\(\)](#), [repometrics\\_data\\_user\(\)](#)

---

repometrics\_data\_repo *Collate code and repository data for a local R package.*

---

### Description

This forms part of the data collated by the main [repometrics\\_data](#) function, along with detailed data on individual contributors extracted by the [repometrics\\_data\\_user](#) function.

### Usage

```
repometrics_data_repo(path, date_interval = "month", num_cores = -1L)
```

### Arguments

|               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|---------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| path          | Path to local repository containing an R package.                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| date_interval | Interval at which to analyse package statistics, with options of "day", "week", "month", or "year". The last commit for each period is chosen.                                                                                                                                                                                                                                                                                                                                            |
| num_cores     | Number of cores to use in multi-core processing. Has no effect on Windows operating systems, on which calculations are always single-core only. Negative values are subtracted from number of available cores, determined as <code>parallel::detectCores()</code> , so default of <code>num_cores = -1L</code> uses <code>detectCores() - 1L</code> . Positive values use precisely that number, restricted to maximum available cores, and a value of zero will use all available cores. |

### Value

A list of two items:

1. "pkgstats" Containing summary data from apply `pkgstats` routines across the git history of the repository.
2. "rm" Containing data used to derive "CHAOSS metrics", primarily from GitHub data.

### See Also

Other data: [repo\\_pkgstats\\_history\(\)](#), [repometrics\\_data\(\)](#), [repometrics\\_data\\_user\(\)](#)

---

repometrics\_data\_user *Extract and combine data on all contributors to a repository.*

---

### Description

This forms part of the data collated by the main [repometrics\\_data](#) function, along with data on repository structure and historical developed extracted by the [repometrics\\_data\\_repo](#) function.

**Usage**

```
repometrics_data_user(
  login,
  end_date = Sys.Date(),
  nyears = 1,
  n_per_page = 100
)
```

**Arguments**

|            |                                                                                                                     |
|------------|---------------------------------------------------------------------------------------------------------------------|
| login      | GitHub login of user                                                                                                |
| end_date   | Parameter used in some aspects of resultant data to limit the end date of data collection. Defaults to Sys.Date (). |
| nyears     | Parameter <= 1 determining fraction of a year over which data up until end_date are collected.                      |
| n_per_page | Number of items per page to pass to GitHub GraphQL API requests. This should never need to be changed.              |

**Value**

A list of the following data.frame objects:

1. commit\_cmt with details of commits made on commits
2. commits with summaries of all repositories to which user made commits
3. followers A list of followers of specified user
4. following A list of other people who nominated user is following
5. general with some general information about specified user
6. issue\_cmts with information on all issue comments made by user
7. issues with information on all issues opened by user

**See Also**

Other data: [repo\\_pkgstats\\_history\(\)](#), [repometrics\\_data\(\)](#), [repometrics\\_data\\_repo\(\)](#)

---

rm\_metrics\_list

---

*List all implemented CHAOSS metrics*


---

**Description**

This function returns a list of internal functions defined within the 'repometrics' package. These internal functions are not intended to be called directly, rather this list is provided for information only, to enable users to know which metrics are implemented.

**Usage**

```
rm_metrics_list()
```

**Value**

A data.frame with two columns:

1. "fn\_names", with the internal function names of all implemented CHAOSS metrics.
2. "url", with the URL to the CHAOSS community web page describing that metric.

**Note**

Metrics have been adapted in this package, and so may not precisely reflect the descriptions provided in the CHAOSS community web pages linked to in the URLs from this function. Adaptations have in particular been implemented to align metrics with their usage in aggregate "models".

**Examples**

```
metrics <- rm_metrics_list ()
```

# Index

- \* **auxiliary**
  - rm\_metrics\_list, [6](#)
- \* **dashboard**
  - repometrics\_dashboard, [3](#)
- \* **data**
  - repo\_pkgstats\_history, [2](#)
  - repometrics\_data, [3](#)
  - repometrics\_data\_repo, [5](#)
  - repometrics\_data\_user, [5](#)

repo\_pkgstats\_history, [2](#), [4-6](#)  
repometrics\_dashboard, [3](#), [3](#)  
repometrics\_data, [2](#), [3](#), [3](#), [5](#), [6](#)  
repometrics\_data\_repo, [2-4](#), [5](#), [5](#), [6](#)  
repometrics\_data\_user, [2-4](#), [5](#), [5](#)  
rm\_metrics\_list, [4](#), [6](#)