

Package: smapr (via r-universe)

November 27, 2024

Type Package

Title Acquisition and Processing of NASA Soil Moisture Active-Passive (SMAP) Data

Version 0.2.1

Depends R (>= 3.2.5)

Imports hdf5r, httr (>= 1.1.0), methods, rappdirs (>= 0.3.1), rvest, terra, xml2

Maintainer Maxwell Joseph <maxwell.b.joseph@colorado.edu>

Description Facilitates programmatic access to NASA Soil Moisture Active Passive (SMAP) data with R. It includes functions to search for, acquire, and extract SMAP data.

License GPL-3

LazyData TRUE

RoxygenNote 7.2.3

Suggests knitr, rmarkdown, roxygen2, testthat, utils, covr

VignetteBuilder knitr

URL <https://docs.ropensci.org/smapr>, <https://github.com/ropensci/smapr>

BugReports <https://github.com/ropensci/smapr/issues>

Encoding UTF-8

Config/pak/sysreqs libgdal-dev gdal-bin libgeos-dev libhdf5-dev libicu-dev libxml2-dev libssl-dev libproj-dev libsqlite3-dev

Repository <https://ropensci.r-universe.dev>

RemoteUrl <https://github.com/ropensci/smapr>

RemoteRef master

RemoteSha 6274022ddcfa4e109679df5b71c32de104ae06e3

Contents

smmapr-package	2
download_smmap	2
extract_smmap	3
find_smmap	4
list_smmap	5
set_smmap_credentials	6

Index	7
--------------	----------

smmapr-package	<i>smmapr: A package for acquisition and processing of NASA SMAP data.</i>
----------------	--

Description

The smmapr package provides a means to discover, acquire, and process NASA Soil Moisture Active Passive (SMAP) data.

Author(s)

Max Joseph <maxwell.b.joseph@colorado.edu>

download_smmap	<i>Download SMAP data</i>
----------------	---------------------------

Description

This function downloads SMAP data in HDF5 format.

Usage

```
download_smmap(files, directory = NULL, overwrite = TRUE, verbose = TRUE)
```

Arguments

files	A data.frame produced by find_smmap() that specifies data files to download.
directory	A local directory path in which to save data, specified as a character string. If left as NULL, data are stored in a user's cache directory.
overwrite	TRUE or FALSE: should existing data files be overwritten?
verbose	TRUE or FALSE: should messages be printed to indicate that files are being downloaded?

Details

This function requires a username and password from NASA's Earthdata portal. If you have an Earthdata username and password, pass them in using the `set_smap_credentials()` function.

If you do not yet have a username and password, register for one here: <https://urs.earthdata.nasa.gov/>

Value

Returns a `data.frame` that appends a column called `local_dir` to the input data frame, which consists of a character vector specifying the local directory containing the downloaded files.

Examples

```
## Not run:
files <- find_smap(id = "SPL4SMGP", dates = "2015-03-31", version = 4)
# files[1, ] refers to the first available data file
downloads <- download_smap(files[1, ])

## End(Not run)
```

extract_smap	<i>Extracts contents of SMAP data</i>
--------------	---------------------------------------

Description

Extracts datasets from SMAP data files.

Usage

```
extract_smap(data, name)
```

Arguments

<code>data</code>	A data frame produced by <code>download_smap()</code> that specifies input files from which to extract data.
<code>name</code>	The path in the HDF5 file pointing to data to extract.

Details

The arguments `group` and `dataset` must refer specifically the group and name within group for the input file, such as can be obtained with `list_smap()`. This function will extract that particular dataset, returning a Raster object.

Value

Returns a `SpatRaster` object.

Examples

```
## Not run:
files <- find_smmap(id = "SPL4SMGP", dates = "2015-03-31", version = 4)
downloads <- download_smmap(files[1, ])
sm_raster <- extract_smmap(downloads, name = '/Geophysical_Data/sm_surface')

## End(Not run)
```

find_smmap

Find SMAP data

Description

This function searches for SMAP data on a specific date, returning a `data.frame` describing available data.

Usage

```
find_smmap(id, dates, version)
```

Arguments

<code>id</code>	A character string that refers to a specific SMAP dataset, e.g., "SPL4SMGP" for SMAP L4 Global 3-hourly 9 km Surface and Rootzone Soil Moisture Geophysical Data. See "Details" for a list of supported data types and their associated id codes.
<code>dates</code>	An object of class <code>Date</code> or a character string formatted as <code>To search for one specific date, this can be a Date object of length one. To search over a time interval, it can be a multi-element object of class Date such as produced by seq.Date.</code>
<code>version</code>	Which data version would you like to search for? Version information for each data product can be found at https://nsidc.org/data/smmap/data_versions

Details

There are many SMAP data products that can be accessed with this function. Currently, `smmap` supports level 3 and level 4 data products, each of which has an associated Data Set ID which is specified by the `id` argument, described at <https://nsidc.org/data/smmap/smmap-data.html> and summarized below:

SPL2SMAP_S SMAP/Sentinel-1 Radiometer/Radar Soil Moisture

SPL3FTA Radar Northern Hemisphere Daily Freeze/Thaw State

SPL3SMA Radar Global Daily Soil Moisture

SPL3SMP Radiometer Global Soil Moisture

SPL3SMAP Radar/Radiometer Global Soil Moisture

SPL4SMAU Surface/Rootzone Soil Moisture Analysis Update
SPL4SMGP Surface/Rootzone Soil Moisture Geophysical Data
SPL4SMLM Surface/Rootzone Soil Moisture Land Model Constants
SPL4CMDL Carbon Net Ecosystem Exchange

This function requires a username and password from NASA's Earthdata portal. If you have an Earthdata username and password, pass them in using the `set_smap_credentials()` function.

If you do not yet have a username and password, register for one here: <https://urs.earthdata.nasa.gov/>

Value

A data.frame with the names of the data files, the remote directory, and the date.

Examples

```
## Not run:
# looking for data on one day:
find_smap(id = "SPL4SMGP", dates = "2015-03-31", version = 4)

# searching across a date range
start_date <- as.Date("2015-03-31")
end_date <- as.Date("2015-04-02")
date_sequence <- seq(start_date, end_date, by = 1)
find_smap(id = "SPL4SMGP", dates = date_sequence, version = 4)

## End(Not run)
```

list_smap	<i>Lists the contents of SMAP data files</i>
-----------	--

Description

This function returns a list of the contents of SMAP data files.

Usage

```
list_smap(files, all = TRUE)
```

Arguments

files A data.frame produced by `download_smap()` that specifies input data files.
all If TRUE a longer, more detailed list of information on each entry is provided.

Value

Returns a list of data.frame objects that list the contents of each data file in files.

Examples

```
## Not run:
files <- find_smap(id = "SPL4SMGP", dates = "2015-03-31", version = 4)
files <- download_smap(files[1, ])
list_smap(files)
list_smap(files, all = TRUE)

## End(Not run)
```

set_smap_credentials *Set credentials for NASA's Earthdata portal*

Description

To use smapr, users need to provide NASA Earthdata portal credentials. This function allows users to interactively set these credentials via the user's Earthdata username and password.

Usage

```
set_smap_credentials(username, password, save = TRUE, overwrite = FALSE)
```

Arguments

username	A character string of your Earthdata portal username
password	A character string of your Earthdata portal password
save	Logical: whether to save your credentials to your .Renviron file (e.g., ~/.Renviron). Previous Earthdata credentials will not be overwritten unless overwrite = TRUE.
overwrite	Logical: whether to overwrite previous Earthdata credentials in your .Renviron file (only applies when save = TRUE)

Details

If you do not yet have a username and password, register for one here: <https://urs.earthdata.nasa.gov/>
A warning: do not commit your username and password to a public repository! This function is meant to be used interactively, and not embedded within a script that you would share.

Value

A data.frame with the names of the data files, the remote directory, and the date.

Examples

```
## Not run:
set_smap_credentials('myusername', 'mypassword')

## End(Not run)
```

Index

* package

smapr-package, 2

download_smap, 2

extract_smap, 3

find_smap, 4

list_smap, 5

set_smap_credentials, 6

set_smap_credentials(), 3, 5

smapr-package, 2