

Package: unrtf (via r-universe)

September 5, 2026

Type Package

Title Extract Text from Rich Text Format (RTF) Documents

Version 1.4.9000

Description Wraps the 'unrtf' utility
<<https://www.gnu.org/software/unrtf/>> to extract text from RTF
files. Supports document conversion to HTML, LaTeX or plain
text. Output in HTML is recommended because 'unrtf' has limited
support for converting between character encodings.

License GPL-3

Encoding UTF-8

Imports sys (>= 2.0)

URL <https://docs.ropensci.org/unrtf/>
<https://ropensci.r-universe.dev/unrtf>

BugReports <https://github.com/ropensci/unrtf/issues>

RoxygenNote 7.3.3

Roxygen list(markdown = TRUE)

Repository <https://ropensci.r-universe.dev>

Date/Publication 2026-07-07 10:03:42 UTC

RemoteUrl <https://github.com/ropensci/unrtf>

RemoteRef main

RemoteSha a4e622e57e15ab243e9a796d50feed3799735176

Contents

unrtf	2
Index	3

`unrtf`*Convert rtf Documents*

Description

Converts an rtf document to html, text or latex. Output in html is recommended because `unrtf` has limited support for converting between character encodings which is problematic for non-ascii text.

Usage

```
unrtf(  
  file = NULL,  
  format = c("html", "text", "latex"),  
  verbose = FALSE,  
  conf_dir = NULL  
)
```

Arguments

<code>file</code>	path or url to the 'rtf' file
<code>format</code>	output format, must be "text", "html" or "latex"
<code>verbose</code>	print some output to stderr
<code>conf_dir</code>	use a custom dir with .conf files which serve as output templates.

Details

Output can be customized via a set of .conf files which serve as templates for the various formats. The default conf files are located in `system.file("share", package = "unrtf")`. To modify the output, copy these files to a custom location and set pass the directory as the `conf_dir` argument in `unrtf`.

Examples

```
library(unrtf)  
text <- unrtf("https://jeroen.github.io/files/sample.rtf", format = "text")  
html <- unrtf("https://jeroen.github.io/files/sample.rtf", format = "html")  
cat(text)
```

Index

unrtf, [2](#)